

ACRYLIC LATEX ENAMELIZED HOUSE PAINT, W2557

MSDS Number

BLZZM

National Stock Number

8010-00N024136

Product Name

ACRYLIC LATEX ENAMELIZED HOUSE PAINT, W2557

Manufacturer

AMERITONE PAINT CORP

Product Identification

Product ID:ACRYLIC LATEX ENAMELIZED HOUSE PAINT, W2557

MSDS Date:11/20/1987

FSC:8010

NIIN:00N024136

MSDS Number: BLZZM

Responsible Party

AMERITONE PAINT CORP

18414 S SANTA FE AVE

COMPTON , CA 90221

US

Emergency Phone: 213-639-6791

Info Phone: 213-639-6791

Cage: FO133

Contractor

AMERITONE PAINT CORP/COMPTON, CA 90221

190

LONG BEACH, CA 90801

US

310-639-6791

Cage: FO133

Ingredients

NO INGREDIENT FOR THIS FORMULATION_INGREDIENT

Hazards

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:ACUTE: INHAL: IRRITATION OF THE RESPIRATORY TRACT, HEADACHE, NAUSEA, DIZZINESS. SKIN/EYE: PRIMARY IRRITATION. CHRONIC: PROLONGED AND REPEATED BREATHING OF SPRAY MIST AND/OR SANDING DUST OVER A PERIOD OF YEARS MAY CAUSE DUST DISEASE OF THE LUNGS.

Explanation of Carcinogenicity:NOT RELEVANT

Effects of Overexposure:SEE HEALTH HAZARDS.

Medical Cond Aggravated by Exposure:NONE WHEN USED IN ACCORDANCE WITH SAFE HANDLING AND USE INFORMATION.

First Aid

First Aid:INHAL: REMOVE TO FRESH AIR. EYES: FLUSH IMMEDIATELY WITH

LARGE AMOUNTS OF WATER FOR AT LEAST 15 MINUTES. CONSULT A PHYSICIAN FOR MEDICAL TREATMENT. SKIN: REMOVE WITH SOAP AND WATER. REMOVE SOILED CLOTHING. INGEST: DRINK 1 OR 2 GLASSES OF WATER TO DILUTE. DO NOT INDUCE VOMITING. CONSULT PHYSICIAN IMMEDIATELY. TREAT SYMPTOMATICALLY.

Fire Fighting

Flash Point:NONE

Lower Limits:SEE INGRED

Extinguishing Media:CO₂, DRY CHEMICAL, FOAM OR OTHER NFPA APPROVED METHOD FOR TREATING CLASS B FIRE.

Fire Fighting Procedures:USE NIOSH/MSHA APPROVED SCBA & FULL PROTECTIVE EQUIPMENT. WATER SPRAY MAY BE INEFFECTIVE. IF H₂O IS USED, FOG NOZZLES ARE PREFERRED. IF EXPOSED TO FIRE/EXTREME HEAT, (SUPPLEMENTAL DATA)

Unusual Fire/Explosion Hazard:DUE TO PRESSURE BUILDUP CLOSED CONTAINERS EXPOSED TO EXTREME HEAT MAY EXPLODE. DURING EMERGENCY CONDITIONS, OVEREXPOSURE TO DECOMPOSITION PRODUCTS MAY CAUSE A HEALTH HAZARD. SYMPTOMS MAY NOT (SUPPLEMENTAL DATA)

Accidental Release

Spill Release Procedures:WASH WITH WATER. BEFORE ATTEMPTING CLEANUP, REFER TO HAZARD CAUTION INFORMATION IN MSDS FORM. CONTAIN SPILLED MATERIAL AND REMOVE WITH INERT ABSORBENT. STORE IN CLOSED CONTAINER UNTIL PROPERLY DISPOSED OF.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

Handling

Handling and Storage Precautions:STORE BELOW 110°F AND KEEP FROM FREEZING. KEEP CONTAINER CLOSED WHEN NOT IN USE. DO NOT REUSE EMPTY CONTAINERS.

Other Precautions:DO NOT TRANSFER CONTENTS TO BOTTLES OR OTHER UNLABELLED CONTAINERS. KEEP OUT OF REACH OF CHILDREN.

Exposure Controls

Respiratory Protection:DO NOT BREATH VAPOR/SPRAY/MIST/SANDING DUST. WHEN SPRAY APPLIED IN OUTDOOR/OPEN AREAS WITH UNRESTRICTED VENTS & DURING SANDING /GRINDING OPERATIONS, USE NIOSH/MSHA APPROVED MECHANICAL FILTER RESPIRATOR DESIGNED TO REMOVE SOLID AIRBORNE PARTICLES OF (CLASS 8)

Ventilation:USE ONLY WITH ADEQUATE VENT. PROVIDE GENERAL DILUTION/LOCAL EXHAUST VENT IN VOLUME & PATTERN TO KEEP CONTAMINANT AIR CONCENTRATION BELOW (SUPPLEMENTAL DATA)

Protective Gloves:IMPERVIOUS GLOVES .

Eye Protection:CHEMICAL WORKERS GOGGLES .

Other Protective Equipment:NONE REQUIRED.

Work Hygienic Practices:REMOVE AND WASH SOILED CLOTHING BEFORE REUSE. WASH HANDS BEFORE EATING, SMOKING OR USING THE WASHROOM.

Supplemental Safety and Health

FIRE FIGHT PROCEDURE: H₂O SHOULD BE USED TO COOL CLOSED CONTAINERS & PREVENT PRESSURE BUILDUP/POSSIBLE AUTO-IGNITION. EXPLOSION HAZARD:BE IMMEDIATELY APPARENT. OBTAIN MEDICAL ATTENTION. VENT:CURRENT APPLICATION SAFETY & HEALTH STANDARDS IN MIX, APPLICATION & CURING AREAS & TO REMOVE SANDING DUSTS OF DRIED COATING & DECOMPOSITION PRODUCT DURING WELDING & FLAME CUTTING ON SURFACES COATED WITH PRODUCT.

Chemical Properties

HCC:N1

Boiling Point:Boiling Point:212°F,100°C

Vapor Pressure:SEE INGREDIENTS

Vapor Density:HVR/AIR

Evaporation Rate & Reference:SLOWER THAN ETHER

Appearance and Odor:NONE SPECIFIED BY MANUFACTURER.

Percent Volatiles by Volume:65-70

Stability

Stability Indicator/Materials to Avoid:YES

NONE SPECIFIED BY MANUFACTURER.

Stability Condition to Avoid:NONE SPECIFIED BY MANUFACTURER.

Hazardous Decomposition Products:MAY CAUSE HAZARDOUS FUMES WHEN HEATED TO DECOMPOSITION. FUMES MAY CONTAIN CO, CO₂, NO_x.

Disposal

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS. INCINERATE ONLY IN APPROVED FACILITY. DO NOT INCINERATE CLOSED CONTAINERS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.