

ACRYLIC LATEX ENAMELIZED HOUSE PAINT, W2579

MSDS Number

BLZZR

National Stock Number

8010-00N024145

Product Name

ACRYLIC LATEX ENAMELIZED HOUSE PAINT, W2579

Manufacturer

AMERITONE PAINT CORP

Product Identification

Product ID:ACRYLIC LATEX ENAMELIZED HOUSE PAINT, W2579

MSDS Date:11/20/1987

FSC:8010

NIIN:00N024145

MSDS Number: BLZZR

Responsible Party

AMERITONE PAINT CORP

18414 S SANTA FE AVE

COMPTON , CA 90221

US

Emergency Phone: 213-639-6791

Info Phone: 213-639-6791

Cage: FO133

Contractor

AMERITONE PAINT CORP/COMPTON, CA 90221

190

LONG BEACH, CA 90801

US

310-639-6791

Cage: FO133

Ingredients

NO INGREDIENT FOR THIS FORMULATION_INGREDIENT

Hazards

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:ACUTE: INHAL: IRRITATION OF

RESPIRATORY TRACT: HEADACHE, NAUSEA, DIZZINESS. SKIN/EYE CONTACT:

PRIMARY IRRITATION. CHRONIC: PROLONGED/REPEATED BREATHING OF SPRAY

MIST &/OR SANDING DUST OVER A PERIOD OF YEARS MAY CAUSE DUST

DISEASE OF THE LUNGS.

Explanation of Carcinogenicity:NOT RELEVANT

Effects of Overexposure:SEE HEALTH HAZARDS.

Medical Cond Aggravated by Exposure:NONE WHEN USED IN ACCORDANCE

W/CONTROL MEASURES.

First Aid

First Aid:INHAL: REMOVE TO FRESH AIR. EYES: FLUSH IMMED W/LGE AMTS OF

WATER FOR AT LEAST 15 MIN. CONSULT MD FOR MED TREATMENT. SKIN: REMOVE W/SOAP & WATER. REMOVE SOILED CLTHG. INGEST: DRINK 1-2 GLASSES OF WATE R TO DILUTE. DO NOT INDUCE VOMITING. CONSULT MD IMMED. TREAT SYMPTOMATICALLY. DURING EMER CNDTNS, OVEREXP TO DECOMP PRODS MAY CAUSE HLTH HAZ. SYMPTOMS MAY NOT BE IMMED APPARENT. OBTAIN MED ATTN.

Fire Fighting

Flash Point:NONE
Lower Limits:SEE ING 2,4
Extinguishing Media:CO*2, DRY CHEMICAL, FOAM OR OTHER NFPA APPROVED METHOD FOR TREATING CLASS B FIRE.
Fire Fighting Procedures:SUMMON PROFESSIONAL FIREFIGHTERS. USE NIOSH/MSHA APPRVD SCBA/FULL PROT EQUIP . WATER SPRAY MAY BE INEFTIVE. IF H*2O IS USED, FOG NOZZ ARE PREF.(SUPP DATA)
Unusual Fire/Explosion Hazard:DUE TO PRESSURE BUILD-UP, CLOSED CONTRS EXPOSED TO EXTREME HEAT MAY EXPLODE.

Accidental Release

Spill Release Procedures:WASH W/WATER. BEFORE ATTEMPTING CLEAN-UP, REFER TO HAZARD CAUTION INFORMATION. CONTAIN SPILLED MATERIAL AND REMOVE W/INERT ABSORBENT. STORE IN CLOSED CONTAINER UNTIL PROPERLY DISPOSED OF.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

Handling

Handling and Storage Precautions:STORE BELOW 110F AND KEEP FROM FREEZING. KEEP CONTR CLOSED WHEN NOT IN USE. DO NOT REUSE EMPTY CONTRS.

Other Precautions:DO NOT TRANSFER CONTENTS TO BOTTLES OR OTHER UNLABELLED CONTAINERS. KEEP OUT OF REACH OF CHILDREN.

Exposure Controls

Respiratory Protection:DO NOT BRTH VAPS/SPRAY MIST/SANDING DUST. WHEN SPRAY APPLIED IN OUTDOOR/OPEN AREAS W/UNRESTRICTED VENT & DURING SANDING/GRINDING OPERATIONS, USE NIOSH/MSHA APPRVD MECH FILTER RESP TO REMOVE SOLID AIRB ORNE PARTICLES OF OVERSPRAY (SUPP DATA)

Ventilation:USE ONLY W/ADEQ VENT.PROVIDE GEN DILUTION/LOC EXHST VENT IN VOL/PATTERN TO KEEP AIR CONTAM CONC BELOW CURRENT (ING 9)

Protective Gloves:NOT REQUIRED. IMPERVIOUS GLOVES .

Eye Protection:CHEMICAL WORKERS GOGGLES .

Other Protective Equipment:NONE REQUIRED.

Work Hygienic Practices:REMOVE & WASH SOILED CLOTHING BEFORE REUSE. WASH HANDS BEFORE EATING, SMOKING OR USING THE WASHROOM.

Supplemental Safety and Health

FIRE FIGHT PROC: IF EXPOS TO FIRE/EXTREME HEAT, H*2O SHLD BE USED TO COOL CLOSED CONTRS & PVNT PRESS BUILD-UP/POSS AUTO-IGNIT. RESP PROT: & SANDING DUST. WHEN USED IN RESTRICTED VENT AREAS, WEAR NIOSH /MSHA APPRVD CHEM MECH FILTER DESIGNED TO REMOVE A COMBINATION OF PARTICULATES/VAP. WHEN USED IN CONFINED AREAS, (ING 7)

Chemical Properties

HCC:N1

Boiling Pt:B.P. Text:212F,100C

Vapor Pres:SEE INGRED

Vapor Density:HVR/AIR

Spec Gravity:8.8-11.00

Evaporation Rate & Reference:SLOWER THAN ETHER

Appearance and Odor:NONE SPECIFIED BY MANUFACTURER.

Percent Volatiles by Volume:65-70

Stability

Stability Indicator/Materials to Avoid:YES

NONE SPECIFIED BY MANUFACTURER.

Stability Condition to Avoid:NONE SPECIFIED BY MANUFACTURER.

Hazardous Decomposition Products:MAY CAUSE HAZARDOUS FUMES WHEN HEATED

TO DECOMPOSITION. FUMES MAY CONTAIN CO, CO*2, NO*X.

Disposal

Waste Disposal Methods:DISPOSE OF I/A/W LOCAL, STATE, AND FEDERAL REGULATIONS. INCINERATE ONLY IN APPROVED FACILITY. DO NOT INCINERATE CLOSED CONTAINERS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.