
ACRYLIC LATEX ENAMELIZED HOUSE PAINT, W2500

MSDS Number

BMCJW

National Stock Number

8010-00N024158

Product Name

ACRYLIC LATEX ENAMELIZED HOUSE PAINT, W2500

Manufacturer

AMERITONE PAINT CORP

Product Identification

Product ID: ACRYLIC LATEX ENAMELIZED HOUSE PAINT, W2500

MSDS Date: 11/20/1987

FSC: 8010

NIIN: 00N024158

MSDS Number: BMCJW

Responsible Party

AMERITONE PAINT CORP

18414 S SANTA FE AVE

COMPTON, CA 90221

US

Emergency Phone: 213-639-6791

Info Phone: 213-639-6791

Cage: FO133

Contractor

AMERITONE PAINT CORP/COMPTON, CA 90221

190

LONG BEACH, CA 90801

US

310-639-6791

Cage: FO133

Ingredients

WITH THIS PROD. FOLLOW RESP MFR DIRECTIONS FOR RESP

RTECS: 9999999ZZ

ON SURF COATED WITH THIS PRODUCT.

RTECS: 9999999ZZ

TITANIUM OXIDE; (TITANIUM DIOXIDE)

CAS: 13463-67-7

RTECS: XR2275000

Fraction By Weight: 0-30%

OSHA PEL15 MG/M3 TDUST

ACGIH TLV: 10 MG/M3 TDUST; 9293

0.1 @ 70F. LEL

CAS: 57-55-6

RTECS: TY2000000

Fraction By Weight: 5-10%

11.9 @ 68F

CAS: 1336-21-6

RTECS: BQ9625000

Fraction By Weight:

OSHA PEL35 PPM STEL

ACGIH TLV: 25 PPM

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

DIATOMACEOUS EARTH

CAS: 68855-54-9

Fraction By Weight:

OSHA PEL10 MG/M3 TDUST

ACGIH TLV: 10 MG/M3 TDUST

0.62

CAS: 25265-67-7

Fraction By Weight:

MERCURY, (ACETATO) PHENYL; (PHENYLMERCURIC ACETATE)

CAS: 62-38-4

RTECS: OV6475000

Fraction By Weight:

EPA Report Quantity: 100 LBS

DOT Report Quantity: 100 LBS

ATTAPULGITE; (ATTAPULGITE CLAY)

CAS: 12174-11-7

RTECS: RT6400000

Fraction By Weight:

SANDING DUST. WHEN USED IN RESTRICTED VENT AREA,

RTECS: 9999999ZZ

TO REMOVE A COMBINATION OF PARTICULATES & VAP. WHEN

RTECS: 9999999ZZ

SUPPLY RESP/HOODS. USE NIOSH/MSHA APPRVD RESP WHEN

RTECS: 9999999ZZ

Hazards

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.

Routes of Entry: Inhalation:YES Skin:NO Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:(ACUTE) INHAL: IRRITATION OF THE RESPIRATORY TRACT; HDCH, NAUS, DIZZ. SKIN/EYE: PRIMARY IRRITATION. (CHRONIC) PROLONGED AND REPEATED BREATHING OF SPRAY MIST AND/OR SANDING DUST OVER A PERIOD OF YEARS MAY CAUSE DUST DISEASE OF THE LUNGS.

Explanation of Carcinogenicity:NOT RELEVANT

Effects of Overexposure:SEE HEALTH HAZARDS.

Medical Cond Aggravated by Exposure:NONE WHEN USED IN ACCORDANCE WITH SAFE HANDLING AND USE INFORMATION.

First Aid

First Aid:INHAL: REMOVE TO FRESH AIR. EYES: FLUSH IMMEDIATELY WITH LARGE AMOUNTS OF WATER FOR AT LEAST 15 MINUTES. CALL MD FOR MEDICAL TREATMENT. SKIN: REMOVE WITH SOAP AND WATER. REMOVE SOILED CLOTHING. INGEST : DRINK 1 OR 2 GLASSES OF WATER TO DILUTE. DO NOT INDUCE VOMITING. CALL MD IMMEDIATELY. TREAT SYMPTOMATICALLY.

Fire Fighting

Flash Point:NONE

Lower Limits:SEE INGRED

Extinguishing Media:IN CASE OF FIRE USE CO*2, DRY CHEMICAL, FOAM OR OTHER NFPA APPROVED METHOD FOR TREATING A CLASS B FIRE.

Fire Fighting Procedures:WEAR NIOSH/MSHA APPRVD SCBA & FULL PROT EQUIP .SUMMON PROF FIREFIGHTERS.WATER SPRAY MAY BE INEFT.IF WATER IS USED,FOG NOZZ ARE PREF.IF EXPSD (SUPP DATA)

Unusual Fire/Explosion Hazard:DUE TO PRESS BUILD-UP, CLSD CNTNRS EXPSD TO EXTREME HEAT MAY EXPLODE.DURING EMER CNDTNS,OVEREXP TO DECOMP PRODS MAY CAUSE HLTH HAZ.SYMP MAY NOT BE (SUPP DATA)

Accidental Release

Spill Release Procedures:WASH WITH WATER. BEFORE ATTEMPTING CLEAN-UP, REFER TO HAZARD CAUTION INFO IN OTHER SECTION OF MSDS. CONTAIN SPILLED MATERIAL AND REMOVE WITH INERT ABSORBENT. STORE IN CLOSED CONTAINER UNTIL PROPERLY D ISPOSED OF.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

Handling

Handling and Storage Precautions:STORE BELOW 110F & KEEP FROM FREEZING. KEEP CNTNR CLSD WHEN NOT IN USE. DO NOT REUSE EMPTY CNTNRS. DO NOT TRANSFER CONTENTS TO BOTTLES/UNLAB CNTNRS.

Other Precautions:KEEP OUT OF REACH OF CHILDREN. DO NOT BREATHE VAPORS, SPRAY MIST OR SANDING DUST.

Exposure Controls

Respiratory Protection:WHEN SPRAY APPLIED IN OUTDOOR/OPEN AREAS W/UNRESTRICTED VENT & DURING SANDING/GRINDING OPER USE NIOSH/MSHA APPRVD MECH FILTER RESP TO REMOVE SOLID AIRBORNE PARTICLES OF OVERSPRAY & (ING 8)

Ventilation:USE ONLY W/ADEQ VENT.PROVIDE GEN DILUTION/LOC EXHST VENT IN VOLUME & PATTERN TO KEEP AIR CONC Protective Gloves:NOT REQUIRED.

Eye Protection:CHEMICAL WORKERS GOGGLES .

Other Protective Equipment:NONE REQUIRED.

Work Hygienic Practices:REMOVE AND WASH SOILED CLOTHING BEFORE REUSE. WASH HANDS BEFORE EATING, SMOKING OR USING THE WASHROOM.

Supplemental Safety and Health

FIRE FIGHT PROC: TO FIRE/EXTREME HEAT, WATER SHOULD BE USED TO COOL CLSD CNTNRS & PVNT PRESS BUILD-UP/POSS AUTO-IGNIT. EXPLO HAZ: IMMED APPARENT. CALL MD. VENT: SAFETY & HLTH STANDARDS IN MIXING, APPL ICATN & CURING AREAS & TO REMOVE SANDING DUSTS OF DRIED COATING & DECOMP PRODS DURING WELDING & FLAME CUTTING (ING 12)

Chemical Properties

HCC:N1
Boiling Pt:B.P. Text:>212F,100C
Vapor Pres:SEE INGRED
Vapor Density:HVR/AIR
Spec Gravity:1.05-1.31
Evaporation Rate & Reference:SLOWER THAN ETHER
Appearance and Odor:NONE SPECIFIED BY MANUFACTURER.
Percent Volatiles by Volume:65-70

Stability

Stability Indicator/Materials to Avoid:YES
NONE SPECIFIED BY MANUFACTURER.
Stability Condition to Avoid:NONE SPECIFIED BY MANUFACTURER.
Hazardous Decomposition Products:MAY CAUSE HAZ FUMES WHEN HEATED TO
DECOMP. FUMES MAY CONTAIN CO, CO*2, NO*X.

Disposal

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE AND
FEDERAL REGULATIONS. INCINERATE ONLY IN APPROVED FACILITY. DO NOT
INCINERATE CLOSED CONTAINERS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.