

U-2 HI-Q ENAMEL

MSDS Number

BMLBZ

National Stock Number

8010-00F021124

Product Name

U-2 HI-Q ENAMEL

Manufacturer

TRU TEST MANUFACTURING CO

Product Identification

Product ID:U-2 HI-Q ENAMEL

MSDS Date:07/25/1990

FSC:8010

NIIN:00F021124

MSDS Number: BMLBZ

Responsible Party

TRU-TEST MANUFACTURING CO

201 JANDUS

CARY , IL 60013

Emergency Phone: (800) 228-5635

Info Phone: (708) 639-5383

Cage: TRUTE

Contractor

TRU-TEST MANUFACTURING CO

CARY, IL 60013

US

708-639-5383

Cage: TRUTE

Ingredients

TOLUENE (SARA III)

CAS: 108-88-3

RTECS: XS5250000

Fraction By Weight: 19-25%

OSHA PEL200 PPM/150 STEL

ACGIH TLV: 50 PPM; 9293

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

ACETONE, DIMETHYL KETONE

CAS: 67-64-1

RTECS: AL3150000

Fraction By Weight: 31-36%

OSHA PEL1000PPM

ACGIH TLV: 750PPM/1000STEL;9293

EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

HYDROCARBON PROPELLANT, PETROLEUM GASES LIQUEFIED

CAS: 68476-86-8

Fraction By Weight: 25-30%

OSHA PEL1000 PPM

ACGIH TLV: 1000 PPM

GROG; CALCIUM-BARIUM PHOSPHOSILICATE

CAS: 66402-68-4

Fraction By Weight: 1-3%

OSHA PEL15 MG/CUM

ACGIH TLV: 20 MG/CUM

TALC (POWDER), (ASBESTOS FREE), TALCUM, MAGNESIUM SILICATE

CAS: 14807-96-6

RTECS: WW2710000

Fraction By Weight: 3-6%

OSHA PEL20 MPPCF

ACGIH TLV: 2 MG/CUM (RESP DUST)

Hazards

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:EYES: IRRITATION. SKIN: DRYNESS.

INHALATION: HEADACHE, DIZZINESS, NAUSEA, PERMANENT BRAIN & NERVOUS SYSTEM DAMAGE.

Explanation of Carcinogenicity:NONE

Effects of Overexposure:EYES: IRRITATION. SKIN: DRYNESS. INHALATION:

HEADACHE, DIZZINESS, NAUSEA, PERMANENT BRAIN & NERVOUS SYSTEM

DAMAGE.

First Aid

First Aid:EYES: FLUSH W/FRESH WATER. SKIN: WASH W/SOAP & WATER.

INHALATION: REMOVE TO FRESH AIR. GIVE CPR OR OXYGEN IF NEEDED.

INGESTION: DON'T INDUCE VOMITING. KEEP PERSON WARM & QUIET. OBTAIN

MEDICAL ATTENTION IN ALL CASES.

Fire Fighting

Flash Point:Extinguishing Media:FOAM, CO2, WATER FOG & DRY CHEMICAL

Fire Fighting Procedures:TREAT AS A VOLATILE LIQUID FIRE. WATER SPRAY

MAY BE INEFFECTIVE. IF WATER IS USED, FOG NOZZLES ARE PREFERRED.

CLOSE CONTAINERS MAY EXPLODE WHEN EXPOSED TO HEAT.

Unusual Fire/Explosion Hazard:WATER MAY BE USED TO COOL FIRE EXPOSED

CONTAINERS TO PREVENT PRESSURE BUILD-UP/EXPLOSION & AUTO-IGNITION

WHEN EXPOSED TO HEAT. FLAMMABLE LIQUID.

Accidental Release

Spill Release Procedures:ELIMINATE IGNITION SOURCES. CONTAIN SPILL,

ABSORB LIQUID W/CLAY, SAND OR FLOOR ABSORBENT. PREVENT RUN-OFF TO

SEWERS, STREAMS OR OTHER BODIES OF WATER.

Handling

Handling and Storage Precautions:ELMINATE IGNITION SOURCES. DON'T EXPOSE OR STORE AT TEMPS >120F.
Other Precautions:DON'T TAKE INTERNALLY. AVOID SKIN CONTACT.

Exposure Controls

Respiratory Protection:USE NIOSH/MSHA APPROVED AIR SUPPLIED RESPIRATOR IF >TLV. APPROVED MECHANICAL FILTER TO REMOVE SOLID AIRBORNE PARTICLES.
Ventilation:MECHANICAL/GENERAL/LOCAL EXHAUST
Protective Gloves:RECOMMENDED
Eye Protection:RECOMMENDED
Other Protective Equipment:IMPERVIOUS CLOTHING & BOOTS
Work Hygienic Practices:WASH HANDS BEFORE EATING, SMOKING OR USING BATHROOM. DON'T REUSE CONTAMINATED CLOTHING.
Supplemental Safety and Health

Chemical Properties

Boiling Pt:B.P. Text:Vapor Density:>AIR
Evaporation Rate & Reference:SLOWER THAN ETHER
Appearance and Odor:VARIES W/COLOR
Percent Volatiles by Volume:83%

Stability

Stability Indicator/Materials to Avoid:YES
STRONG OXIDIZING AGENTS
Stability Condition to Avoid:HEAT, SPARKS, OPEN FLAMES & TEMPS ABOVE 120F
Hazardous Decomposition Products:CO2 & CO

Disposal

Waste Disposal Methods:CONTAMINATED ABSORBENT MAY BE DEPOSITED IN A LANDFILL IN ACCORDANCE W/LOCAL, STATE & FEDERAL REGULATIONS.
DISPOSE OF EMPTY CANS IN NON-INCINERATED TRASH ONLY. FLAMMABLE LIQUID.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.