https://msdsreport.com/msds/BMLPS

D TRU-TEST COLORANTS

MSDS Number

BMLPS

National Stock Number

8010-00F021349

Product Name

D TRU-TEST COLORANTS

Manufacturer

TRU TEST MANUFACTURING COMPANY

Product Identification

Product ID:D TRU-TEST COLORANTS MSDS Date:07/25/1990 FSC:8010 NIIN:00F021349 MSDS Number: BMLPS

Responsible Party

TRU-TEST MANUFACTURING COMPANY

201 JANDUS ROAD

CARY , IL 60013

Emergency Phone: (800) 228-5635

Info Phone: (708) 639-5383

Cage: TRUTE

Contractor

TRU-TEST MANUFACTURING CO

CARY, IL 60013

US

708-639-5383

Cage: TRUTE

Ingredients

TALC (POWDER), (ASBESTOS FREE), TALCUM, MAGNESIUM SILICATE

CAS: 14807-96-6

RTECS: WW2710000

Fraction By Weight: 10-20%

OSHA PEL20 MPPCF

ACGIH TLV: 2 MG/CUM (RESP DUST)

Hazards

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:INHALATION: IRRITATION OF EYES, NOSE, THROAT, & MUCOUS MEMBRANES OF RESPIRATORY TRACT. SKIN/EYES: IRRITATION. Explanation of Carcinogenicity:NONE Effects of Overexposure:INHALATION: IRRITATION TO EYES, NOSE, THROAT, & MUCOUS MEMBRANES OF RESPIRATORY TRACT. SKIN/EYES: IRRITATION.

First Aid

First Aid:INHALATION: REMOVE TO FRESH AIR. SKIN: WASH W/SOAP & WATER.



EYES: FLUSH IMMEDIATELY W/LARGE AMOUNTS OF WATER. INGESTION: GIVE 2 GLASSES OF WATER TO DILUTE. DON'T INDUCE VOMITING. OBTAIN MEDICAL ATTENT ION IN ALL CASES.

•

Fire Fighting

Extinguishing Media:FOAM, CO2, DRY CHEMICAL, WATER FOG Fire Fighting Procedures:WATER MAY BE USED TO COOL CLOSED CONTAINERS. Unusual Fire/Explosion Hazard:CLOSED CONTAINERS MAY EXPLODE OR BUILD-UP PRESSURE WHEN EXPOSED TO EXTREME HEAT.

Accidental Release

Spill Release Procedures: DIKE & CONTAIN SPILL W/INERT MATERIAL SUCH AS SAND OR EARTH. TRANSFER THE LIQUID TO CONTAINERS FOR RECOVERY OR DISPOSAL. KEEP SPILL OUT OF SEWERS & OPEN BODIES OF WATER.

Handling

Handling and Storage Precautions: KEEP FROM FREEZING. AVOID CONTACT W/SKIN & EYES. DON'T TAKE INTERNALLY. AVOID INHALATION OF VAPORS OR SPRAY MISTS.

Exposure Controls

Respiratory Protection:WHEN BRUSHED OR ROLLED NONE REQUIRED IF GOOD VENTILATION MAINTAINED. DURING SPRAY APPLICATION, AN APPROVED MECHANICAL FILTER RESPIRATOR TO REMOVE AIRBORN PARTICLES OF OVERSPRAY IS REQUIRED.

Ventilation:SUFFICIENT TO KEEP Protective Gloves:AS REQUIRED Eye Protection:SAFETY GLASSES INCLUDING SPLASH GUARDS Other Protective Equipment:EYE WASH FACILITY, PROTECTIVE CLOTHING Work Hygienic Practices:REMOVE/LAUNDER CONTAMINATED CLOTHING BEFORE REUSE. WASH HANDS BEFORE EATING, SMOKING, OR USING WASHROOM. Supplemental Safety and Health

Chemical Properties

Boiling Pt:B.P. Text:212F Vapor Density:Evaporation Rate & Reference:SLOWER THAN ETHER Appearance and Odor:VARIES W/COLOR

Stability

Stability Indicator/Materials to Avoid:YES Stability Condition to Avoid:EXTREME HEAT & FREEZING

Disposal

Waste Disposal Methods:LIQUID MATERIAL & CONTAMINATED DIKING MATERIAL SHOULD BE LANDFILLED ACCORDING TO CURRENT LOCAL, STATE, & FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.