
TT-P-95C TY 2, 25526 BLUE, 700L50

MSDS Number

BMPWY

National Stock Number

8010-00-054-9322

Product Name

TT-P-95C TY 2, 25526 BLUE, 700L50

Manufacturer

GRIGGS PAINT

Product Identification

Product ID:TT-P-95C TY 2, 25526 BLUE, 700L50

MSDS Date:01/01/1990

FSC:8010

NIIN:00-054-9322

MSDS Number: BMPWY

Responsible Party

GRIGGS PAINT

3602 S 16TH PLACE

PHOENIX , AZ 85040

US

Emergency Phone: 800-424-9300 CHEMTREC

Info Phone: 602-243-3293

Preparer: ROBERT COMMISSO

Cage: DO312

Contractor

GRIGGS PAINT

PHOENIX, AZ 85040-1319

US

602-243-3293

Cage: DO312

Ingredients

TITANIUM DIOXIDE

CAS: 13463-67-7

RTECS: XR2275000

Fraction By Weight: 15 - 20%

OSHA PEL15 MG/M3 TDUST

ACGIH TLV: 10 MG/M3 TDUST; 9293

MAGNESIUM SILICATE

CAS: 14807-96-6

RTECS: WW2710000

Fraction By Weight: 10%

ACGIH TLV: 2 MG/M3

MINERAL SPIRITS (VAPOR PRESSURE 2.0 MM HG @ 68 F)

CAS: 8032-32-4

RTECS: OI6180000

Fraction By Weight: 45%

OSHA PEL500 PPM

ACGIH TLV: 100 PPM

CHLORINATED ALKYD RESIN

Fraction By Weight:

AROMATIC PETROLEUM DISTILLATES (VAPOR PRESSURE 10.0 MM HG @

CAS: 64742-95-6

Fraction By Weight:

OSHA PEL100 PPM

ACGIH TLV: 300 PPM

4.84 (580 G/L)

RTECS: 9999999VO

Hazards

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:DIRECT CONTACT TO EYES: IRRIT.

PROLONGED/ REPEATED CONTACT: SKIN IRRIT. INHALATION OF HIGH CONC OF VAPORS MAY LEAD TO LUNG CHANGES, NAUSEA, VOMITING, COUGH, PULMONARY IRRIT & CENTRAL NERV SYS DEPRESS. INGESTION: GASTROINTEST DISTURBANCES. ASPIRATION OF PROD INTO LUNGS MAY CAUSE PNEUMONITIS, PULMONARY EDEMA & HEMORRAGE.

Effects of Overexposure:INHAL: BREATHING OF HIGH VAPOR CONC MAY CAUSE DROWSINESS, DIZZINESS, FATIGUE, FOLLOWED BY COMA. EYE: DIRECT CONTACT/CONTACT W/VAPOR--IRRIT. SKIN:

PROLONG/REPEAT--IRRIT/DERMATITIS. SKIN ABSORPTION: PRO LONG/REPEAT--DEFATTING/IRRIT/DERMATITIS. INGEST: ASPIRATION INTO LUNGS--PNEUMONITIS, PULMONARY EDEMA & HEMMORAGE.

Medical Cond Aggravated by Exposure:INDIVIDUALS WITH PRE-EXISTING DISEASES IN OR HISTORY OF AILMENTS INVOLVING SKIN, CENTRAL NERVOUS SYSTEM, LIVER AND KIDNEY. 21FEB92

First Aid

First Aid:EYE: IMMEDIATELY FLUSH WITH LARGE AMOUNTS OF WATER FOR 15 MINUTES. SEEK MEDICAL AID. SKIN: WASH THOROUGHLY WITH SOAP AND WATER. SEEK MEDICAL AID IF IRRITATION PERSISTS. INGESTION: IMMEDIATELY SEEK MED ICAI AID. DO NOT INDUCE VOMITING. DO NOT ATTEMPT TO GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON.

Fire Fighting

Flash Point Method:TCC

Flash Point:100F,38C

Autoignition Temp:Autoignition Temp Text:474F

Lower Limits:1.0%

Extinguishing Media:FOAM, CO2, DRY CHEMICAL, WATER FOG.

Fire Fighting Procedures:APPROVED GAS MASK REQUIRED FOR FIRE FIGHTING PERSONNEL. WATER MAY BE INEFFECTIVE. WATER MAY BE USED TO COOL CONTAINERS. IF WATER IS USED, FOG NOZZLES PREFERRED.

Unusual Fire/Explosion Hazard:KEEP CONTAINERS TIGHTLY CLOSED. ISOLATE FROM HEAT, ELECTRICAL EQUIPMENT, SPARKS AND OPEN FLAME. CLOSED

CONTAINERS MAY EXPLODE WHEN EXPOSED TO HEAT.

Accidental Release

Spill Release Procedures: STOP LEAK IF NO RISK INVOLVED. REMOVE ALL SOURCES OF IGNITION. STAY UPWIND. ABSORB WITH INERT MATERIAL. FLUSH AREA WITH WATER. VENTILATE AREA FOR AT LEAST 24 HOURS OR UNTIL AREA HAS BEEN DECLARED SAFE .

Handling

Handling and Storage Precautions: KEEP CONTAINERS CLOSED AND UPRIGHT TO PREVENT LEAKAGE. AVOID FLAMES, WELDING, OPEN LIGHTS, ETC. AVOID BREATHING OF VAPOR AND SPRAY MIST.

Other Precautions: AVOID SKIN AND EYE CONTACT. MAINTAIN GOOD PERSONAL HYGIENE. DO NOT USE IN CONFINED AREAS, TANK OR PIT WITHOUT ADEQUATE VENTILATION.

Exposure Controls

Respiratory Protection: IF VENT DOESN'T MAINTAIN INHALATION EXPOSURES BELOW TLV/PEL, USE NIOSH/MSHA APPRVD UNITS. USE UNITS PER CURRENT 29 CFR 1910.134 & FOLLOW MFRS' INSTRUCTIONS & WARNINGS. IF W/IN OSHA PROTECTION FACTOR, AIR PURIFYING OV/FILTER UNITS ARE OK.

Ventilation: LOCAL AND MECHANICAL EXHAUST.

Protective Gloves: RUBBER GLOVES.

Eye Protection: SAFETY GLASSES W/SIDE SHIELDS OR GOGGLES

Other Protective Equipment: EYE BATH AND SAFETY SHOWER.

Work Hygienic Practices: MAINTAIN GOOD PERSONAL HYGIENE. DO NOT USE IN CONFINED AREAS WITHOUT ADEQUATE VENTILATION.

Supplemental Safety and Health

Chemical Properties

HCC: F4

Boiling Pt: B.P. Text: 310 TO 320F

Vapor Density: > AIR

Spec Gravity: 1.1 (WATER=1)

Viscosity: 70+ KU

Evaporation Rate & Reference: SLOWER THAN ETHER.

Solubility in Water: ESSENTIALLY NIL.

Appearance and Odor: VISCOUS LIQUID WITH TYPICAL PAINT ODOR.

Percent Volatiles by Volume: 71.1

Stability

Stability Indicator/Materials to Avoid: YES

STRONG OXIDIZING AGENTS.

Stability Condition to Avoid: FLAMES, SPARKS, SMOKING AND HEAT.

Hazardous Decomposition Products: CARBON MONOXIDE, CARBON DIOXIDE.

Disposal

Waste Disposal Methods: USE INERT ABSORBENT MATERIALS ON SPILLS. DISPOSE OF IN ACCORDANCE WITH ALL FEDERAL, STATE AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.