https://msdsreport.com/msds/BMVNG

273A110, 7-STAR SUPER SPAR VARNISH

MSDS Number

BMVNG

National Stock Number

8010-00N029007

Product Name

273A110, 7-STAR SUPER SPAR VARNISH

Manufacturer

ACE HARDWARE CORP PAINT DIV

Product Identification

Product ID:273A110, 7-STAR SUPER SPAR VARNISH MSDS Date:10/01/1986 FSC:8010 NIIN:00N029007 MSDS Number: BMVNG

Responsible Party

ACE HARDWARE CORP/PAINT DIV

21901 SOUTH CENTRAL AVENUE

MATTESON , IL 60443

US

Emergency Phone: 312-720-0600

Info Phone: 312-720-0600

Cage: ACEHA

Contractor

ACE HARDWARE CORPORATION

MATTESON, IL 60443

US

708-720-0600

Cage: ACEHA

Ingredients

5.3. CAS: 110-80-5 RTECS: KK8050000 Fraction By Weight: OSHA PEL200 PPM, S ACGIH TLV: 5 PPM, S EPA Report Quantity: 1000 LBS DOT Report Quantity: 1000 LBS

KEROSENE (PETROLEUM), HYDROTREATED; (MINERAL SPIRITS). VP CAS: 64742-47-8 RTECS: OA5504000 Fraction By Weight: 44.6% OSHA PEL500 PPM (MFR)

ACGIH TLV: 100 PPM (MFR)

Hazards

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER. Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:INHAL IS ANESTH. IRRIT OF RESP TRACT/NERVOUS SYSTEM DEPRESS. HEADACHE, DIZZINESS, NAUSEA, CONFUSION, UNCONSCIOUSNESS/ COMA. SKIN/EYE CONTACT: PRIMARY IRRIT. REPORTS HAVE ASSOC RPTD/PRLNG OCCUP OVEREXP TO SOLVS W/PERM BRAIN & NERVOUS SYSTEMDMG. NIOSH RECOMMENDS THAT 2-ETHOXYETHANOL BE REGARDED IN THE (EFTS OF OVEREXP) Explanation of Carcinogenicity:NOT RELEVANT Effects of Overexposure:HLTH HAZ: WORKPLACE AS HAVING POTENTIAL TO CAUSE ADVERSE REPRODUCTIVE EFFECTS IN MALE AND FEMALE WORKERS . Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

•

First Aid

First Aid:INHAL: REMOVE FROM EXPOSURE, RESTORE BREATHING, KEEP WARM & QUIET, NOTIFY MD. EYES: FLUSH IMMEDIATELY WITH RUNNING WATER FOR AT LEAST 15 MINUTES. SKIN: WASH WITH SOAP AND WATER AND APPLY SKIN CREAM. I NGEST: CALL MD IMMEDIATELY . NOTIFY MD IN ALL CASES.

Fire Fighting

Flash Point Method:PMCC Flash Point:105F,41C Lower Limits:0.9% Extinguishing Media:FOAM, "ALCOHOL" FOAM, CO2, DRY CHEMICAL. Fire Fighting Procedures:WEAR NIOSH/MSHA APPRVD SCBA & FULL PROT EQUIP. DURING EMERG CNDTNS OVEREXP TO DECOMP PRODS MAY CAUSE A HLTH HAZ. SYMPS MAY NOT BE IMMED (SUPP DATA) Unusual Fire/Explosion Hazard:KEEP CNTNRS TIGHTLY CLSD. ISOLATE FROM HEAT, ELECT EQUIP, SPARKS, & OPEN FLAME. HEAT MAY CAUSE PRESS BUILDUP IN CLSD CNTNRS, WATER MAY BE USED TO COOL.

Accidental Release

Spill Release Procedures: REMOVE ALL SOURCES OF IGNITION. VENTILATE & REMOVE WITH INERT ABSORBENT. Neutralizing Agent: NONE SPECIFIED BY MANUFACTURER.

Handling

Handling and Storage Precautions:DOL STORAGE CATEGORY 2. KEEP CNTNR CLOSED WHEN NOT IN USE. DO NOT TRANSFER CONTENTS TO OTHER CNTNRS FOR STORAGE. CONSULT NFPA CODE. Other Precautions:USE APPRVD BONDING & GROUNDING PROCS. AVOID BREATHING VAP/SPRAY MIST. AVOID CONTACT W/SKIN & EYES. CONTENTS ARE COMBUSTIBLE, KEEP AWAY FROM HEAT & OPEN FLAME. USE ONLY W/ADEQ VENT. DO NOT TAKE INTERNA LLY, KEEP OUT OF REACH OF CHILDREN.

Exposure Controls

Respiratory Protection:IF ENGINEERING & ADMINISTRATIVE CONTROLS OF AIR CONTAMINANTS ARE NOT POSSIBLE, USE NIOSH/MSHA APPROVED RESPIRATORY DEVICES FOR PROTECTION AGAINST SPRAY MIST AND VAPORS. Ventilation:LOCAL EXHAUST PREF. MECHANICAL (GENERAL) EXHAUST ACCEPTABLE. SPECIAL VENT REQUIRED TO KEEP BELOW TLV & LEL. Protective Gloves:IMPERVIOUS GLOVES . Eye Protection:CHEMICAL WORKERS GOGGLES . Other Protective Equipment:NONE SPECIFIED BY MANUFACTURER. Work Hygienic Practices:WASH HANDS AFTER USING. REMOVE & WASH CONTAMD CLOTHING, DISCARD CONTAMD SHOES. Supplemental Safety and Health FIRE FIGHT PROC: APPARENT. OBTAIN MED ATTN. WATER SPRAY MAY BE INEFFECTIVE. WATER MAY BE USED TO COOL CLOSED CONTAINERS TO PREVENT PRESSURE BUILDUP AND POSSIBLE AUTO IGNITION OR EXPLOSION WHEN EXPOSED TO EXTREME HEAT.



https://msdsreport.com/msds/BMVNG

Chemical Properties

HCC:F4 Boiling Pt:B.P. Text:>308F,>153C Vapor Pres:SEE INGRED Vapor Density:HVR/AIR Spec Gravity:0.912 Evaporation Rate & Reference:SLOWER THAN ETHER Appearance and Odor:NONE SPECIFIED BY MANUFACTURER. Percent Volatiles by Volume:52.24

Stability

Stability Indicator/Materials to Avoid:YES NONE REASONABLY FORESEEABLE. Stability Condition to Avoid:HIGH TEMPERATURES, OPEN FLAME. Hazardous Decomposition Products:BY FIRE: CO2, CO.

Disposal

Waste Disposal Methods:INCINERATE IN APPROVED FACILITY. DO NOT INCINERATE CLOSED CONTAINERS. DISPOSE OF IN ACCORDANCE WITH FEDERAL, STATE AND LOCAL REGULATIONS REGARDING POLLUTION.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.