

## **197A105, 7-STAR QUICK DRY RUST (SUPP DATA)**

### **MSDS Number**

BMXXD

### **National Stock Number**

8010-00N028435

### **Product Name**

197A105, 7-STAR QUICK DRY RUST (SUPP DATA)

### **Manufacturer**

ACE HARDWARE CORP PAINT DIV

### **Product Identification**

Product ID:197A105, 7-STAR QUICK DRY RUST (SUPP DATA)

MSDS Date:10/01/1986

FSC:8010

NIIN:00N028435

MSDS Number: BMXXD

### **Responsible Party**

ACE HARDWARE CORP/PAINT DIV

21901 SOUTH CENTRAL AVENUE

MATTESON , IL 60443

US

Emergency Phone: 312-720-0600

Info Phone: 312-720-0600

Cage: ACEHA

### **Contractor**

ACE HARDWARE CORPORATION

MATTESON, IL 60443

US

708-720-0600

Cage: ACEHA

### **Ingredients**

KEROSENE (PETROLEUM), HYDROTREATED; (MINERAL SPIRITS 140

CAS: 64742-47-8

RTECS: OA5504000

Fraction By Weight: 3.5%

OSHA PEL500 PPM (MFR)

ACGIH TLV: 100 PPM (MFR)

0.6.

CAS: 2807-30-9

RTECS: KM2800000

Fraction By Weight:

OSHA PEL50 PPM (MFR)

ACGIH TLV: 50 PPM (MFR)

KEROSENE (PETROLEUM), HYDROTREATED; (MINERAL SPIRITS). VP

CAS: 64742-47-8

RTECS: OA5504000

Fraction By Weight: 40%

OSHA PEL500 PPM (MFR)

ACGIH TLV: 100 PPM (MFR)

## Hazards

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.

Routes of Entry: Inhalation:YES Skin:NO Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:INHALATION IS ANESTHETIC. IRRITATION OF RESPIRATORY TRACT OR NERVOUS SYSTEM DEPRESSION. HEADACHE, DIZZINESS, NAUSEA, CONFUSION, UNCONSCIOUSNESS OR COMA. SKIN OR EYE CONTACT: PRIMARY IRRITATION.

Explanation of Carcinogenicity:NOT RELEVANT

Effects of Overexposure:REPORTS HAVE ASSOCIATED REPEATED AND PROLONGED OCCUPATIONAL OVEREXPOSURE TO SOLVENTS, WITH PERMANENT BRAIN AND NERVOUS SYSTEM DAMAGE.

Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

## First Aid

First Aid:INHAL: REMOVE FROM EXPOSURE, RESTORE BREATHING, KEEP WARM AND QUIET, NOTIFY MD. EYES: FLUSH IMMEDIATELY WITH RUNNING WATER FOR AT LEAST 15 MINUTES. SKIN: WASH WITH SOAP AND WATER AND APPLY SKIN CREAM. NOTIFY MD IN ALL CASES. INGEST: CALL MD IMMEDIATELY .

## Fire Fighting

Flash Point Method:PMCC

Flash Point:105F,41C

Lower Limits:0.9%

Extinguishing Media:FOAM, "ALCOHOL" FOAM, CO\*2, DRY CHEMICAL.

Fire Fighting Procedures:WEAR NIOSH/MSHA APPRVD SCBA & FULL PROT EQUIP . DURING EMER CONDITIONS OVEREXP TO DECOMP PRODS MAY CAUSE HLTH HAZ. SYMPTS MAY NOT BE IMMED (SUPP DATA)

Unusual Fire/Explosion Hazard:KEEP CNTNRS TIGHTLY CLSD. ISOLATE FROM HEAT/ELEC EQUIP/SPKS & OPEN FLAME. HEAT MAY CAUSE PRESS BUILD-UP IN CLSD CNTNRS, WATER MAY BE USED TO COOL.

## Accidental Release

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION. VENTILATE AND REMOVE WITH INERT ABSORBENT.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

## Handling

Handling and Storage Precautions:CONTENTS ARE COMBUSTIBLE, KEEP AWAY FROM HEAT AND OPEN FLAME. KEEP CONTAINER CLOSED WHEN NOT IN USE. USE APPROVED BONDING & GROUNDING PROCEDURES.

Other Precautions:USE ONLY WITH ADEQUATE VENTILATION. AVOID BREATHING VAPOR AND SPRAY MIST. AVOID CONTACT WITH SKIN AND EYES. DO NOT TRANSFER CONTENTS TO OTHER CONTAINERS FOR STORAGE. DO NOT TAKE INTERNALLY. KEEP OUT OF REACH OF CHILDREN. CONSULT NFPA CODE.

## Exposure Controls

Respiratory Protection:IF ENGINEERING AND ADMINISTRATIVE CONTROLS OF AIR CONTAMINANTS ARE NOT POSSIBLE, USE RESPIRATORY DEVICES APPROVED BY NIOSH/MSHA FOR PROTECTION AGAINST SPRAY AND VAPORS.

Ventilation:LOCAL EXHAUST PREF. MECHANICAL (GENERAL) EXHAUST ACCEPTABLE. SPECIAL VENTILATION REQUIRED TO KEEP BELOW TLV AND LEL.

Protective Gloves:IMPERVIOUS GLOVES .

Eye Protection:CHEMICAL WORKERS GOGGLES .

Other Protective Equipment:NONE SPECIFIED BY MANUFACTURER.

Work Hygienic Practices: REMOVE AND WASH CONTAMINATED CLOTHING, DISCARD CONTAMINATED SHOES. WASH HANDS AFTER USING.

Supplemental Safety and Health

MFR'S TRADE NAME/PART NO: PREVENTATIVE OIL ENAMEL GLOSS BLACK. FIRE FIGHT PROC: APPARENT. OBTAIN MEDICAL ATTENTION. WATER SPRAY MAY BE INEFFECTIVE. WATER MAY BE USED TO COOL CLOSED CONTAINERS TO PREVENT PRESSURE BUILD-UP AND POSSIBLE AUTO IGNITION OR EXPLOSION WHEN EXPOSED TO EXTREME HEAT.

## Chemical Properties

HCC:F4

Boiling Pt:B.P. Text:>308F,>153C

Vapor Pres:SEE INGRED

Vapor Density:HVR/AIR

Spec Gravity:1.06

Evaporation Rate & Reference:SLOWER THAN ETHER

Appearance and Odor:NONE SPECIFIED BY MANUFACTURER.

Percent Volatiles by Volume:62.8

## Stability

Stability Indicator/Materials to Avoid:YES

NONE REASONABLY FORESEEABLE.

Stability Condition to Avoid:HIGH TEMPERATURES, OPEN FLAMES.

Hazardous Decomposition Products:BY FIRE: CO\*2, CO.

## Disposal

Waste Disposal Methods:INCINERATE IN APPROVED FACILITY. DO NOT INCINERATE CLOSED CONTAINERS. DISPOSE OF I/A/W FEDERAL, STATE AND LOCAL REGULATIONS REGARDING POLLUTION.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.