

186A214, 7-STAR ACE-TONE LATEX SEMI-GLOSS (

MSDS Number

BMYPK

National Stock Number

8010-00N028834

Product Name

186A214, 7-STAR ACE-TONE LATEX SEMI-GLOSS (

Manufacturer

ACE HARDWARE CORP PAINT DIV

Product Identification

Product ID:186A214, 7-STAR ACE-TONE LATEX SEMI-GLOSS (

MSDS Date:10/01/1986

FSC:8010

NIIN:00N028834

MSDS Number: BMYKP

Responsible Party

ACE HARDWARE CORP/PAINT DIV

21901 SOUTH CENTRAL AVENUE

MATTESON , IL 60443

US

Emergency Phone: 312-720-0600

Info Phone: 312-720-0600

Cage: ACEHA

Contractor

ACE HARDWARE CORPORATION

MATTESON, IL 60443

US

708-720-0600

Cage: ACEHA

Ingredients

0.1

CAS: 107-21-1

RTECS: KW2975000

Fraction By Weight: 2.0%

OSHA PEL50 PPM, C

ACGIH TLV: 50 PPM, VAPOR, C

EPA Report Quantity: 1 LB

DOT Report Quantity: 1 LB

1-PROPANOL, 2-AMINO-2-METHYL;

CAS: 124-68-5

RTECS: UA5950000

Fraction By Weight:

OSHA PEL20 PPM (MFR)

ACGIH TLV: 10 PPM (MFR)

Hazards

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:ACUTE: IN A CONFINED AREA, VAPORS IN HIGH CONCENTRATION ARE ANESTHETIC. IRRITANT TO SKIN & UPPER RESPIRATORY SYSTEM. OVEREXPOSURE MAY RESULT IN LIGHTHEADEDNESS & STAGGERING GAIT.

Explanation of Carcinogenicity:NOT RELEVANT.

Effects of Overexposure:SEE HEALTH HAZARDS.

Medical Cond Aggravated by Exposure:CHRONIC PROBLEMS W/RESPIRATORY SYSTEM MAY BE AGGRAVATED BY EXPOSURE TO VAPORS.

First Aid

First Aid:INHAL:IF AFFECTED, REMOVE FROM EXPOSURE & RESTORE BREATHING.

KEEP WARM & QUIET. SKIN:WASH AFFECTED AREAS THOROUGHLY W/SOAP & WATER. REMOVE CONTAMINATED CLOTHING & LAUNDER BEFORE REUSE. EYE:

FLUSH W/W ATER FOR AT LEAST 15 MINS. GET MEDICAL ATTENTION.

INGEST:CALL MD IMMEDIATELY .

Fire Fighting

Flash Point Method:PMCC

Flash Point:199F,93C

Extinguishing Media:ALCOHOL FOAM, CO2 & DRY CHEMICAL.

Fire Fighting Procedures:WEAR NIOSH/MSHA APPRVD SCBA & FULL PROT EQUIP

. WATER SPRAY MAY NOT BE EFTIVE. WATER MAY BE USED TO COOL CLSD

CONTRS TO PVNT PRESS BUILD-UP & (SUPP DATA)

Unusual Fire/Explosion Hazard:EXTREME HEAT MAY CAUSE CLOSED CONTAINER TO BURST.

Accidental Release

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION. VENTILATE & REMOVE W/INERT ABSORBENT.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

Handling

Handling and Storage Precautions:DOL STORAGE CATEGORY-3B. KEEP CONTR CLOSED WHEN NOT IN USE. TRANSFER ONLY TO APPROVED CONTRS W/COMPLETE & APPROPRIATE LABELING. USE ONLY W/ADEQ VENT.

Other Precautions:DO NOT TAKE INTERNALLY. AVOID BREATHING VAPOR & SPRAY MIST. AVOID CONTACT W/SKIN & EYES. KEEP OUT OF REACH OF CHILDREN.

Exposure Controls

Respiratory Protection:IF PERSONAL EXPOSURE CANNOT BE CONTROLLED BELOW APPLICABLE LIMITS BY VENTILATION, WEAR NIOSH/MSHA APPROVED RESPIRATORY PROTECTION.

Ventilation:LOC EXHST PREFERABLE, GENERAL EXHST ACCEPTABLE BELOW TLV OF INGRED SECTION. REFER OSHA STDS 1910.94,1910.107,1910.108.

Protective Gloves:IMPERVIOUS GLOVES .

Eye Protection:CHEMICAL WORKERS GOGGLES .

Other Protective Equipment:NONE SPECIFIED BY MANUFACTURER.

Work Hygienic Practices:WASH HANDS AFTER USING.

Supplemental Safety and Health

MFRS TRADE NAME/PART NO:ULTRA DEEP BASE. FIRE FIGHT PROC:POSSIBLE AUTOIGNITION OR EXPLOSION WHEN EXPOSED TO EXTREME HEAT.

Chemical Properties

HCC:V4

Boiling Pt:B.P. Text:212F,100C

Vapor Pres:SEE INGRED

Vapor Density:HVR/AIR

Spec Gravity:1.22

pH:8.5-9

Evaporation Rate & Reference: SLOWER THAN ETHER
Appearance and Odor: NONE SPECIFIED BY MANUFACTURER.
Percent Volatiles by Volume: 66.52

Stability

Stability Indicator/Materials to Avoid: YES
NONE SPECIFIED BY MANUFACTURER.
Stability Condition to Avoid: EXTREME HEAT & OPEN FLAME.
Hazardous Decomposition Products: BY FIRE: CARBON DIOXIDE & CARBON MONOXIDE.

Disposal

Waste Disposal Methods: INCINERATE IN APPROVED FACILITY. DO NOT
INCINERATE CLOSED CONTAINER. DISPOSE OF IN ACCORDANCE W/ FEDERAL,
STATE & LOCAL REGULATIONS REGARDING POLLUTION.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.