

114A140, 7-STAR RUSTIC TONES OIL SOLID OX B

MSDS Number

BMYMK

National Stock Number

8010-00N028918

Product Name

114A140, 7-STAR RUSTIC TONES OIL SOLID OX B

Manufacturer

ACE HARDWARE CORP PAINT DIV

Product Identification

Product ID:114A140, 7-STAR RUSTIC TONES OIL SOLID OX B

MSDS Date:10/01/1986

FSC:8010

NIIN:00N028918

MSDS Number: BMYMK

Responsible Party

ACE HARDWARE CORP/PAINT DIV

21901 SOUTH CENTRAL AVENUE

MATTESON , IL 60443

US

Emergency Phone: 312-720-0600

Info Phone: 312-720-0600

Cage: ACEHA

Contractor

ACE HARDWARE CORPORATION

MATTESON, IL 60443

US

708-720-0600

Cage: ACEHA

Ingredients

KEROSENE (PETROLEUM), HYDROTREATED; (MINERAL SPIRITS). VP

CAS: 64742-47-8

RTECS: OA5504000

Fraction By Weight: 37%

OSHA PEL500 PPM (MFR)

ACGIH TLV: 100 PPM (MFR)

KEROSENE (PETROLEUM), HYDROTREATED; (MINERAL SPIRITS 140

CAS: 64742-47-8

RTECS: OA5504000

Fraction By Weight: 4%

OSHA PEL500 PPM (MFR)

ACGIH TLV: 100 PPM (MFR)

SILICA, CRYSTALLINE - CRISTOBALITE

CAS: 14464-46-1

RTECS: VV7325000

Fraction By Weight: 1.5%

OSHA PELSEE TABLE Z3

ACGIH TLV: 0.05 MG/M3 RDUST9293

Hazards

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.

Routes of Entry: Inhalation:YES Skin:NO Ingestion:YES

Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:NO

Health Hazards Acute and Chronic:REPORTS HAVE ASSOCIATED REPEATED AND PROLONGED OCCUPATIONAL OVEREXPOSURE TO SOLVENTS WITH PERMANENT BRAIN AND NERVOUS SYSTEM DAMAGE.

Explanation of Carcinogenicity:CRYSTALLINE SILICA (CRYSTOBALITE): GROUP 2A (IARC), GROUP 2 (NTP).

Effects of Overexposure:INHAL: ANESTHETIC. IRRITATION OF RESPIRATORY TRACT OR NERVOUS SYSTEM DEPRESSION. HEADACHE, DIZZINESS, NAUSEA, CONFUSION, UNCONSCIOUSNESS OR COMA. SKIN/EYE: PRIMARY IRRITATION. SANDING OF DRY FILM CAN G ENERATE DUST CONTAINING CRYSTALLINE SILICA. USE RESPIRATORY PROTECTION.

Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

First Aid

First Aid:INHAL: REMOVE FROM EXPOSURE. RESTORE BREATHING. KEEP WARM AND QUIET. CALL MD. EYE: FLUSH IMMEDIATELY WITH RUNNING WATER FOR AT LEAST 15 MIN. SKIN: WASH WITH SOAP AND WATER AND APPLY SKIN CREAM. CALL M D IN ALL CASES. INGEST: CALL MD IMMEDIATELY.

Fire Fighting

Flash Point Method:PMCC

Flash Point:105F,41C

Lower Limits:0.9 %

Extinguishing Media:FOAM, "ALCOHOL" FOAM, CARBON DIOXIDE, DRY CHEMICAL.

Fire Fighting Procedures:WEAR NIOSH/MSHA APPRVD SCBA & FULL PROT EQUIP. WATER SPRAY MAY BE INEFT. WATER MAY BE USED TO COOL CLOSED CNTNRS TO PVNT PRESS BUILD-UP & POSS (SUPP DATA)

Unusual Fire/Explosion Hazard:KEEP CNTNRS CLSD. ISOLATE FROM HEAT, ELEC EQUIP, SPARKS & OPEN FLAME. HEAT MAY CAUSE PRESSURE BUILD-UP IN CLOSED CNTNRS, WATER MAY BE USED TO COOL.

Accidental Release

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION. VENTILATE AND REMOVE WITH INERT ABSORBENT.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

Handling

Handling and Storage Precautions:DOL STORAGE CATEGORY-2. KEEP CONTAINER CLOSED WHEN NOT IN USE. DO NOT TRANSFER CONTENTS TO OTHER CONTAINERS FOR STORAGE. USE W/ADEQUATE VENTILATION.

Other Precautions:CONTENTS ARE COMBUSTIBLE, KEEP AWAY FROM HEAT & OPEN FLAME. AVOID BREATHING VAPOR & SPRAY MIST. AVOID CNTCT W/SKIN & EYES. DO NOT TAKE INTERNALLY. KEEP OUT OF REACH OF CHILDREN. CONSULT NFPA CODE. USE APPRVD BONDING & GROUNDING PROCEDURES.

Exposure Controls

Respiratory Protection:IF ENGINEERING AND ADMINISTRATIVE CONTROLS OR AIR CONTAMINANTS ARE NOT POSSIBLE, USE NIOSH/MSHA APPROVED RESPIRATORY DEVICES FOR PROTECTION AGAINST SPRAY MIST AND VAPORS.

Ventilation:LOCAL EXHAUST PREFERABLE. MECHANICAL (GENERAL) EXHAUST ACCEPTABLE. SPECIAL VENTILATION REQUIRED TO KEEP BELOW TLV & LEL.

Protective Gloves:IMPERVIOUS GLOVES .

Eye Protection:CHEMICAL WORKERS GOGGLES
Other Protective Equipment:NONE SPECIFIED BY MANUFACTURER.
Work Hygienic Practices:REMOVE AND WASH CONTAMINATED CLOTHING, DISCARD
CONTAMINATED SHOES. WASH HANDS AFTER USING.
Supplemental Safety and Health
FIRE FIGHT PROC: AUTO-IGNITION OR EXPLOSION WHEN EXPOSED TO EXTREME
HEAT. DURING EMERGENCY CONDITIONS OVEREXPOSURE TO DECOMPOSITON
PRODUCTS MAY CAUSE A HEALTH HAZARD. SYMPTOMS MAY NOT BE IMMEDIATELY
APPARENT. OBTAIN MEDICAL ATTENTION.

Chemical Properties

HCC:F4
Boiling Pt:B.P. Text:308F,153C
Vapor Pres:SEE INGRED
Vapor Density:HVR/AIR
Spec Gravity:1.01
Evaporation Rate & Reference:SLOWER THAN ETHER
Appearance and Odor:NONE SPECIFIED BY MANUFACTURER.
Percent Volatiles by Volume:61.38

Stability

Stability Indicator/Materials to Avoid:YES
NONE REASONABLY FORESEEABLE.
Stability Condition to Avoid:HIGH TEMPERATURES, OPEN FLAME.
Hazardous Decomposition Products:BY FIRE: CO2, CO.

Disposal

Waste Disposal Methods:INCINERATE IN APPROVED FACILITY. DO NOT
INCINERATE CLOSED CONTAINER. DISPOSE OF IN ACCORDANCE WITH FEDERAL,
STATE AND LOCAL REGULATIONS REGARDING POLLUTION.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.