

## **118A101, 5-STAR OIL HOUSE PAINT WHITE**

### **MSDS Number**

BNBHP

### **National Stock Number**

8010-00N028657

### **Product Name**

118A101, 5-STAR OIL HOUSE PAINT WHITE

### **Manufacturer**

ACE HARDWARE CORP PAINT DIV

### **Product Identification**

Product ID:118A101, 5-STAR OIL HOUSE PAINT WHITE

MSDS Date:10/01/1986

FSC:8010

NIIN:00N028657

MSDS Number: BNBHP

### **Responsible Party**

ACE HARDWARE CORP/PAINT DIV

21901 SOUTH CENTRAL AVENUE

MATTESON , IL 60443

US

Emergency Phone: 312-720-0600

Info Phone: 312-720-0600

Cage: ACEHA

### **Contractor**

ACE HARDWARE CORPORATION

MATTESON, IL 60443

US

708-720-0600

Cage: ACEHA

### **Ingredients**

KEROSENE (PETROLEUM), HYDROTREATED; (MINERAL SPIRITS, 140

CAS: 64742-47-8

Fraction By Weight: 13.5%

OSHA PEL500 PPM (MFR)

ACGIH TLV: 100 PPM (MFR)

KEROSENE (PETROLEUM), HYDROTREATED; (MINERAL SPIRITS). VP

CAS: 64742-47-8

Fraction By Weight: 25%

OSHA PEL500 PPM (MFR)

ACGIH TLV: 100 PPM (MFR)

CAS: 2807-30-9

RTECS: KM2800000

Fraction By Weight:

OSHA PEL50 PPM (MFR)

ACGIH TLV: 50 PPM (MFR)

## Hazards

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:ACUTE: INHALATION IS ANESTHETIC.

IRRITATION OF RESPIRATORY TRACT OR NERVOUS SYSTEM DEPRESSION.

HEADACHE, DIZZINESS, NAUSEA, CONFUSION, UNCONSCIOUSNESS OR COMA.

SKIN OR EYE CONTACT: PRIMARY IRRITATION. CHRONIC: REPORTS HAVE ASSOCIATED RPTD/PRLNG OCCUPATIONAL OVEREXPOSURE TO SOLVENTS W/PERM BRAIN & NERVOUS SYSTEM DAMAGE.

Explanation of Carcinogenicity:NOT RELEVANT.

Effects of Overexposure:SEE HEALTH HAZARDS.

Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

## First Aid

First Aid:INHAL: REMOVE FROM EXPOSURE, RESTORE BREATHING, KEEP WARM & QUIET, NOTIFY MD. EYES: FLUSH IMMEDIATELY W/RUNNING WATER FOR A MINIMUM OF 15 MINUTES. SKIN: WASH W/SOAP & WATER AND APPLY SKIN CREAM. NOTIF Y MD IN ALL CASES. INGEST: CALL MD IMMEDIATELY .

## Fire Fighting

Flash Point Method:PMCC

Flash Point:105F,41C

Lower Limits:0.9%

Extinguishing Media:FOAM, ALCOHOL FOAM, CO2, DRY CHEMICAL.

Fire Fighting Procedures:USE NIOSH/MSHA APPRVD SCBA & FULL PROT EQUIP .

DURING EMER CNDTNS OVEREXP TO DECOMP PROD MAY CAUSE HLTH HAZ. SYMP MAY NOT BE IMMED APPARENT. (SUPP DATA)

Unusual Fire/Explosion Hazard:KEEP CONTRS TIGHTLY CLOSED. ISOLATE FROM HEAT, ELEC EQUIP, SPARKS, & OPEN FLAME. HEAT MAY CAUSE PRESSURE BUILD-UP IN CLOSED CONTRS, WATER MAY BE USED TO COOL.

## Accidental Release

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION. VENTILATE AND REMOVE WITH INERT ABSORBENT.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

## Handling

Handling and Storage Precautions:DOL STORAGE CATEGORY - 2. CONTENTS ARE COMBUSTIBLE, KEEP AWAY FROM HEAT & OPEN FLAME. USE ONLY W/ADEQ VENT. AVOID BRTHG VAPOR & SPRAY MIST.

Other Precautions:AVOID CONT W/SKIN & EYES. WASH HANDS AFTER USING.

KEEP CONTR CLOSED WHEN NOT IN USE. DO NOT TRANSFER CONTENTS TO OTHER CONTRS FOR STOR. DO NOT TAKE INTERNALLY. KEEP OUT OF REACH OF CHILDREN. CONSULT N FPA CODE. USE APPRVD BOND/GROUND PROC.

## Exposure Controls

Respiratory Protection:IF ENGINEERING AND ADMINISTRATIVE CONTROLS OF AIR CONTAMINANTS ARE NOT POSSIBLE, USE RESPIRATORY DEVICES APPROVED BY NIOSH/ MSHA FOR PROTECTION AGAINST SPRAY MIST AND VAPORS.

Ventilation:LOCAL EXHAUST PREFERABLE. MECHANICAL (GENERAL) EXHAUST ACCEPTABLE. SPECIAL VENTILATION REQUIRED TO KEEP BELOW TLV/LEL.

Protective Gloves:IMPERVIOUS GLOVES.

Eye Protection:CHEMICAL WORKERS GOGGLES .

Other Protective Equipment:NONE SPECIFIED BY MANUFACTURER.

Work Hygienic Practices:REMOVE AND WASH CONTAMINATED CLOTHING, DISCARD CONTAMINATED SHOES. WASH HANDS AFTER USING.

Supplemental Safety and Health

FIRE FIGHT PROC: OBTAIN MED ATTN. WATER SPRAY MAY BE INEFFECTIVE. WATER MAY BE USED TO COOL CLOSED CONTRS TO PREVENT PRESSURE BUILD-UP AND POSSIBLE AUTO-IGNITION OR EXPLOSION WHEN EXPOSED TO EXTREME H EAT.

## Chemical Properties

HCC:F4

Boiling Pt:B.P. Text:>308F,>153C

Vapor Pres:SEE INGRED

Vapor Density:HVR/AIR

Spec Gravity:1.09

Evaporation Rate & Reference:SLOWER THAN ETHER

Appearance and Odor:NONE SPECIFIED BY MANUFACTURER.

Percent Volatiles by Volume:53.73

## Stability

Stability Indicator/Materials to Avoid:YES

NONE REASONABLY FORESEEABLE.

Stability Condition to Avoid:HIGH TEMPERATURES, OPEN FLAME.

Hazardous Decomposition Products:BY FIRE: CO2, CO.

## Disposal

Waste Disposal Methods:INCINERATE IN APPROVED FACILITY. DO NOT INCINERATE CLOSED CONTAINERS. DISPOSE OF IN ACCORDANCE W/FEDERAL, STATE, AND LOCAL REGULATIONS REGARDING POLLUTION.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.