

## **LEAK-TEC 16-OX, 55 GALLON DRUMS**

### **MSDS Number**

BNBKQ

### **National Stock Number**

6850-00N028786

### **Product Name**

LEAK-TEC 16-OX, 55 GALLON DRUMS

### **Manufacturer**

AMERICAN GAS AND CHEMICAL CO

### **Product Identification**

Product ID:LEAK-TEC 16-OX, 55 GALLON DRUMS

MSDS Date:07/01/1991

FSC:6850

NIIN:00N028786

MSDS Number: BNBKQ

### **Responsible Party**

AMERICAN GAS AND CHEMICAL CO

220 PEGASUS AVENUE

NORTHVALE , NJ 07647

US

Emergency Phone: 201-767-7300

Info Phone: 201-767-7300

Preparer: GEORGE KOSEL

Cage: 03530

### **Contractor**

AMERICAN GAS AND CHEMICAL COMPANY,LTD

NORTHVALE, NJ 07647-1904

US

201-767-7300

Cage: 03530

### **Ingredients**

NON HAZARDOUS INGREDIENTS

### **Hazards**

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.

Routes of Entry: Inhalation:YES Skin:NO Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:INHAL:NOT CONSIDERED LIKELY. SKIN:MILD IRRITANT. EYES:MILD IRRITANT. INGEST:NO PROBLEM ANTICIPATED OTHER THAN IRRITATION.

Explanation of Carcinogenicity:NOT RELEVANT

Effects of Overexposure:SEE HEALTH HAZARDS.

Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

### **First Aid**

First Aid:INHAL:REMOVE TO FRESH AIR. SKIN:WASH WITH SOAP AND WATER.

EYE:FLUSH WITH WATER FOR AT LEAST 15 MINUTES. SEEK MD ATTENTION IF IRRITATION PERSISTS. INGEST:INDUCE VOMITING. CALL MD.

### **Fire Fighting**

Flash Point:NONE  
Extinguishing Media:USE ANY SUITABLE FOR SURROUNDING MATERIAL.  
Fire Fighting Procedures:WEAR NIOSH/MSHA APPROVED SCBA AND FULL PROTECTIVE EQUIPMENT . USE WATER TO COOL FIRE EXPOSED CONTAINERS.  
Unusual Fire/Explosion Hazard:NONE SPECIFIED BY MANUFACTURER.

## Accidental Release

Spill Release Procedures:FLUSH WITH WATER TO SANITARY SEWER SYSTEM.  
Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

## Handling

Handling and Storage Precautions:STORE IN A COOL, DRY AREA. KEEP CONTAINERS CLOSED AND PLAINLY LABELED. SHELF LIFE:2 YEARS. AVOID REPEATED OR PROLONGED CONTACT WITH SKIN.  
Other Precautions:DO NOT GET IN EYES. FOR BEST RESULTS, TRAIN PERSONNEL TO REQMTS OF ASNT TC-1A OR EQUIVALENT. HOWEVER, EVEN WHEN USED BY QUALIFIED PERSONNEL DO NOT EXPECT TO FIND ALL LEAKS/FLAWS WHICH COULD THEORETICALLY BE FOUND.

## Exposure Controls

Respiratory Protection:USE NIOSH/MSHA APPROVED RESPIRATOR APPROPRIATE FOR EXPOSURE OF CONCERN .  
Ventilation:NONE SPECIFIED BY MANUFACTURER.  
Protective Gloves:IMPERVIOUS GLOVES .  
Eye Protection:CHEMICAL WORKERS GOGGLES .  
Other Protective Equipment:NONE SPECIFIED BY MANUFACTURER.  
Work Hygienic Practices:NONE SPECIFIED BY MANUFACTURER.  
Supplemental Safety and Health  
PH:6.0-7.5.

## Chemical Properties

HCC:N1  
Boiling Pt:B.P. Text:212F,100C  
Vapor Pres:17.5 @ 20C  
Vapor Density:>1 (AIR=1)  
Spec Gravity:0.12  
pH:SUPDAT  
Evaporation Rate & Reference:Solubility in Water:SOLUBLE  
Appearance and Odor:COLORLESS LIQUID WITH NO ODOR.  
Percent Volatiles by Volume:99+

## Stability

Stability Indicator/Materials to Avoid:YES  
OXIDIZING AGENTS.  
Stability Condition to Avoid:NONE SPECIFIED BY MANUFACTURER.  
Hazardous Decomposition Products:NONE

## Disposal

Waste Disposal Methods:CONSIDERED TO BE RELATIVELY TOXIC TO AQUATIC LIFE AT CONCENTRATIONS AS LOW AS 0.1%. STRONG FOAMER.  
BIODEGRADABILITY IS 90% OR BETTER AS DETERMINED BY SEMI-CONTINUOUS ACTIVATED SLUDGE METHOD. CHECK ALL LOCAL/STATE/FEDERAL REGS FOR COMPLIANCE IN DISP.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.