

113A175, 7-STAR RUSTIC TONES OIL SEMI-(SUPP

MSDS Number

BNBMV

National Stock Number

8010-00N028913

Product Name

113A175, 7-STAR RUSTIC TONES OIL SEMI-(SUPP

Manufacturer

ACE HARDWARE CORP PAINT DIV

Product Identification

Product ID:113A175, 7-STAR RUSTIC TONES OIL SEMI-(SUPP

MSDS Date:10/01/1986

FSC:8010

NIIN:00N028913

MSDS Number: BNBMV

Responsible Party

ACE HARDWARE CORP/PAINT DIV

21901 SOUTH CENTRAL AVENUE

MATTESON , IL 60443

US

Emergency Phone: 312-720-0600

Info Phone: 312-720-0600

Cage: ACEHA

Contractor

ACE HARDWARE CORPORATION

MATTESON, IL 60443

US

708-720-0600

Cage: ACEHA

Ingredients

KEROSENE (PETROLEUM), HYDROTREATED;(MINERAL SPIRITS).

CAS: 64742-47-8

RTECS: OA5504000

Fraction By Weight: 65%

OSHA PEL500 PPM (MFR)

ACGIH TLV: 100 PPM (MFR)

KEROSENE (PETROLEUM), HYDROTREATED; (MINERAL SPIRITS 140

CAS: 64742-47-8

RTECS: OA5504000

Fraction By Weight: 10%

OSHA PEL500 PPM (MFR)

ACGIH TLV: 100 PPM (MFR)

Hazards

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.
Routes of Entry: Inhalation:YES Skin:NO Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:INHALATION IS ANESTHETIC. IRRITATION OF RESPIRATORY TRACT OR NERVOUS SYSTEM DEPRESSION. HEADACHE, DIZZINESS, NAUSEA, CONFUSION, UNCONSCIOUSNESS OR COMA.
SKIN/EYE:PRIMARY IRRITATION. REPORTS HAVE ASSOCIATED REPEATED & PROLONGED OCCUPATIONALOVEREXPOSURE TO SOLVENTS WITH PERMANENT BRAIN & NERVOUS SYSTEM DAMAGE.
Explanation of Carcinogenicity:NOT RELEVANT.
Effects of Overexposure:SEE HEALTH HAZARDS.
Medical Condition Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

First Aid

First Aid:INHAL:MOVE FROM EXPOSURE, RESTORE BREATHING, KEEP WARM & QUIET & CALL MD. EYE:FLUSH IMMEDIATELY WITH RUNNING WATER FOR 15 MINUTES. SKIN:WASH WITH SOAP & WATER & APPLY SKIN CREAM. CALL MD IN ALL CASES. INGEST:CALL MD IMMEDIATELY .

Fire Fighting

Flash Point Method:PMCC
Flash Point:105F,41C
Lower Limits:0.9%
Extinguishing Media:FOAM, "ALCOHOL" FOAM, CO2, DRY CHEMICAL.
Fire Fighting Procedures:WEAR NIOSH/MSHA APPROVED SCBA & FULL PROTECTIVE EQUIP . DURING EMERGENCY CONDITIONS OVEREXPOSURE TO DECOMPOSITION PRODUCTS MAY CAUSE HEALTH HAZARDS. SYMPTOMS MAY NOT BE IMMEDIATELY APPARENT. (SUPPLEMENTAL DATA)
Unusual Fire/Explosion Hazard:KEEP CONTAINERS TIGHTLY CLOSED. ISOLATE FROM HEAT/ ELECTRICAL EQUIPMENT, SPARKS/OPEN FLAME. HEAT MAY CAUSE PRESSURE TO BUILD UP IN CLOSED CONTAINERS, WATER MAY BE USED TO COOL

Accidental Release

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION. VENTILATE AND REMOVE WITH INERT ABSORBENT.
Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

Handling

Handling and Storage Precautions:CONTENTS ARE COMBUSTIBLE. KEEP AWAY FROM HEAT & OPEN FLAME. USE ONLY WITH ADEQUATE VENTILATION. DOT STORAGE CATEGORY 2. AVOID BREATHING VAPOR/SPRAY MIST.
Other Precautions:AVOID CONTACT WITH SKIN & EYES. KEEP CONTAINER CLOSED WHEN NOT IN USE. DO NOT TRANSFER CONTENTS TO OTHER CONTAINERS FOR STORAGE. DO NOT TAKE INTERNALLY. KEEP OUT OF REACH OF CHILDREN. USE APPROVED BONDING/ GROUNDING PROCEDURE. CONSULT NFPA CODE.

Exposure Controls

Respiratory Protection:IF ENGINEERING & ADMINISTRATIVE CONTROLS OF AIR CONTAMINANTS ARE NOT POSSIBLE, USE NIOSH/MSHA APPROVED RESPIRATOR FOR PROTECTION AGAINST SPRAY MISTS AND VAPORS.
Ventilation:LOCAL EXHAUST PREFERRED. MECHANICAL (GENERAL) EXHAUST ACCEPTABLE. SPECIAL VENTILATION REQUIRED TO KEEP BELOW PEL/TLV.
Protective Gloves:IMPERVIOUS GLOVES .
Eye Protection:CHEMICAL WORKERS GOGGLES .
Other Protective Equipment:NONE SPECIFIED BY MANUFACTURER.
Work Hygienic Practices:REMOVE & WASH CONTAMINATED CLOTHING, DISCARD CONTAMINATED SHOES. WASH HANDS AFTER USING.
Supplemental Safety and Health
MFR PART#/TRADE NAME:TRANSPARENT STAIN NATURAL WEATHER REDWOOD. FIRE FIGHT PROCEDURE:GET MD. WATER SPRAY MAY BE INEFFECTIVE BUT MAY BE USED TO COOL CLOSED CONTAINERS TO PREVENT PRESSURE BUILD-UP & POSSIBLE ACCIDENTAL IGNITION OR EXPLOSION WHEN EXPOSED TO EXTREME HEAT.

Chemical Properties

HCC:F4
Boiling Point:B.P. Text:>308F,>153C

Vapor Pres:SEE ING
Vapor Density:HVR/AIR
Spec Gravity:0.9
Evaporation Rate & Reference:SLOWER THAN ETHER
Appearance and Odor:NONE SPECIFIED BY MANUFACTURER.
Percent Volatiles by Volume:82.9

Stability

Stability Indicator/Materials to Avoid:YES
NONE REASONABLY FORSEEABLE.
Stability Condition to Avoid:HIGH TEMPERATURES, OPEN FLAME.
Hazardous Decomposition Products:BY FIRE:CO, CO2.

Disposal

Waste Disposal Methods:INCINERATE IN APPROVED FACILITY. DO NOT
INCINERATE CLOSED CONTAINERS. DISPOSE OF IN ACCORDANCE WITH
FEDERAL, STATE, AND LOCAL REGULATIONS REGARDING POLLUTION.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.