

102A102, 7-STAR BRIGHT N EASY LATEX GLOSS(S

MSDS Number

BNBNY

National Stock Number

8010-00N028983

Product Name

102A102, 7-STAR BRIGHT N EASY LATEX GLOSS(S

Manufacturer

ACE HARDWARE CORP PAINT DIV

Product Identification

Product ID:102A102, 7-STAR BRIGHT N EASY LATEX GLOSS(S

MSDS Date:10/01/1986

FSC:8010

NIIN:00N028983 MSDS Number: BNBNY

Responsible Party

ACE HARDWARE CORP/PAINT DIV

21901 SOUTH CENTRAL AVENUE

MATTESON, IL 60443

US

Emergency Phone: 312-720-0600

Info Phone: 312-720-0600

Cage: ACEHA

Contractor

ACE HARDWARE CORPORATION

MATTESON, IL 60443

US

708-720-0600 Cage: ACEHA

Ingredients

1-PROPANOL, 2-AMINO-2-METHYL-;

CAS: 124-68-5

RTECS: UA5950000 Fraction By Weight:

OSHA PEL20 PPM (MFR)

ACGIH TLV: 10 PPM (MFR)

0.1 MMHG.

CAS: 107-21-1

RTECS: KW2975000

Fraction By Weight: 4.0%

OSHA PEL50 PPM, C

ACGIH TLV: 50 PPM, VAP/MIST, C



EPA Report Quantity: 1 LB DOT Report Quantity: 1 LB

Hazards

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER. Routes of Entry: Inhalation:YES Skin:NO Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:IN CONFINED AREA VAPORS IN HIGH CONCENTRATION ARE ANESTHETIC. IRRITANT TO SKIN AND UPPER

RESPIRATORY SYSTEM. OVEREXPOSURE MAY RESULT IN LIGHTHEADEDNESS AND

STAGGERING GAIT.

Explanation of Carcinogenicity: NOT RELEVANT. Effects of Overexposure: SEE HEALTH HAZARDS.

Medical Cond Aggravated by Exposure: CHRONIC PROBLEMS WITH RESPIRATORY

SYSTEM MAY BE AGGRAVATED BY EXPOSURE TO VAPORS.

First Aid

First Aid:INHALATION: REMOVE FROM EXPOSURE. RESTORE BREATHING. KEEP WARM AND QUIET. SKIN: WASH AFFECTED AREAS THOROUGHLY WITH SOAP AND WATER. REMOVE CONTAMINATED CLOTHING AND LAUNDER BEFORE RE-USE. EYES: FLUSH WITH WATER FOR AT LEAST 15 MINUTES. GETMEDICAL

ATTENTION. INGESTION: CALL MD IMMEDIATELY.

Fire Fighting

Flash Point Method: PMCC Flash Point: 199F, 93C

Extinguishing Media: "ALCOHOL" FOAM, CO2, DRY CHEMICAL.

Fire Fighting Procedures: WEAR NIOSH/MSHA APPRVD SCBA & FULL PROT EQUIP. H2O SPRAY MAY NOT BE EFT. H2O MAY BE USED TO COOL CNTNRS TO

PVNT PRESS BUILD-UP & POSS AUTO (SUPP DATA)

Unusual Fire/Explosion Hazard: EXTREME HEAT MAY CAUSE CLOSED CONTAINERS

TO BURST.

Accidental Release

Spill Release Procedures: REMOVE ALL SOURCES OF IGNITION. VENTILATE AND REMOVE WITH INERT ABSORBENT.

Neutralizing Agent: NONE SPECIFIED BY MANUFACTURER.

Handling

Handling and Storage Precautions: KEEP CONTAINER CLOSED WHEN NOT IN USE. TRANSFER ONLY TO APPROVED CONTAINERS WITH COMPLETE AND APPROPRIATE LABELING.

Other Precautions: DO NOT TAKE INTERNALLY. KEEP OUT OF REACH OF CHILDREN. DOL STORAGE CATEGORY 3B.

Exposure Controls

Respiratory Protection:IF PERSONAL EXPOSURE CANNOT BE CONTROLLED BELOW APPLICABLE LIMITS BY VENTILATION, WEAR NIOSH/MSHA APPROVED RESPIRATORY DEVICE.

Ventilation:LOCAL EXHAUST PREFERABLE, GENERAL EXHAUST ACCEPTABLE BELOW TLV. REFER OSHA 1910.94, .107,.108.

Protective Gloves: IMPERVIOUS GLOVES

Eye Protection: CHEMICAL WORKERS GOGGLES .

Other Protective Equipment: NONE SPECIFIED BY MANUFACTURER.

Work Hygienic Practices: USE ONLY WITH ADEQ VENT. AVOID BREATHING VAPOR AND SPRAY MIST. AVOID CONTACT WITH SKIN AND EYES. WASH HANDS AFTER USING.

Supplemental Safety and Health

TRADE NAME/PART #: ENAMEL UNDERCOATER WHITE. FIRE FIGHT PROC: IGNITION OR EXPLOSION WHEN EXPOSED TO EXTREME HEAT.

Chemical Properties

HCC:V4

Boiling Pt:B.P. Text:212F,100C Vapor Pres:SEE INGRED Vapor Density:HVR/AIR



Spec Gravity:1.35

pH:8.5-9

Evaporation Rate & Reference: SLOWER THAN ETHER Appearance and Odor: NONE SPECIFIED BY MANUFACTURER.

Percent Volatiles by Volume: 70.2

Stability

Stability Indicator/Materials to Avoid:YES NONE SPECIFIED BY MANUFACTURER. Stability Condition to Avoid:EXTREME HEAT AND OPEN FLAME. Hazardous Decomposition Products:BY FIRE: CARBON DIOXIDE AND CARBON MONOXIDE.

Disposal

Waste Disposal Methods:INCINERATE IN APPROVED FACILITY. DO NOT INCINERATE CLOSED CONTAINERS. DISPOSE OF IN ACCORDANCE WITH FEDERAL, STATE, AND LOCAL REGULATIONS REGARDING POLLUTION.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.