

## **128A100, 5-STAR LATEX STIPPLE TEXTURE PAINT**

### **MSDS Number**

BNBNZ

### **National Stock Number**

8010-00N028984

### **Product Name**

128A100, 5-STAR LATEX STIPPLE TEXTURE PAINT

### **Manufacturer**

ACE HARDWARE CORP PAINT DIV

### **Product Identification**

Product ID:128A100, 5-STAR LATEX STIPPLE TEXTURE PAINT

MSDS Date:10/01/1986

FSC:8010

NIIN:00N028984

MSDS Number: BNBNZ

### **Responsible Party**

ACE HARDWARE CORP/PAINT DIV

21901 SOUTH CENTRAL AVENUE

MATTESON , IL 60443

US

Emergency Phone: 312-720-0600

Info Phone: 312-720-0600

Cage: ACEHA

### **Contractor**

ACE HARDWARE CORPORATION

MATTESON, IL 60443

US

708-720-0600

Cage: ACEHA

### **Ingredients**

1-PROPANOL, 2-AMINO-2-METHYL-;

CAS: 124-68-5

RTECS: UA5950000

Fraction By Weight:

OSHA PEL20 PPM (MFR)

ACGIH TLV: 10 PPM (MFR)

0.1 MMHG.

CAS: 107-21-1

RTECS: KW2975000

Fraction By Weight: 3.5%

OSHA PEL50 PPM, C

ACGIH TLV: 50 PPM, VAP/MIST, C

EPA Report Quantity: 1 LB

DOT Report Quantity: 1 LB

SILICA, CRYSTALLINE - CRISTOBALITE

CAS: 14464-46-1

RTECS: VV7325000

Fraction By Weight: 5.0%

OSHA PELSEE TABLE Z3

ACGIH TLV: 0.05 MG/M3 RDUST9293

## Hazards

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.  
Routes of Entry: Inhalation:YES Skin:NO Ingestion:YES  
Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:NO  
Health Hazards Acute and Chronic:(ACUTE) IN CONFINED AREA VAPORS IN HIGH CONCENTRATION ARE ANESTHETIC. IRRITANT TO SKIN AND UPPER RESPIRATORY SYSTEM. OVER EXPOSURE MAY RESULT IN LIGHTHEADEDNESS AND STAGGERING GAIT. SANDING OF DRIED FILM CAN GENERATE DUST CONTAINING CRYSTALLINE SILICA-USE RESPIRATORY PROTECTION.  
Explanation of Carcinogenicity:CRYSTALLINE SILICA: IARC GRP 2B, NTP GRP 2.  
Effects of Overexposure:SEE HEALTH HAZARDS.  
Medical Cond Aggravated by Exposure:CHRONIC PROBLEMS WITH RESPIRATORY SYSTEM MAY BE AGGRAVATED BY EXPOSURE TO VAPORS.

## First Aid

First Aid:INHALATION: REMOVE FROM EXPOSURE, RESTORE BREATHING, KEEP WARM AND QUIET. SKIN: WASH AFFECTED AREAS THOROUGHLY WITH SOAP AND WATER. REMOVE CONTAMINATED CLOTHING AND LAUNDRY BEFORE RE-USE. EYES: FLUSH WITH WATER FOR AT LEAST 15 MINUTES. GETMEDICAL ATTENTION. INGESTION: CALL MD IMMEDIATELY .

## Fire Fighting

Flash Point Method:PMCC  
Flash Point:199F,93C  
Extinguishing Media:"ALCOHOL" FOAM, CO2, DRY CHEMICAL.  
Fire Fighting Procedures:WEAR NIOSH/MSHA APPRVD SCBA & FULL PROT EQUIP.H2O SPRAY MAY NOT BE EFT.H2O MAY BE USED TO COOL CLSD CNTNRS TO PVNT PRESS BUILD-UP & POSS (SUPP DATA)  
Unusual Fire/Explosion Hazard:EXTREME HEAT MAY CAUSE CLOSE CONTAINERS TO BURST.

## Accidental Release

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION. VENTILATE AND REMOVE WITH INERT ABSORBENT.  
Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

## Handling

Handling and Storage Precautions:KEEP CONTAINER CLOSED WHEN NOT IN USE. TRANSFER ONLY TO APPROVED CONTAINERS WITH COMPLETE AND APPROPRIATE LABELING. DOL STORAGE CAT 3B.  
Other Precautions:DO NOT TAKE INTERNALLY. KEEP OUT OF REACH OF CHILDREN. USE ONLY WITH ADEQ VENT. AVOID BREATHING VAPOR AND SPRAY MIST. AVOID CONTACT WITH SKIN AND EYES.

## Exposure Controls

Respiratory Protection:IF PERSONAL EXPOSURE CANNOT BE CONTROLLED BELOW APPLICABLE LIMITS BY VENTILATION, WEAR NIOSH/MSHA APPROVED RESPIRATORY DEVICE.  
Ventilation:LOCAL EXHAUST PREFERABLE, GENERAL EXHAUST ACCEPTABLE BELOW TLV. REFER TO OSHA 1910.94, .107,.108.

Protective Gloves:IMPERVIOUS GLOVES .  
Eye Protection:CHEMICAL WORKERS GOGGLES .  
Other Protective Equipment:NONE SPECIFIED BY MANUFACTURER.  
Work Hygienic Practices:WASH HANDS AFTER USING.  
Supplemental Safety and Health  
PH: 8.5-9.0. FIRE FIGHT PROC: AUTO IGNITION OR EXPLOSION WHEN EXPOSED  
TO EXTREME HEAT.

## Chemical Properties

HCC:V4  
Boiling Pt:B.P. Text:>212F,>100C  
Vapor Pres:ING 1 & 2  
Vapor Density:HVR/AIR  
Spec Gravity:1.3  
pH:SUPDAT  
Evaporation Rate & Reference:SLOWER THAN ETHER  
Appearance and Odor:NONE SPECIFIED BY MANUFACTURER.  
Percent Volatiles by Volume:54.66

## Stability

Stability Indicator/Materials to Avoid:YES  
NONE SPECIFIED BY MANUFACTURER.  
Stability Condition to Avoid:EXTREME HEAT AND OPEN FLAME.  
Hazardous Decomposition Products:BY FIRE: CO2 AND CO.

## Disposal

Waste Disposal Methods:INCINERATE IN APPROVED FACILITY. DO NOT  
INCINERATE CLOSED CONTAINERS. DISPOSE OF IN ACCORDANCE WITH  
FEDERAL, STATE, AND LOCAL REGULATIONS REGARDING POLLUTION.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.