

154A100, 5-STAR SWIMMING POOL PAINT (SUPP D

MSDS Number

BNBPG

National Stock Number

8010-00N028994

Product Name

154A100, 5-STAR SWIMMING POOL PAINT (SUPP D

Manufacturer

ACE HARDWARE CORP PAINT DIV

Product Identification

Product ID:154A100, 5-STAR SWIMMING POOL PAINT (SUPP D MSDS Date:10/01/1986 FSC:8010 NIIN:00N028994 MSDS Number: BNBPG

Responsible Party

ACE HARDWARE CORP/PAINT DIV

21901 SOUTH CENTRAL AVENUE

MATTESON, IL 60443

US

Emergency Phone: 312-720-0600

Info Phone: 312-720-0600

Cage: ACEHA

Contractor

ACE HARDWARE CORPORATION

MATTESON, IL 60443

US

708-720-0600

Cage: ACEHA

Ingredients

10 CAS: 64742-48-9 Fraction By Weight: 17.9% OSHA PEL100 PPM (MFR) ACGIH TLV: 100 PPM (MFR)

2

CAS: 64742-47-8 Fraction By Weight: 17% OSHA PEL500 PPM (MFR) ACGIH TLV: 100 PPM (MFR)

Hazards

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.



Routes of Entry: Inhalation:YES Skin:NO Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:ACUTE: INHAL: ANESTHETIC. IRRIT OF RESPIRATORY TRACT OR NERVOUS SYSTEM DEPRESSION. HEADACHE, DIZZINESS, NAUSEA, CONFUSION, UNCONSCIOUSNESS OR COMA. SKIN/EYE CONT: PRIMARY IRRITATION. CHRONIC: REPORTS HAVE ASSOCIATED REPEATED AND PROLONGED OCCUPATIONAL OVEREXPOSURE TO SOLVENTS WITH PERMANENT BRAIN & (EFTS OF OVEREX) Explanation of Carcinogenicity:NOT RELEVANT. Effects of Overexposure:HLTH HAZ: NERVOUS SYSTEM DAMAGE. Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

•

First Aid

First Aid:INHAL: REMOVE FROM EXPOSURE, RESTORE BREATHING. KEEP WARM AND QUIET, NOTIFY PHYSICIAN. EYES: FLUSH IMMED WITH RUNNING WATER FOR AT LEAST 15 MINUTES. SKIN: WASH WITH SOAP AND WATER AND APPLY SKIN CREAM . NOTIFY PHYSICIAN IN ALL CASES. INGEST: CALL MD .

Fire Fighting

Flash Point:103F,39C Lower Limits:0.7% Extinguishing Media:FOAM, "ALCOHOL" FOAM, CO2, DRY CHEMICAL. Fire Fighting Procedures:WEAR NIOSH/MSHA APPROVED SCBA AND FULL PROTECTIVE EQUIPMENT . Unusual Fire/Explosion Hazard:DO NOT USE NEAR HEAT, SPARKS, OPEN FLAME, OR STATIC DISCHARGE.

Accidental Release

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION, FLAMES, HOT SURF & ELECTRICAL STATIC OR FRICTIONAL SPARKS. AVOID BREATHING VAPORS; VENTILATE AREA. REMOVE WITH INERT ABSORBENT AND NONSPARKING TOOLS.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

Handling

Handling and Storage Precautions: DO NOT STORE IN TEMP ABOVE 120F. STORE LG QTY IN BLDG DESIGNATED & PROTECTED FOR STORAGE OF NFPA CLASS IA FLAMM LIQ.

Other Precautions: DO NOT USE NEAR OPEN FLAME. DO NOT TAKE INTERNALLY. CLOSE CONTAINER AFTER EACH USE. AVOID BREATHING VAPORS. KEEP OUT OF REACH OF CHILDREN. CONTAINERS SHOULD BE GROUNDED WHEN POURING.

Exposure Controls

Respiratory Protection:IF EYE WATERING, HDCH/DIZZ IS EXPERIENCED, INCR FRESH AIR, WEAR NIOSH/MSHA APPRVD RESP EQUIP (TC 23 C OR EQUIVALENT) OR LEAVE AREA. Ventilation:DO NOT FLAMECUT/BRAZE/WELD COATED PARTS W/OUT RESP PROT. PROVIDE GEN/DILUTING VENT SUFFICIENT TO KEEP VAP (SUPP DATA) Protective Gloves:RUBBER GLOVES. Eye Protection:CHEMICAL WORKERS GOGGLES . Other Protective Equipment:PREVENT PROLONGED SKIN CONTACT WITH CONTAMINATED CLOTHING. Work Hygienic Practices:REMOVE AND WASH CONTAMINATED CLOTHING, DISCARD CONTAMINATED SHOES. Supplemental Safety and Health MFR TRADE NAME/PART NO: BRILLANT WHITE. VENT: CONCENTRATION BELOW TLV AND LEL.

Chemical Properties

HCC:F4 Boiling Pt:B.P. Text:305F,152C Vapor Pres:SEE INGRED Vapor Density:HVR/AIR Spec Gravity:1.38-1.4 Evaporation Rate & Reference:SLOWER THAN ETHER Appearance and Odor:NONE SPECIFIED BY MANUFACTURER. Percent Volatiles by Volume:58-59



Stability

Stability Indicator/Materials to Avoid:YES STRONG OXIDIZING AGENTS. Stability Condition to Avoid:HIGH TEMPERATURES AND OPEN FLAME. Hazardous Decomposition Products:THERMAL DECOMPOSITION MAY YIELD CO (AS DURING A FIRE).

Disposal

Waste Disposal Methods: DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE, AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.