

## **207A100, 5-STAR BASEMENT WATER-PROOF (SUPP**

### **MSDS Number**

BNBPH

### **National Stock Number**

8010-00N028996

### **Product Name**

207A100, 5-STAR BASEMENT WATER-PROOF (SUPP

### **Manufacturer**

ACE HARDWARE CORP PAINT DIV

### **Product Identification**

Product ID:207A100, 5-STAR BASEMENT WATER-PROOF (SUPP

MSDS Date:10/01/1986

FSC:8010

NIIN:00N028996

MSDS Number: BNBPH

### **Responsible Party**

ACE HARDWARE CORP/PAINT DIV

21901 SOUTH CENTRAL AVENUE

MATTESON , IL 60443

US

Emergency Phone: 312-720-0600

Info Phone: 312-720-0600

Cage: ACEHA

### **Contractor**

ACE HARDWARE CORPORATION

MATTESON, IL 60443

US

708-720-0600

Cage: ACEHA

### **Ingredients**

KEROSENE (PETROLEUM), HYDROTREATED; (MINERAL SPIRITS). VP

CAS: 64742-47-8

Fraction By Weight: 27%

OSHA PEL500 PPM (MFR)

ACGIH TLV: 100 PPM (MFR)

10.

CAS: 64742-95-6

Fraction By Weight: 3%

OSHA PEL100 PPM

ACGIH TLV: 100 PPM

### **Hazards**

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:INHALATION IS ANESTHETIC. IRRITATION OF RESPIRATORY TRACT OR NERVOUS SYSTEM DEPRESSION. HEADACHE, DIZZINESS, NAUSEA, CONFUSION, UNCONSCIOUSNESS OR COMA. SKIN OR EYE CONTACT: PRIMARY IRRITATION. REPORT S HAVE ASSOCIATED REPEATED/PROLONGED OCCUPATIONAL OVEREXPOS TO SOLVENTS W/PERMANENT BRAIN/NERVS SYS DAMAGE.  
Explanation of Carcinogenicity:NOT RELEVANT.  
Effects of Overexposure:SEE HEALTH HAZARDS.  
Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

## First Aid

First Aid:INHAL: REMOVE FROM EXPOSURE, RESTORE BREATHING, KEEP WARM AND QUIET, NOTIFY MD. EYES: FLUSH IMMEDIATELY W/ RUNNING WATER FOR A MINIMUM OF 15 MINUTES. SKIN: WASH W/SOAP & WATER AND APPLY SKIN CREAM. NO TIFY MD IN ALL CASES. INGEST: CALL MD IMMEDIATELY .

## Fire Fighting

Flash Point:102F,39C  
Lower Limits:0.7%  
Extinguishing Media:FOAM, CO2, DRY CHEMICAL.  
Fire Fighting Procedures:WEAR NIOSH/MSHA APPROVED SCBA & FULL PROTECTIVE EQUIPMENT .  
Unusual Fire/Explosion Hazard:DO NOT USE NEAR HEAT, SPARKS, OPEN FLAME, OR STATIC DISCHARGE.

## Accidental Release

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION, FLAMES, HOT SURFACES AND ELECTRICAL STATIC OR FRICTIONAL SPARK. AVOID BREATHING VAPORS; VENTILATE AREA. REMOVE WITH INERT ABSORBENT AND NONSPARKING TOOLS.  
Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

## Handling

Handling and Storage Precautions:DO NOT STORE IN TEMPERATURES ABOVE 120F. STORE LARGE QUANTITIES IN BUILDING DESIGNATED AND PROTECTED FOR STORAGE OF NFPA CLASS 1A FLAMMABLE LIQUIDS.  
Other Precautions:DO NOT USE NEAR OPEN FLAME. DO NOT TAKE INTERNALLY. CLOSED CONTAINER AFTER EACH USE. AVOID BREATHING VAPORS. KEEP OUT OF REACH OF CHILDREN. CONTAINERS SHOULD BE GROUNDED WHEN POURING.

## Exposure Controls

Respiratory Protection:IF EYE WATERING, HEADACHE OR DIZZINESS IS EXPERIENCED, INCREASE FRESH AIR, OR WEAR APPROVED RESPIRATORY EQUIPMENT (NIOSH/MSHA TC 23C OR EQUIVALENT) OR LEAVE THE AREA. DO NOT FLAME CUT, BRAZE OR WELD C OATED PARTS W/O RESPIRATORY PROTECTION.  
Ventilation:PROVIDE GENERAL OR DILUTING VENTILATION SUFFICIENT TO KEEP VAPOR CONCENTRATION BELOW TLV AND LEL.  
Protective Gloves:RUBBER GLOVES.  
Eye Protection:CHEMICAL WORKERS GOGGLES .  
Other Protective Equipment:NONE SPECIFIED BY MANUFACTURER.  
Work Hygienic Practices:PREVENT PROLONGED SKIN CONTACT W/CONTAMINATED CLOTHING. REMOVE & WASH CONTAMINATED CLOTHING, DISCARD CONTAMINATED SHOES.  
Supplemental Safety and Health  
MFR'S TRADE NAME: MASONRY COATING WHITE.

## Chemical Properties

HCC:F4  
Boiling Pt:B.P. Text:>313F,>156C  
Vapor Pres:SEE INGRED  
Vapor Density:HVR/AIR  
Spec Gravity:1.5  
Evaporation Rate & Reference:SLOWER THAN ETHER  
Appearance and Odor:NONE SPECIFIED BY MANUFACTURER.

Percent Volatiles by Volume:55

## Stability

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS.

Stability Condition to Avoid:HIGH TEMPERATURES AND OPEN FLAME.

Hazardous Decomposition Products:THERMAL DECOMPOSITION MAY YIELD CARBON MONOXIDE (AS DURING A FIRE).

## Disposal

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE, AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.