

TT-E-489H Y83, B4892.5

MSDS Number

BNCCM

National Stock Number

8010-00-286-9088

Product Name

TT-E-489H Y83, B4892.5

Manufacturer

DAVLIN PAINT CO INC

Product Identification

Product ID:TT-E-489H Y83, B4892.5

MSDS Date:03/20/1992

FSC:8010

NIIN:00-286-9088

MSDS Number: BNCCM

Responsible Party

DAVLIN PAINT CO INC

700 ALLSTON WAY

BERKELEY , CA 94702

US

Emergency Phone: 510-848-2863

Info Phone: 510-848-2863

Preparer: PATRICIA SHAW

Cage: 3Z268

Contractor

DAVLIN PAINT CO INC

2308

BERKELEY, CA 94702

US

510-848-2863

Cage: 3Z268

Ingredients

N-BUTYL ACETATE (SARA III) (VAPOR PRESSURE 8.7 MM HG @

CAS: 123-86-4

RTECS: AF7350000

Fraction By Weight: 5%

OSHA PEL150 PPM

ACGIH TLV: 150 PPM

EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

XYLENE (SARA III) (VAPOR PRESSURE 11.0 MM HG @ 77F)

CAS: 1330-20-7

RTECS: ZE2100000

Fraction By Weight: 5%

OSHA PEL100 PPM

ACGIH TLV: 100 PPM

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

BARIUM SULFATE (SARA III)

CAS: 7727-43-7

RTECS: CR0600000

Fraction By Weight: 8%

OSHA PEL15 MG/M3 TDUST

ACGIH TLV: 10 MG/M3 TDUST; 9293

SOLVENT NAPHTHA (VAPOR PRESSURE 10.3 MM HG @ 100F)

CAS: 64742-95-6

Fraction By Weight: 15%

Hazards

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:INHAL: NASAL & RESP IRRIT, NARCOSIS (CNTRL NERV SYS DEPRESS). EYE: SEVERE IRRIT. SKIN: IRRIT, DEFAT, DERMATITIS. INGEST: DIGEST TRACT IRRIT, CNTRL NERV SYS DEPRESS. ASPIRATION HZD. MAT'L ENTER LUNGS (SWALLOW/VOMIT), CAUSE LUNG INFLAMM. CHRONIC: CNTRL NERV SYS/ RESP SYS/LUNG/EYE/SKIN/GI TRACT/LIVER/SPLEEN/KIDNEY DAMAGE.

Effects of Overexposure:INHALATION: DIZZINESS, WEAKNESS, FATIGUE, NAUSEA, AND HEADACHE. EYE: TEARING, REDNESS, AND BLURRED VISION.

Medical Cond Aggravated by Exposure:RESPIRATORY TRACT IRRITATION, DERMATITIS, NAUSEA.

First Aid

First Aid:EYE: FLUSH W/WATER 15 MIN, OCCASIONALLY LIFTING EYELIDS. GET MED ATTN. SKIN: REMOVE CONTAMINATED CLOTHING, WASH W/ SOAP & WATER. IF IRRITATION PERSISTS, SEE DR. INHAL: REMOVE TO FRESH AIR. APPLY ARTIF RESPIRATION/ADMINISTER OXYGEN IF NEEDED. CONSULT DR. INGEST: GIVE WATER/MILK TO DRINK. PHONE FOR MED ADVICE. DON'T INDUCE VOMIT UNLESS DIRECTED BY MED PERSONNEL. IF ADVICE UNAVAIL, TAKE TO EMERG ROOM

Fire Fighting

Flash Point Method:TCC

Flash Point:76.0F,24.4C

Lower Limits:1.0

Upper Limits:7.6

Extinguishing Media:FOAM, ALCOHOL FOAM, CO2, DRY CHEMICAL, WATER FOG.

Fire Fighting Procedures:USE EXTINGUISHER (NFPA FLAMMABLE LIQ FIRE).

WATER MAY BE INEFFECTIVE, USE AS FOG FOR COOLING. WEAR FULL

PROTECTIVE CLOTHING & BREATHING APPARATUS.

Unusual Fire/Explosion Hazard:VAPORS FORM EXPLOSIVE MIX W/AIR (LEL TO UEL) WHICH CAN BE IGNITED BY MANY SOURCES. CLOSED CNTNRS MAY EXPLODE W/HEAT. ISOLATE FROM HEAT/IGNITION SOURCES.

Accidental Release

Spill Release Procedures:EVACUATE ALL NON-ESSENTIAL PERSONNEL. REMOVE ALL IGNITION SOURCES. VENTILATE AREA. PROVIDE PROTECTIVE EQUIPMENT.

DIKE AROUND SPILL AREA. COVER SPILL WITH INERT ABSORBENT AND TRANSFER USING NON- SPARKING TOOLS.

Handling

Handling and Storage Precautions:STORE BELOW 80 F IN CLOSED CONTAINER. STORE IN ORIGINAL CONTAINER. AVOID FLAME AND HIGH TEMPERATURES. DO NOT STORE NEAR OXIDIZING AGENTS OR ACIDS.
Other Precautions:VAPOR IS HEAVIER THAN AIR, MAY TRAVEL CONSIDERABLE DISTANCE TO IGNITION SOURCE & FLASHBACK. DON'T INGEST OR INHALE. GROUND ALL CONNECTIONS, CONTAINERS, ETC WHEN POURING OR TRANSFERING TO MINIMIZE STAT IC ELECTRICITY. USE NON-SPARK TOOLS.

Exposure Controls

Respiratory Protection:USE NIOSH/MSHA EQUIPMENT WHEN AIRBORNE EXPOSURE LIMITS ARE EXCEEDED. CONSULT RESPIRATOR MANUFACTURER TO DETERMINE EQUIPMENT FOR GIVEN APPLICATION. HIGH AIRBORNE CONCENTRATIONS MAY REQUIRE USE OF SUPPLIED-AIR RESPIRATOR OR SCBA.
Ventilation:PROVIDE VENTILATION TO CONTROL EXPOSURE LEVELS BELOW AIRBORNE EXPOSURE LIMITS. VENT EQUIPMENT MUST BE EXPLOSION PROOF.
Protective Gloves:CONSULT GLOVE MFR TO DETERMINE TYPE.
Eye Protection:CHEMICAL SAFETY GLASSES OR GOGGLES.
Other Protective Equipment:WEAR IMPERMEABLE APRONS & PROTECT CLOTHES WHEN POSSIBLE TO PREVENT REPEAT/EXTEND EXPOSURE OF SKIN. HEAD CAPS RECOMMENDED
Work Hygienic Practices:AFTER USING, WASH BEFORE EATING, TOILETING OR SMOKING.
Supplemental Safety and Health

Chemical Properties

HCC:F3
Boiling Pt:B.P. Text:259 TO 315F
Vapor Density:> AIR
Spec Gravity:1.3 (WATER=1)
Evaporation Rate & Reference:SLOWER THAN ETHER
Solubility in Water:NOT WATER SOLUBLE
Appearance and Odor:PIGMENTED LIQUID. SOLVENT ODOR.

Stability

Stability Indicator/Materials to Avoid:YES
STRONG OXIDIZING AGENTS.
Stability Condition to Avoid:DO NOT EXPOSE TO HEAT OR IGNITION SOURCES.
Hazardous Decomposition Products:THERMAL DECOMPOSITION MAY YIELD CARBON DIOXIDE AND/OR MONOXIDE, LOW MOLECULAR WEIGHT HYDROCARBONS & ORGANIC ACIDS.

Disposal

Waste Disposal Methods:KEEP OUT OF DRAINS, SEWERS AND WATERWAYS. DISPOSE OF PRODUCT IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.