

# **TT-E-489G OLIVE DRAB 14084**

### **MSDS Number**

**BNCCT** 

## **National Stock Number**

8010-00-297-2005

### **Product Name**

TT-E-489G OLIVE DRAB 14084

#### Manufacturer

CHEMRAY COATING CORP

### **Product Identification**

Product ID:TT-E-489G OLIVE DRAB 14084 MSDS Date:10/25/1989 FSC:8010 NIIN:00-297-2005 MSDS Number: BNCCT

# **Responsible Party**

CHEMRAY COATING CORP

209 N MICHIGAN AVE

KENILWORTH, NJ 07033

US

Emergency Phone: 800-424-9300(CHEMTREC)201-245-1111

Info Phone: 201-245-1111
Preparer: FRED ARMSTRONG

Cage: 33832

Contractor

CHEMRAY COATING CORP

KENILWORTH, NJ 07033

US

201-245-1111 Cage: 33832

# **Ingredients**

CAS: 8052-41-3

PETROLEUM SOLVENT, M.S. 66

RTECS: WJ8925000 Fraction By Weight: 54% OSHA PEL500 PPM

ACGIH TLV: 100 PPM; 9293

LEAD AD. (PB), LEAD DRIER.

Fraction By Weight: 1%
OSHA PEL0.05 MG/M3
ACGIH TLV: 0.05 MG/M3

**Hazards** 



Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO

Health Hazards Acute and Chronic: NAUSEA, HEADACHE, DIZZINESS CAUSED BY

OVER INHALATION.

Medical Cond Aggravated by Exposure: NONE GENERALLY KNOWN.

### First Aid

First Aid: EYE: FLUSH WITH WATER 15 MINUTES OR UNTIL IRRITATION SUBSIDES. IF IRRITATION PERSISTS CALL PHYSICIAN. SKIN: REMOVE CONTAMINATED CLOTHING AND WASH THOROUGHLY WITH SOAP AND WATER. INHALATION: IF OVERCOM E BY VAPORS, REMOVE TO FRESH AIR. CALL PHYSICIAN. INGESTION: DO NOT INDUCE VOMITING. CALL PHYSICIAN.

## Fire Fighting

Flash Point Method:SCC Flash Point:103F,39C

Autoignition Temp: Autoignition Temp Text: 473 F

Lower Limits: 0.9 Upper Limits: 7

Extinguishing Media: CARBON DIOXIDE, FOAM, WATER FOG, DRY CHEMICAL. Fire Fighting Procedures: USE AIR SUPPLIED BREATHING EQUIPMENT, COOL ENCLOSED CONTAINERS WITH WATER SPRAY, AVOID BREATHING VAPOR OR FUMES.

Unusual Fire/Explosion Hazard:IF LEAK OR SPILL HAS IGNITED, USE WATER SPRAY TO DISPERSE THE VAPORS FROM FIRE FIGHTERS.

#### **Accidental Release**

Spill Release Procedures: RMV ALL IGNIT SOURCES. KEEP FROM HEAT SPARKS/OPEN FLAME. ADD ABSORB (SAND, EARTH, SAWDUST) TO SPILL. VENTILATE AREA (OPEN WINDOWS, DOORS) IF LARGE SPILL KEEP PRODUCT FROM ENTERING SEWERS & WATERCOURSE S BY DIKING. ADVISE AUTHORITIES IF PRODUCT ENTERED

### Handling

Handling and Storage Precautions:STORE AWAY FROM IGNITION SOURCES, KEEP IN COOL, DRY, WELL VENTILATED AREAS. AVOID DIRECT SUNLIGHT AND EXTREME TEMPERATURES - HOT OR COLD.

Other Precautions: AVOID EYE, SKIN CONTACT, INHALATION INGESTION OF MISTS, SPRAY OR VAPORS. AVOID BREATHING SANDING OR BLASTING DUST.

#### **Exposure Controls**

Respiratory Protection: USE HYDROCARBON VAPOR CANISTER OR SUPPLIED AIR RESPIRATORY IN CONFINED AREA.

Ventilation:LOCAL EXHAUST-FACE VELOCITY 60 FPM SPECIAL-USE ONLY WITH ADEQUATE VENTILATION. MECHANICAL-USE EXPLOSION PROOF EQUIPMENT. Protective Gloves:CHEMICAL RESISTANT.

Eye Protection: SPLASH GOGGLES OR FACE SHIELD.

Other Protective Equipment: USE CHEM RESISTANT APRON OR CLOTHING.

Supplemental Safety and Health

### **Chemical Properties**

HCC:F4

Boiling Pt:B.P. Text:308 F Melt/Freeze Pt:M.P/F.P Text:0 F Decomp Temp:Decomp Text:600 F Vapor Pres:Vapor Density:4.8 Spec Gravity:.924

Spec Gravity:.924 Viscosity:67-77

Evaporation Rate & Reference: 0.09 (BUTYL ACETETE)

Solubility in Water: NEGLIGIBLE

Appearance and Odor: BLUE LIQUID WITH KEROSENE ODOR.

Percent Volatiles by Volume: 64.4

## **Stability**

Stability Indicator/Materials to Avoid:YES
CAN REACT WITH OXIDIZING MATERIAL WHEN HEATED TO DECOMPOSTION.
Stability Condition to Avoid:HIGH TEMPERATURE.



Hazardous Decomposition Products: CARBON MONOXIDE.

### **Disposal**

Waste Disposal Methods: ASSURE CONFORMITY WITH APPLICABLE DISPOSAL REGULATIONS DISPOSE OF ABSORBED MATERIAL AT AN APPROVED DISPOSAL SITE OR FACILITY. DISPOSE IN CONFORMITY WITH STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.