•



ACRYLIC LATEX FLAT SUPER WHITE

MSDS Number

BNCFM

National Stock Number

8010-00-598-5733

Product Name

ACRYLIC LATEX FLAT SUPER WHITE

Manufacturer

DELAWARE VALLEY PAINT CO

Product Identification

Product ID:ACRYLIC LATEX FLAT SUPER WHITE MSDS Date:08/12/1988 FSC:8010 NIIN:00-598-5733 MSDS Number: BNCFM

Responsible Party

DELAWARE VALLEY PAINT CO.

2063 E SILVER ST.

PHILADELPHIA, PA 19134

US

Emergency Phone: 215-739-3555 24 HR

Info Phone: 215-739-3555 24 HR

Cage: 0G509

Contractor

DELAWARE VALLEY PAINT CO.

PHILADELPHIA, PA 19134

US

215-739-3555 24 HR

Cage: 0G509

Ingredients

NON-HAZARDOUS MATERIAL ACCORDING TO OSHA, HAZARDOUS

Hazards

Health Hazards Acute and Chronic: MAY BE EYE IRRITANT. VAPORS MAY IRRITATE RESPIRATORY TRACT. MILDLY IRRITATING TO SKIN. Effects of Overexposure: PROLONGED EXPOSURE MAY CAUSE HEADACHE AND NAUSEA.

First Aid

First Aid:INHALE-REMOVE TO FRESH AIR.EYES-FLUSH WITH WATER FOR 15 MINUTES.SKIN-WASH WITH SOAP AND WATER.REMOVE CONTAMINATED CLOTHING AND WASH PRIOR TO REUSE.CALL PHYSICIAN IMMEDIATELY.

Fire Fighting

Flash Point:NONE
Extinguishing Media:ALL MEDIA
Unusual Fire/Explosion Hazard:MATERIAL CAN SPLATTER ABOVE BOILING
POINT.DRIED POLYMER FILM CAN BURN.

Accidental Release



Spill Release Procedures: HANDLE AS NORMAL SOLID WASTE; SCOOP UP AND PLACE IN WASTE CONTAINER. KEEP SPILL OUT OF DRAINS, SEWERS AND WATERWAYS. SPILLED MATERIAL IS SLIPPERY.

Handling

Handling and Storage Precautions:PROTECT FROM FREEZING.STORE COOL AND DRY AT AMBIENT TEMPREATURE AWAY FROM FOOD AND DRINK.

Other Precautions:AVOID PROLONGED BREATHING AND CONTACT WITH SKIN.

Exposure Controls

Respiratory Protection:NONE IF GOOD VENTILATION IS PROVIDED. MSHA/NIOSH APPROVED IF NEEDED.
Ventilation:EXHAUST AT POINT OF USE.
Protective Gloves:IMPERVIOUS TO SOLVENTS.
Eye Protection:SPLASHPROOF SAFETY GLASSES.
Supplemental Safety and Health
NK

Chemical Properties

Boiling Pt:B.P. Text:212F,100C
Melt/Freeze Pt:M.P/F.P Text:32.0F,0.0C
Spec Gravity:1.44
Evaporation Rate & Reference:SLOWER(TO N-BUTYL ACETATE
Solubility in Water:COMPLETE (99.9%)
Appearance and Odor:WHITE LIQUID WITH MILD ODOR
Percent Volatiles by Volume:60.78%

Stability

Stability Indicator/Materials to Avoid:YES NK

Disposal

Waste Disposal Methods: DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.