

G 800, WALK-A-PON VIN/EXOX FL PT

MSDS Number

BNDHD

National Stock Number

8010-00N029535

Product Name

G 800, WALK-A-PON VIN/EXOX FL PT

Manufacturer

EVR GARD COATINGS CO

Product Identification

Product ID:G 800, WALK-A-PON VIN/EXOX FL PT

MSDS Date:01/01/1989

FSC:8010

NIIN:00N029535

MSDS Number: BNDHD

Responsible Party

EVR-GARD COATINGS CO

16400 GARFIELD AVE

PARAMOUNT , CA 90723

US

Emergency Phone: 213-531-0131

Info Phone: 213-531-0131

Cage: 5G582

Contractor

EVR-GARD COATINGS CO

PARAMOUNT, CA 90723

US

310-531-0131

Cage: 5G582

Ingredients

5.0 @ 68F.

Fraction By Weight: 10.41%

OSHA PEL125 PPM (MFR)

Hazards

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.

Routes of Entry: Inhalation:YES Skin:NO Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:INHAL:MAY CAUSE HEADACHE, NAUSEA, DIZZINESS. SKIN/EYE:IRRITANT. REDNESS OR RASH ON SKIN.

INGEST:NAUSEA, DIZZINESS, HEADACHES.

Explanation of Carcinogenicity:NOT RELEVANT.

Effects of Overexposure:PROLONGED INHALATION MAY CAUSE HEADACHE AND NAUSEA. PROLONGED CONTACT WITH MATERIAL MAY CAUSE DERMATITIS.

Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

First Aid

First Aid:INHAL:MOVE TO FRESH AIR. EYE:FLUSH WITH WATER FOR AT LEAST 15 MINUTES. SKIN:REMOVE SATURATED CLOTHING AND WASH SKIN WITH SOAPY

WATER THOROUGHLY. INGEST:INDUCE VOMITING WITH 1 OZ OF SYRUP OF IPECAC FOL LOWED IN 5 MINUTES WITH A GLASS OF WATER. CALL MD.

Fire Fighting

Lower Limits:0.6%

Extinguishing Media:FOAM, ALCOHOL FOAM, CO2, DRY CHEMICAL, WATER FOG.

Fire Fighting Procedures:WEAR NIOSH/MSHA APPROVED SCBA AND FULL PROTECTIVE EQUIPMENT . THIS IS A WATER BASED PRODUCT. WILL NOT SUPPORT COMBUSTION.

Unusual Fire/Explosion Hazard:NONE.

Accidental Release

Spill Release Procedures:ABSORB SPILL WITH ANY ABSORBENT MATERIAL- SAWDUST, SAND, CLAYS, ETC., AND FLUSH SPILL AREA WITH LOTS OF WATER.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

Handling

Handling and Storage Precautions:THIS PRODUCT IS STABLE UNDER NORMAL USE AND STORAGE CONDITIONS.

Other Precautions:KEEP OUT OF REACH OF CHILDREN. KEEP FROM FREEZING. DO NOT TAKE INTERNALLY.

Exposure Controls

Respiratory Protection:THE USE OF NIOSH/MSHA APPROVED MASKS DURING APPLICATION TO AVOID EXCESSIVE INHALATION OF VAPORS IS HIGHLY RECOMMENDED. OPEN WINDOWS & DOOR OR USE OHTER MEANS TO INSURE FRESH AIR ENTRY DURING APPLICATIO N AND DRYING.

Ventilation:PROVIDE ADEQ VENT AT ALL TIMES DURING HANDLING AND APPLICATION OF PRODUCT. INSURE ADEQ SUPPLY OF FRESH AIR AT ALL TIMES.

Protective Gloves:BUNA N GLOVES.

Eye Protection:CHEMICAL WORKERS GOGGLES .

Other Protective Equipment:MASKS AND GLOVES IF NECESSARY.

Work Hygienic Practices:OBSERVE STANDARD HYGIENIC PRACTICES WHEN HANDLING THIS PRODUCT.

Supplemental Safety and Health
NONE SPECIFIED BY MANUFACTURER.

Chemical Properties

HCC:N1

Vapor Pres:SEE ING

Vapor Density:HVR/AIR

Spec Gravity:1.3 (H2O=1)

Evaporation Rate & Reference:SLOWER THAN ETHER

Solubility in Water:DILUTABLE

Appearance and Odor:WHITE PAINT AND COLORS WITH SLIGHT AMMONIA SMELL

Stability

Stability Indicator/Materials to Avoid:YES

STRONG ACIDS AND ALKALIES AND MATERIALS THAT REACT WITH WATER.

Stability Condition to Avoid:DO NOT STORE IN HIGH TEMPERATURE AREAS.

Hazardous Decomposition Products:NONE.

Disposal

Waste Disposal Methods:PLACE ALL HAZARDOUS WASTES, INCLUDING ABSORBENTS USED FOR SPILLS, IN 55-GAL METAL DRUMS AND DISPOSE IN APPROVED DUMPSITE IN ACCORDANCE WITH PRESCRIBED FEDERAL, STATE, AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their

particular situation.