

62-3037, FUSER LUBRICANT (K355, K403, K555)

MSDS Number

BNDPF

National Stock Number

9150-00N029860

Product Name

62-3037, FUSER LUBRICANT (K355, K403, K555)

Manufacturer

A B DICK CO

Product Identification

Product ID:62-3037, FUSER LUBRICANT (K355, K403, K555)

MSDS Date:11/10/1986

FSC:9150

NIIN:00N029860

MSDS Number: BNDPF

Responsible Party

A B DICK CO

5700 WEST TOUHY AVE

CHICAGO , IL 60648

US

Emergency Phone: 312-763-1900

Info Phone: 312-763-1900

Preparer: KENNETH W.PINTER

Cage: HO951

Contractor

DICK A B CO

CHICAGO, IL 60648

US

312-647-8800

Cage: HO951

Ingredients

DOW CORNING 200 FLUID(DIMETHYL SILOXANE)

CAS: 63148-62-9

RTECS: JT6484500

Fraction By Weight: 100%

Hazards

LD50 LC50 Mixture:LD50: (ORAL,RAT) 35 G/KG.

Routes of Entry: Inhalation:YES Skin:NO Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:MAY CAUSE MINIMAL IRRITATION OF
RESPIRATORY PASSAGES ON CONTINUAL EXPOSURE TO HIGH CONCENTRATIONS.

Explanation of Carcinogenicity:NOT RELEVANT.

Effects of Overexposure:SEE HEALTH HAZARDS.

Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

First Aid

First Aid:INGESTION: DILUTE STOMACH CONTENTS WITH SEVERAL GLASSES OF

WATER. EYES: FLUSH EYES THOROUGHLY WITH WATER FOR AT LEAST 15 MINUTES. SKIN: WASH WITH SOAP AND WATER. INHALATION: REMOVE FROM EXPOSURE.

Fire Fighting

Flash Point Method:COC
Flash Point:>500F,>260C
Extinguishing Media:WATER FOG, FOAM, CO2.
Fire Fighting Procedures:WEAR NIOSH/MSHA APPROVED SCBA AND FULL PROTECTIVE EQUIPMENT .
Unusual Fire/Explosion Hazard:NONE.

Accidental Release

Spill Release Procedures:SOAK UP WITH ABSORBENT MATERIAL.
Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

Handling

Handling and Storage Precautions:USE REASONABLE CARE AND CAUTION. CLEAN UP SPILLS COMPLETELY AS RESIDUE IS SLIPPERY.
Other Precautions:NONE.

Exposure Controls

Respiratory Protection:WEAR NIOSH/MSHA APPROVED RESPIRATOR APPROPRIATE FOR EXPOSURE OF CONCERN .
Ventilation:NORMAL OFFICE CONDITIONS.
Protective Gloves:IMPERVIOUS GLOVES .
Eye Protection:CHEMICAL WORKERS GOGGLES .
Other Protective Equipment:NONE REQUIRED WHEN USED AS INTENDED.
Work Hygienic Practices:NONE SPECIFIED BY MANUFACTURER.
Supplemental Safety and Health
NONE SPECIFIED BY MANUFACTURER.

Chemical Properties

HCC:V6
Boiling Pt:B.P. Text:300F,149C
Vapor Pres:Spec Gravity:0.98 (H2O=1)
Solubility in Water:NEGLIGIBLE
Appearance and Odor:CLEAR LIQUID, SLIGHT ODOR.
Percent Volatiles by Volume:

Stability

Stability Indicator/Materials to Avoid:YES
STRONG OXIDIZING AGENTS.
Stability Condition to Avoid:NONE.
Hazardous Decomposition Products:SILICONE DIOXIDE, CARBON DIOXIDE AND TRACES OF INCOMPLETELY BURNED CARBON PRODUCTS.

Disposal

Waste Disposal Methods:ABSORB LIQUID ON VERMICULITE OR OTHER ABSORBENT MATERIAL. DISPOSE OF IN ACCORDANCE WITH FEDERAL, STATE, AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.