

BARIUM IN HNO*3 1000 UG/ML, I56012

MSDS Number

BNLWT

National Stock Number

6810-00N027418

Product Name

BARIUM IN HNO*3 1000 UG/ML, I56012

Manufacturer

PLASMA CHEM ASSOCIATES INC

Product Identification

Product ID:BARIUM IN HNO*3 1000 UG/ML, I56012

MSDS Date: 07/01/1991

FSC:6810

NIIN:00N027418 MSDS Number: BNLWT

Responsible Party

PLASMA-CHEM ASSOCIATES INC

5142 W HURLEY POND ROAD

FARMINGDALE, NJ 07727

US

Emergency Phone: 908-919-0509

Info Phone: 908-919-0509

Cage: 0L438

Contractor

PLASMA-CHEM ASSOCIATES INC

FARMINGDALE, NJ 07727

US

908-919-0509 Cage: 0L438

Ingredients

2)

CAS: 10022-31-8

RTECS: CQ9625000

Fraction By Weight: 0.1-1%

OSHA PELO.5 MG/M3 (BA)

ACGIH TLV: 0.5 MG/M3 (BA)

NITRIC ACID

CAS: 7697-37-2

RTECS: QU5775000

Fraction By Weight: 2%

OSHA PEL2 PPM;4 PPM STEL

ACGIH TLV: 2 PPM;4 PPM STEL



EPA Report Quantity: 1000 LBS DOT Report Quantity: 1000 LBS

WATER

CAS: 7732-18-5 RTECS: ZC0110000

Fraction By Weight: 98%

Hazards

LD50 LC50 Mixture: NONE SPECIFIED BY MANUFACTURER. Routes of Entry: Inhalation: YES Skin: YES Ingestion: YES Reports of Carcinogenicity: NTP: NO IARC: NO OSHA: NO

Health Hazards Acute and Chronic: NONE LISTED BY MANUFACTURER.

Explanation of Carcinogenicity: NOT RELEVANT

Effects of Overexposure: BURNS, COUGHING, IRRITATION, NAUSEA, VOMITING,

LABORED BREATHING.

Medical Cond Aggravated by Exposure: NONE.

First Aid

First Aid: EYES: FLUSH WITH WATER FOR AT LEAST 15 MINUTES. SKIN: FLUSH WITH WATER FOR 15 MINUTES. WASH CONTAMINATED CLOTHING BEFORE REUSE. INHAL: REMOVE TO FRESH AIR. INGEST: DO NOT INDUCE VOMITING. GIVE COPIOUS AMOUNTS OF WATER OR MILK.

Fire Fighting

Extinguishing Media:WATER.
Fire Fighting Procedures:WEAR NIOSH/MSHA APPROVED SCBA & FULL PROTECTIVE EQUIPMENT .
Unusual Fire/Explosion Hazard:NONE.

Accidental Release

Spill Release Procedures:TAKE UP WITH INERT, ABSORBMENT MATERIAL. CONTAINERIZE FOR DISPOSAL. FLUSH SPILL AREA WITH WATER. Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

Handling

Handling and Storage Precautions: STORE IN A CORROSION FREE AREA. KEEP CONTAINER SEALED.
Other Precautions: NONE.

Exposure Controls

Respiratory Protection: NIOSH/MSHA APPROVED RESPIRATOR.

Ventilation: LOCAL EXHAUST RECOMMENDED.

 $\label{lem:protective} Protective \ Gloves: \ NEOPRENE \ GLOVES \ RECOMMENDED.$

Eye Protection: CHEMICAL WORKERS GOGGLES .

Other Protective Equipment: LAB COAT OR APRON.

Work Hygienic Practices: USUAL.

Supplemental Safety and Health

NONE SPECIFIED BY MANUFACTURER.

Chemical Properties

HCC:N1

Boiling Pt:B.P. Text:212F,100C

Spec Gravity:1

Evaporation Rate & Reference:1 (WATER = 1)

Solubility in Water:SOLUBLE

Appearance and Odor: CLEAR, COLORLESS, ODORLESS SOLUTION.

Stability

Stability Indicator/Materials to Avoid:YES STRONG BASES OR STRONG REDUCING AGENTS. Stability Condition to Avoid:EXCESSIVE HEAT OR COLD.



Hazardous Decomposition Products: NO*X.

Disposal

Waste Disposal Methods: CORROSIVE WASTE. DISPOSE OF IN ACCORDANCE WITH ALL FEDERAL, STATE AND LOCAL ENVIRONMENTAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.