

AS953, BRUSH ON SEALER & PREP COAT

MSDS Number

BNPCZ

National Stock Number

8010-00N030686

Product Name

AS953, BRUSH ON SEALER & PREP COAT

Manufacturer

DUNCAN ENTERPRISES

Product Identification

Product ID:AS953, BRUSH ON SEALER & PREP COAT

MSDS Date:08/01/1987

FSC:8010

NIIN:00N030686

MSDS Number: BNPCZ

Responsible Party

DUNCAN ENTERPRISES

5673 E SHIELDS AVE

FRESNO , CA 93727

US

Emergency Phone: 303-623-4884

Info Phone: 209-291-4444

Cage: 21546

Contractor

DUNCAN ENTERPRISES

FRESNO, CA 93727

US

209-291-4444

Cage: 21546

Ingredients

NONHAZARDOUS INGREDIENTS

Hazards

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.

Routes of Entry: Inhalation:YES Skin:NO Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:NON TOXIC. ABRASIVE CAN SCRATCH EYE.
OVEREXPOSURE CAN CAUSE DRY SKIN.

Explanation of Carcinogenicity:NOT RELEVANT

First Aid

First Aid:EYE: FLUSH WITH WATER FOR AT LEAST 15 MIN. SKIN: WASH WITH
SOAP AND WATER. INHAL: REMOVE TO FRESH AIR. SUPPORT BRTHG. (GIVE
O2/ARTF RESP) . INGEST: CALL MD IMMED .

Fire Fighting

Extinguishing Media:WATER BASED MATERIAL. MEDIA SUITABLE FOR
SURROUNDING FIRE .

Fire Fighting Procedures:WEAR NIOSH/MSHA APPROVED SCBA AND FULL
PROTECTIVE EQUIPMENT .

Unusual Fire/Explosion Hazard:NONE.

Accidental Release

Spill Release Procedures:CLEAN UP PROPERLY WITH PAPER TOWELS AND WET SPONGE.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

Handling

Handling and Storage Precautions:KEEP SEALED.

Exposure Controls

Respiratory Protection:IF SPRAYING, DO NOT INHAL MIST. USE NIOSH/MSHA APPROVED RESPIRATOR FOR SPRAYS AND MIST.

Ventilation:MECH(GEN): EXHAUST SPRAY TO OUTSIDE. SPECIAL: USE A NIOSH/MSHA APPROVED RESPIRATOR WHEN SPRAYING.

Protective Gloves:IMPERVIOUS GLOVES .

Eye Protection:CHEMICAL WORKERS GOGGLES .

Other Protective Equipment:NONE NEEDED.

Work Hygienic Practices:GOOD CLEANLINESS. AVOID EYE CONTACT.

Supplemental Safety and Health

NONE SPECIFIED BY MANUFACTURER.

Chemical Properties

HCC:N1

Boiling Pt:B.P. Text:212F,100C

Melt/Freeze Pt:M.P/F.P Text:1800F,982C

Spec Gravity:1.1(H2O=1)

Evaporation Rate & Reference:1(BUTYL ACETATE=1)

Solubility in Water:INSOLUBLE

Appearance and Odor:OPAQUE COLORED LATEX PAINT.

Stability

Stability Indicator/Materials to Avoid:YES

Disposal

Waste Disposal Methods:PUT PAPER TOWEL IN TRASH AND RINSE OUT SPONGE. DISPOSE OF IN ACCORDANCE WITH FEDERAL, STATE AND LOCAL REGULATIONS

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.