
PR-9021 CLASS A, PART B

MSDS Number

BNRMN

National Stock Number

8030-00-083-6523

Product Name

PR-9021 CLASS A, PART B

Manufacturer

COURTAULDS AEROSPACE INC

Product Identification

Product ID:PR-9021 CLASS A, PART B

MSDS Date:02/08/1989

FSC:8030

NIIN:00-083-6523

Kit Part:Y

MSDS Number: BNRMN

Responsible Party

COURTAULDS AEROSPACE INC

757 CALIFORNIA ST

GLENDALE , CA 91203

US

Emergency Phone: 818-549-7973

Info Phone: 818-549-7973

Preparer: JESLINE SAMSON

Cage: 83574

Contractor

PRC-DESOTO INTERNATIONAL, INC. A PPG INDUSTRIES COMPANY

1800

GLENDALE, CA 91209

US

818-240-2060

Cage: 83574

Ingredients

2-BUTANONE (METHYL ETHYL KETONE) (SARA III)

CAS: 78-93-3

RTECS: EL6475000

Fraction By Weight: 10%

OSHA PEL200 PPM/300 PPM STEL

ACGIH TLV: 200 PPM/300 PPM STEL

EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

PHENOL POLYMER WITH FORMALDEHYDE (PHENOLIC RESIN)

CAS: 9003-35-4

Fraction By Weight:

ISOPROPYLIDENEDIPHENOLEPICHLOOROHYDRIN RESIN (EPOXY RESIN)

CAS: 25068-38-6

RTECS: KC2100000

Fraction By Weight:

142.44

RTECS: 9999999VO

Hazards

Routes of Entry: Inhalation: YES Skin: YES Ingestion: YES
Reports of Carcinogenicity: NTP: NO IARC: NO OSHA: NO
Health Hazards Acute and Chronic: EYES: IRRITATION. SKIN: LOCAL IRRITATION. PROLONGED OR REPEATED EXPOSURE MAY CAUSE DRYING AND CRACKING OF SKIN &/OR DERMATITIS. INHALATION: IRRITATION TO NOSE AND THROAT. PROLONGED EXPOSURE ABOVE PEL MAY CAUSE HEADACHE, DIZZINESS, AND UNCONSCIOUSNESS. INGESTION: MAY CAUSE NAUSEA, VOMITING, LIVER & KIDNEY DAMAGE.

First Aid

First Aid: EYES: FLUSH WITH LUKEWARM WATER FOR 15 MINUTES. IF SYMPTOMS PERSIST, CONSULT PHYSICIAN. SKIN: WASH WITH SOAP AND WATER. IF SYMPTOMS PERSIST, CONSULT A PHYSICIAN. INHALATION: REMOVE TO FRESH AIR. IF SYMPTOMS ARE PRESENT CONSULT A PHYSICIAN. INGESTION: CONSULT A PHYSICIAN.

Fire Fighting

Flash Point Method: PMCC
Flash Point: 23.0F, -5.0C
Lower Limits: 1.8
Upper Limits: 10 (MEK)
Extinguishing Media: CO2, DRY CHEMICAL, FOAM, WATER FOG.
Fire Fighting Procedures: USE COMPLETE PERSONAL PROTECTION. USE WATER TO COOL HEAT EXPOSED CONTAINERS.
Unusual Fire/Explosion Hazard: HIGH TEMPERATURES MAY CAUSE PRESSURE BUILDUP IN CLOSED CONTAINERS.

Accidental Release

Spill Release Procedures: REMOVE ALL IGNITION SOURCES. WEAR AIR-SUPPLIED RESPIRATOR FOR MAJOR UNVENTILATED SPILL. COVER WITH ABSORBENT. SCOOP INTO CONTAINERS. CLEANUP RESIDUE WITH 1,1,1-TRICHLOROETHANE.

Handling

Other Precautions: THIS PRODUCT CONTAINS A TOXIC CHEMICAL OR CHEMICALS SUBJECT TO THE REPORTING REQUIREMENTS OF SECTION 313 OF TITLE III OF THE SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT OF 1986 AND 40 CFR PART 372.

Exposure Controls

Respiratory Protection: WHEN APPLYING IN CONFINED AREAS OR IN OTHER CIRCUMSTANCES LIKELY TO PRODUCE AIRBORNE LEVELS OF SOLVENTS IN EXCESS OF PEL, USE AN ORGANIC VAPOR CARTRIDGE RESPIRATOR OR AIR-SUPPLIED RESPIRATOR.
Ventilation: GENERAL VENTILATION TO MAINTAIN VAPORS BELOW PEL.
Protective Gloves: SOLVENT RESISTANT GLOVES.
Eye Protection: SAFETY GLASSES.
Supplemental Safety and Health

Chemical Properties

HCC: F2
Vapor Density: 2.5 (MEK)
Spec Gravity: 1.4

Evaporation Rate & Reference: 3.79(METHYL ETHYL KETONE)
Solubility in Water: MODERATE.

Stability

Stability Indicator/Materials to Avoid: YES
STRONG OXIDIZING AGENTS.
Hazardous Decomposition Products: OXIDES OF CARBON, SO₂, TRACES OF H₂S.

Disposal

Waste Disposal Methods: EPA WASTE NOL D-001. DISPOSE OF SPILLAGE IN COMPLIANCE WITH FEDERAL AND STATE REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.