https://msdsreport.com/msds/BNRMR

# <u>PR-1435 PART B</u>

**MSDS Number** 

BNRMR

**National Stock Number** 

8030-00-105-0823

**Product Name** 

PR-1435 PART B

Manufacturer

COURTAULDS AEROSPACE INC

# **Product Identification**

Product ID:PR-1435 PART B MSDS Date:10/17/1988 FSC:8030 NIIN:00-105-0823 Kit Part:Y MSDS Number: BNRMR

## **Responsible Party**

COURTAULDS AEROSPACE INC

757 CALIFORNIA ST

GLENDALE , CA 91203

US

Emergency Phone: 818-549-7973

Info Phone: 818-549-7973

Preparer: JCS

Cage: 83574

# Contractor

PRC-DESOTO INTERNATIONAL, INC. A PPG INDUSTRIES COMPANY 1800 GLENDALE, CA 91209 US 818-240-2060 Cage: 83574 **Ingredients** 2-BUTANONE (METHYL ETHYL KETONE) CAS: 78-93-3 RTECS: EL6475000

Fraction By Weight: 10%

OSHA PEL200 PPM/300 STEL

ACGIH TLV: 200 PPM/300 STEL

EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

#### CAS: 9003-35-4

Fraction By Weight:

(MIXED) 145.15 G/L

RTECS: 9999999VO

#### Hazards

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Effects of Overexposure:EYES: IRRITATION. SKIN: LOCAL IRRITATION. MAY CAUSE ALLERGIC SKIN RASH IN SENSITIZED INDIVIDUALS. INHALTION: IRRITATION OF NOSE AND THROAT. PROLONGED EXPOSURE ABOVE TLV MAY CAUSE HEADACHE, DIZZINESS A ND UNCONCIOUSNESS. INGEST: MAY CAUSE NAUSEA, VOMITING AND LIVER AND KIDNEY DAMAGE.

•

#### **First Aid**

First Aid:EYES: FLUSH W/LUKE WARM WATER FOR 15 MINS. IF SYMPTOMS PERSIST, CONSULT A PHYSICIAN. SKIN: WASH WITH SOAP AND WATER. IF SYMPTOMS PERSIST, CONSULT A PHYSICIAN. INHAL: REMOVE TO FRESH AIR. IF SYMPTOMS A RE PRESENT, CONSULT A PHYSICIAN.

## **Fire Fighting**

Flash Point Method:SCC Flash Point:85.0F,29.4C Lower Limits:1.8 Upper Limits:10% (MEK) Extinguishing Media:CO2, DRY CHEMICAL, FOAM OR WATER SPRAY Fire Fighting Procedures:USE AIR-SUPPLIED RESPIRATOR. USE WATER TO COOL HEAT EXPOSED CONTAINERS. Unusual Fire/Explosion Hazard:HIGH TEMPERATURES MAY CAUSE PRESSURE BUILDUP IN CLOSED CONTAINERS.

## **Accidental Release**

Spill Release Procedures: REMOVE ALL IGNITION SOURCES. WEAR AIR-SUPPLIED RESPIRATOR FOR MAJOR UNVENTILATED SPILL. COVER WITH ABSORBANT. SCOOP INTO CONTAINERS. CLEAN RESIDUE WITH 1,1,1-TRICHLOROETHANE.

#### Handling

Other Precautions:THIS PRODUCT CONTAINS A TOXIC CHEMICAL OR CHEMICALS SUBJECT TO THE REPORTING REQUIREMENTS OF SECTION 313 OF TITLE III OF THE SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT OF 1986 AND 40 CFR PART 372.

#### **Exposure Controls**

Respiratory Protection:N/K PRODUCE AIRBORNE LEVELS OF SOLVENT IN EXCESS OF TLV, USE ORGANIC VAPOR CARTRIDGE RESPIRATOR OR AIR-SUPPLIED RESPIRATOR. Ventilation:GENERAL VENTILATION TO MAINTAIN VAPORS BELOW TLV. WHEN APPLYING IN CONFINED AREAS OR IN OTHER CIRCUMSTANCES LIKELY TO

Protective Gloves:SOLVENT-RESISTENT GLOVES Eye Protection:GOGGLES OR FULL FACE SHIELD. Supplemental Safety and Health

## **Chemical Properties**

HCC:F3 Vapor Density:2.5 (MEK) Spec Gravity:1.40 Evaporation Rate & Reference:3.8 (MEK) Solubility in Water:SLIGHT

#### Stability

Stability Indicator/Materials to Avoid:YES STRONG OXIDIZING AGENTS. Hazardous Decomposition Products:OXIDES OF CARBON, SO2, TRACES OF H2S.

#### Disposal



Waste Disposal Methods: EPA WASTE NO. D-001. DISPOSE OF SPILLAGE IN COMPLIANCE WITH FEDERAL AND STATE REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.