
1771, DEX-O-TEX TERRACOLOR BASECOAT COMP D

MSDS Number

BNSFH

National Stock Number

8040-00N031422

Product Name

1771, DEX-O-TEX TERRACOLOR BASECOAT COMP D

Manufacturer

CROSSFIELD PRODUCTS CORP

Product Identification

Product ID:1771, DEX-O-TEX TERRACOLOR BASECOAT COMP D

MSDS Date:11/04/1985

FSC:8040

NIIN:00N031422

MSDS Number: BNSFH

Responsible Party

CROSSFIELD PRODUCTS CORP

140 VALLEY ROAD

ROSELLE PARK , NJ 07204

US

Emergency Phone: 908-245-2800

Info Phone: 908-245-2800

Cage: 88167

Contractor

CROSSFIELD PRODUCTS CORP

ROSELLE PARK, NJ 07204-1402

US

908-245-2800

Cage: 88167

Ingredients

MODIFIED POLYAMINE; (MODIFIED POLYAMINE EPOXY HARDENER)

Hazards

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.

Routes of Entry: Inhalation:YES Skin:NO Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:ACUTE:MINOR BURNING TO EYE, NOSE, THROAT AND SKIN. CHRONIC:DEFATTING TO THE SKIN-DIZZINESS AND NAUSEA.

Explanation of Carcinogenicity:NOT RELEVANT

Effects of Overexposure:SEE HEALTH HAZARDS.

Medical Cond Aggravated by Exposure:NOT KNOWN

First Aid

First Aid:INHAL:MOVE SUBJECT TO FRESH AIR. EYE:FLUSH WITH WATER FOR AT LEAST 15 MINUTES, CALL PHYSICIAN. SKIN:WASH WITH SOAP AND WATER.

INGEST:DO NOT INDUCE VOMITING-CALL PHYSICIAN.

Fire Fighting

Flash Point Method:SCC

Flash Point:200F,93C
Extinguishing Media:CO2, DRY CHEMICAL
Fire Fighting Procedures:WEAR NIOSH/MSHA APPROVED SCBA AND FULL PROTECTIVE EQUIPMENT .
Unusual Fire/Explosion Hazard:CLOSED CONTAINERS MAY RUPTURE WHEN EXPOSED TO EXTREME HEAT.

Accidental Release

Spill Release Procedures:SPREAD ABSORBENT MATERIAL OVER SPILL AND PLACE IN CLOSED CONTAINER. REMOVE ALL SOURCES OF IGNITION.
Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

Handling

Handling and Storage Precautions:STORE IN COOL DRY AREA-PROTECTIVE GLOVES SHOULD BE WORN AS MATERIAL IS SLIGHTLY CORROSIVE.
Other Precautions:AVOID INHALATION OF HEATED VAPORS AND SPRAY MISTS.

Exposure Controls

Respiratory Protection:NIOSH/MSHA RESPIRATOR IF VENTILATION IS POOR.
Ventilation:GOOD VENTILATION. LOCAL EXHAUST, MECHANICAL (GENERAL).
Protective Gloves:IMPERVIOUS GLOVES .
Eye Protection:CHEMICAL WORKERS GOGGLES .
Other Protective Equipment:AS NEEDED TO PROTECT SKIN CONTACT.
Work Hygienic Practices:NONE SPECIFIED BY MANUFACTURER.
Supplemental Safety and Health
NONE SPECIFIED BY MANUFACTURER.

Chemical Properties

HCC:N1
Spec Gravity:1.01 (H2O=1)
Solubility in Water:NEGLIGIBLE
Appearance and Odor:PALE STRAW LIQUID-MODERATE AMINE ODOR.
Percent Volatiles by Volume:0%

Stability

Stability Indicator/Materials to Avoid:YES
AVOID STRONG OXIDIZING AGENTS. AVOID CONTACT WITH EPOXY RESINS IN UNCONTROLLED CONDITIONS.
Stability Condition to Avoid:TO AVOID HIGH TEMPERATURES
Hazardous Decomposition Products:NONE SPECIFIED BY MANUFACTURER.
Conditions to Avoid Polymerization:AVOID CONTACT WITH EPOXY RESINS UNTIL READY FOR APPLICATION.

Disposal

Waste Disposal Methods:DISPOSE OF IN SANITARY LANDFILL ACCORDING TO LOCAL, STATE, FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.