

## **LUBE-R-COAT**

### **MSDS Number**

BNXZJ

### **National Stock Number**

9150-00F024607

### **Product Name**

LUBE-R-COAT

### **Manufacturer**

RECTORSEAL CORP

### **Product Identification**

Product ID:LUBE-R-COAT

MSDS Date:03/19/1990

FSC:9150

NIIN:00F024607

MSDS Number: BNXZJ

### **Responsible Party**

RECTORSEAL CORPORATION

(2830 PRODUCE ROW)

HOUSTON , TX 77023-5822

US

Emergency Phone: (713) 928-6423

Info Phone: (713) 928-6423

Cage: 2P988

### **Contractor**

THE RECTORSEAL CORPORATION

HOUSTON, TX 77055

US

800-231-3345

Cage: 60150

### **Ingredients**

KEROSENE, KEROSINE

CAS: 8008-20-6

RTECS: OA5500000

SOLVENT REFINED HYDROTREATED HEAVY PARAFFINIC DISTILLATE,

CAS: 64742-54-7

RTECS: PY8035500

OSHA PEL5 MG/CUM (MIST)

ACGIH TLV: 5 MG/CUM

MINERAL OIL; PETROLATUM-LIQUID; WHITE MINERAL OIL, PARAFFIN

CAS: 8012-95-1

RTECS: PY8030000

OSHA PEL5 MG/CUM

ACGIH TLV: 5 MG/CUM

## Hazards

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:EYES: IRRITATION, BLURRED VISION.  
INHALATION: UPPER RESPIRATORY TRACT IRRITATION & NARCOSIS,  
DIZZINESS, NAUSEA, CNS SYMPTOMS. INGESTION: GASTRO-INTESTINAL  
IRRITATION, NAUSEA, VOMITING, DIARRHEA, ASPIRATION INTO LUNGS CAN  
CAUSE CHEMICAL PNEUMONITIS. SKIN: IRRITATION, DERMATITIS,  
DEFATTING, & ABSORPTION.  
Explanation of Carcinogenicity:NONE  
Effects of Overexposure:EYES: IRRITATION, BLURRED VISION. INHALATION:  
PERMANENT BRAIN/NERVOUS SYSTEM DAMAGE. INGESTION: GASTRO-INTESTINAL  
IRRITATION, NAUSEA, VOMITING, DIARRHEA, ASPIRATION INTO LUNGS CAN  
CAUSE CHEMICAL PNEUMONITIS. SKIN: IRRITATION, DERMATITIS,  
DEFATTING, & ABSORPTION.

## First Aid

First Aid:EYES: FLUSH W/PLENTY OF WATER FOR 15 MIN. INHALATION: REMOVE  
TO FRESH AIR; ADMINISTER OXYGEN OR ARTIFICIAL RESPIRATION IF  
NEEDED. INGESTION: GIVE PLENTY OF WATER. DON'T INDUCE VOMITING. IF  
UNCONSCIOUS DON'T GIVE ANYTHING BY MOUTH. SKIN: WASH W/SOAP &  
WATER. OBTAIN MEDICAL ATTENTION IN ALL CASES.

## Fire Fighting

Flash Point Method:TCC  
Flash Point:>100F  
Lower Limits:0.9%  
Upper Limits:7%  
Extinguishing Media:FOAM, DRY CHEMICAL, CO2 OR WATER FOG  
Fire Fighting Procedures:WEAR SELF-CONTAINED FULL FACE-PIECE BREATHING  
APPARATUS. DIKE FIRE CONTROL AREA AS RUN-OFF MAY CREATE  
ADDITIONAL-FIRE HAZARD/ENVIRONMENTAL CONTAMINATION.  
Unusual Fire/Explosion Hazard:VAPORS >AIR, TRAVEL ALONG GROUND OR TO  
LOW SPOTS TO IGNITION SOURCE & FLASHBACK. BURNING LIQUID MAY FLOAT  
ON WATER. HEAT MAY BUILD UP PRESSURE & RUPTURE DRUMS.

## Accidental Release

Spill Release Procedures:USE ABSORBENT TO PREVENT FOOTING HAZARD & TO  
CONTAIN. VENTILATE AREA. AVOID FLUSHING INTO SEWERS, DRAINS,  
WATERWAYS, & SOIL. WEAR PROTECTIVE CLOTHING & RESPIRATORY  
PROTECTION DURING CLEANUP.

## Handling

Handling and Storage Precautions:KEEP CONTAINER CLOSED & UPRIGHT WHEN  
NOT IN USE. DON'T STORE NEAR HEAT, SPARKS, OR OPEN FLAME.  
Other Precautions:AVOID CONTACT W/SKIN/CLOTHING. EMPTY CONTAINERS  
CONTAIN RESIDUE/VAPOR; TREAT AS IF FULL. DON'T REUSE EMPTY  
CONTAINERS. KEEP OUT OF REACH OF CHILDREN. INTENTIONAL MISUSE BY  
DELIBERATELY CONCENTRATING/INHALING CONTENTS MAY BE HARMFUL/FATAL.

## Exposure Controls

Respiratory Protection:USE NIOSH/MSHA APPROVED AIR PURIFYING OR  
SUPPLIED AIR RESPIRATORS IN CONFINED, POORLY VENTILATED AREA.  
Ventilation:LOCAL EXHAUST: ACCEPTABLE. MECHANICAL (GENERAL):  
PREFERABLE. USE NATURAL EXPLOSION-PROOF FORCED AIR VENTILATION.  
Protective Gloves:NON-PERMEABLE  
Eye Protection:GOGGLES  
Other Protective Equipment:COVERALLS RECOMMENDED  
Work Hygienic Practices:WASH THOROUGHLY BEFORE  
EATING/DRINKING/SMOKING/LEAVING WORK. LAUNDER CONTAMINATED CLOTHING  
BEFORE REUSE.  
Supplemental Safety and Health

---

## Chemical Properties

Boiling Pt:B.P. Text:320F

Vapor Pres:Vapor Density:4.7

Spec Gravity:Evaporation Rate & Reference:(ETHYL ACETATE = 1): Solubility in Water:INSOLUBLE

Appearance and Odor:AMBER LIQUID W/PETROLEUM ODOR.

## Stability

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING MATERIALS

Stability Condition to Avoid:HEAT, SPARKS, OPEN FLAMES & STRONG

OXIDIZING CONDITIONS.

Hazardous Decomposition Products:CO, CO2 & FRAGMENTED HYDROCARBONS

## Disposal

Waste Disposal Methods:RCRA CLASSIFIED HAZARDOUS WASTE. DISPOSE OF ABSORBED MATERIALS & LIQUID WASTES IN APPROVED, CONTROLLED INCINERATION FACILITY IN ACCORDANCE W/LOCAL, STATE & FEDERAL REGULATIONS. COMBUSTIBLE. NA1993.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.