

F-07P01, F-150 A-COMP 24272

MSDS Number

BPBCL

National Stock Number

8010-00N032532

Product Name

F-07P01, F-150 A-COMP 24272

Manufacturer

SEAGRAVE COATINGS CORP OF VA

Product Identification

Product ID:F-07P01, F-150 A-COMP 24272

MSDS Date:05/06/1988

FSC:8010

NIIN:00N032532

Kit Part:Y

MSDS Number: BPBCL

Responsible Party

SEAGRAVE COATINGS CORP OF VA

4030 SEAGUARD AVE

PORTSMOUTH , VA 23701

US

Emergency Phone: 404-589-4400;800-424-9300(CHEMTREC)

Info Phone: 804-488-4411

Cage: 60163

Contractor

SHERWIN-WILLIAMS, SEAGUARD

PORTSMOUTH, VA 23704

US

757-397-2223

Cage: 60163

Ingredients

4.4 @ 68F.

CAS: 71-36-3

RTECS: EO1400000

Fraction By Weight: 50%

OSHA PEL100 PPM

ACGIH TLV: S, C 50 PPM; 9293

EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

Hazards

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.

Routes of Entry: Inhalation:YES Skin:NO Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:MATERIAL ON REPEATED OR PROLONGED
CONTACT WITH SKIN CAN CAUSE IRRITATION, DERMATITIS, AND SEVERE

BURNS. EYES CAN BE IRRITATED AND SEVERELY DAMAGED BY SHORT CONTACT.
INHALED MIST CAN IRRITATE TISSUE OF ENTIRE RESPIRATORY TRACT.

Explanation of Carcinogenicity:NOT RELEVANT.

Effects of Overexposure:CONTACT MAY IRRITATE OR BURN SKIN AND EYES.

Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

First Aid

First Aid:SKIN: FLUSH CONT AREA THORO W/H2O; REMOVE CONTAM CLTHG, UNDER SAFETY SHOWER FOR GROSS CONTAM. GET MED HELP IF LRG SKIN AREA CONT/IF IRRIT PERSISTS. INGEST: GIVE DILUTED VINEGAR/CITRUS JUICE TO DRINK. GET MED HELP! DO NOT INDUCE VOMIT. FOLLOW W/MILK/OLIVE OIL/EGG WHITES AND H2O. INHAL: REMOVE FROM EXPOS. SUPPORT BRTHG (GIVE ARTF RESP/ O2) . EYES: FLUSH W/H2O FOR AT LEAST 15 MIN .

Fire Fighting

Flash Point Method:SCC

Flash Point:100F,38C

Lower Limits:1.4%

Extinguishing Media:EXTINGUISH FIRES WITH CO2, WATER (FOG), STEAM, FOAM, DRY CHEMICAL. COOL FIRE-EXPOSED METAL CONTAINERS WITH WATER SPRAY.

Fire Fighting Procedures:WEAR NIOSH/MSHA APPROVED SCBA AND FULL PROTECTIVE EQUIPMENT .

Unusual Fire/Explosion Hazard:WHEN MATL IS INVOLVED IN FIRE, TOXIC DEGRADATION PRODUCTS CAN BE PRODUCED, INCLUDING, CO2, CO, HCHO, AND SIO2.

Accidental Release

Spill Release Procedures:SWEEP UP OR SCOOP UP SOLID SPILLS FOR DISPOSAL OR RECOVERY, AVOIDING DUSTING CONDITIONS AND SKIN CONTACT. PICK UP LIQUID SPILLS WITH SAND OR ABSORBENT SOLID FOR LANDFILL DISPOSAL OR CONDUCT TO HOLDING FACILITY. FLUSH TRACES WITH WATER.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

Handling

Handling and Storage Precautions:STORE APPROVED LIQUID CONTAINERS IN WELL- VENTILATED, LOW FIRE-RISK AREA AWAY FROM COMBUSTIBLES AND CORROSIVE CHEMICALS.

Other Precautions:KEEP AWAY FROM SOURCES OF HEAT. PROTECT CONTAINERS AGAINST PHYSICAL DAMAGE. PROPERLY VENT LIQUID STORAGE.

Exposure Controls

Respiratory Protection:USE NIOSH/MSHA APPRVD CHEM CARTRIDGE RESP/AIR SUPPLIED/SELF-CONTAINED RESP FOR NONROUTINE/EMER EXPOS ABOVE TLV.A

NIOSH/ MSHA APPRVD FULL FACE MASK IS NEEDED TO PVNT EYE IRRIT FROM

VAPS.(UNDER EXCESSIV ELY DUST CNDTNS USE A NIOSH/MSHA (SUPDAT

Ventilation:PROVIDE ADEQUATE GENERAL AND LOCAL EXHAUST VENTILATION

(EXPLOSION-PROOF EQUIPMENT) TO KEEP WORKPLACE VAPORS AT MINIMUM.

Protective Gloves:RUBBER GLOVES.

Eye Protection:CHEM WORK GOG/FULL LGTH FACESHLD .

Other Protective Equipment:PROT CLTHG, LONG SLEEVE SHIRT W/BUTTONED COLLAR, APRON TO PVNT SKIN/EYE CONT W/MATL AS REQD FOR CONDITIONS UNDER (SUPDAT)

Work Hygienic Practices:PREVENT SKIN CONTACT WITH PAINT. PROVIDE FOR ADEQUATE EXHAUST VENTILATION OR APPROVED RESPIRATOR WHERE USED OR STORED.

Supplemental Safety and Health

KEY1;F4. OTHER PROT EQUIP: WHICH IT IS USED. USE OF PROTECTIVE CREAMS ON AREAS OF SKIN EXPOSED TO DUST HAS BEEN RECOMMENDED. USE

DUST-TIGHT CONVEYORS & HNDLG EQUIP. CONSIDER USE OF BARRIER CREAMS

FOR ADNL SKIN PROT. EMER EYE WASH & DELUGE SHOWER . RESP PROT:

APPRVD DUST RESP. NORMALLY, DUST CNDTNS SHOULD NOT BE P

Chemical Properties

HCC:F4

Boiling Pt:B.P. Text:244F,118C

Vapor Pres:SEE INGRED

Vapor Density:>1
Evaporation Rate & Reference:Solubility in Water:NONE
Appearance and Odor:GREEN LIQUID, ALCOHOL SOLVENT ODOR.
Percent Volatiles by Volume:48

Stability

Stability Indicator/Materials to Avoid:YES
STRONG OXIDIZING AGENTS.
Stability Condition to Avoid:EXCESSIVELY HIGH TEMPERATURES.
Hazardous Decomposition Products:CO, CO₂, HCHO, SiO₂.

Disposal

Waste Disposal Methods:FOLLOW FEDERAL, STATE, AND LOCAL ENVIRONMENTAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.