

INTERIOR WIPING STAIN (WALNUT)

MSDS Number

BPFCV

National Stock Number

8010-00-597-8225

Product Name

INTERIOR WIPING STAIN (WALNUT)

Manufacturer

FARWEST PAINT MFG CO

Product Identification

Product ID:INTERIOR WIPING STAIN (WALNUT)

MSDS Date:06/01/1992

FSC:8010

NIIN:00-597-8225

MSDS Number: BPFCV

Responsible Party

FARWEST PAINT MFG CO

4522 S 133 ST

TUKWILA , WA 98168-3251

US

Emergency Phone: 206-941-1619

Info Phone: 206-244-8844

Preparer: NORNA HABEEB

Cage: 6F266

Contractor

FARWEST PAINT MANUFACTURING CO

TUKWILA, WA 98168

US

206-244-8844

Cage: 6F266

Ingredients

VM&P NAPHTHA (LIGROINE)

CAS: 8032-32-4

RTECS: OI6180000

Fraction By Weight: >57%

OSHA PEL300 PPM/400 STEL

ACGIH TLV: 300 PPM; 9293

Hazards

Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:ACUTE: MAY CAUSE RESPIRATORY TRACT IRRITATION AND CENTRAL NERVOUS SYSTEM DEPRESSION IF VAPORS INHALED.

MAY CAUSE SKIN AND EYE IRRITATION ON CONTACT. MAY BE HARMFUL IF SWALLOWED. CHRONIC: PROLONGED INH ALATION OF VAPORS MAY CAUSE NERVOUS SYTEM DAMAGE OR BRAIN DAMAGE. MAY CAUSE SKIN SENSITIZATION.

Explanation of Carcinogenicity:NO INGREDIENT OF A CONCENTRATION OF 0.1%

OR GREATER IS LISTED AS A CARCINOGEN OR SUSPECTED CARCINOGEN.
Effects of Overexposure:INHALED: COUGHING, WHEEZING, SHORTNESS OF BREATH, NAUSEA, DIZZINESS, DROWSINESS, HEADACHE. EYES: REDNESS, TEARING, DISCOMFORT. SKIN: DRYING, RESNESS OR RASH, ITCHING OR DISCOMFORT. INGESTED: NAUSEA, V OMITING, VOMIT MAY BE ASPIRATED CAUSINGCHEMICAL PNEUMONIA.
Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

First Aid

First Aid:SKIN: PROMPTLY WASH WITH SOAP AND WATER. REMOVE CONTAMINATED CLOTHES. EYES: FLUSH WITH LOTS OF WATER FOR 15 MINUTES WHILE HOLDING EYELIDS OPEN. SEE DOCTOR. INHALED: REMOVE PERSON TO FRESH AIR. IF RESP IRATORY SYMPTOMS DEVELOP, GET IMMEDIATEMEDICAL HELP. INGESTED: DO NOT INDUCE VOMITING! GET IMMEDIATE MEDICAL ATTENTION.

Fire Fighting

Flash Point Method:TCC
Flash Point:104F,40C
Lower Limits:0.7%
Upper Limits:6.0%
Extinguishing Media:FOAM, DRY CHEMICAL, WATER FOG, CARBON DIOXIDE OR ANY CLASS "B" EXTINGUISHING AGENT.
Fire Fighting Procedures:WEAR SELF-CONTAINED BREATHING APPARATUS AND PROTECTIVE CLOTHING. EVACUATE AREA OF NON-ESSENTIAL PEOPLE.
Unusual Fire/Explosion Hazard:VAPORS MAY FORM AN EXPLOSIVE MIXTURE IN AIR AND MAY BE IGNITED BY SPARKS OR OTHER IGNITION SOURCES. CLOSED CONTAINERS MAY RUPTURE IN EXTREME HEAT.

Accidental Release

Spill Release Procedures:ELIMINATE ALL SOURCES OF IGNITION. VENTILATE AREA. ABSORB SPILL WITH INERT MATERIAL AND PLACE IN A CONTAINER FOR LATER DISPOSAL. WEAR PROPER PROTECTIVE CLOTHING AND EQUIPMENT.
Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

Handling

Handling and Storage Precautions:KEEP AWAY FROM HEAT OR OPEN FLAME. KEEP CONTAINERS CLOSED.
Other Precautions:DO NOT WELD, HEAT, BRAZE OR CUT CONTAINERS; EMPTY OR FULL.

Exposure Controls

Respiratory Protection:IF TLV EXCEEDED; USE NIOSH/MSHA APPROVED RESPIRATOR. IF RESPIRATOR IS USED; A PROGRAM IN ACCORDANCE WITH 29 CFR 1910.134 MUST BE IN PLACE.
Ventilation:USE ADEQUATE MECHANICAL VENTILATION. LOCAL EXHAUST MAY BE NEEDED ON OCCASSION TO MAINTAIN REGULATORY EXPOSURE LIMITS.
Protective Gloves:NITRILE, NEOPRENE, OR RUBBER
Eye Protection:SAFETY GLASSES/CHEMICAL SPLASH GOGGLES
Other Protective Equipment:EYE WASH STATION & SAFETY SHOWER; PROTECTIVE CLOTHING TO PREVENT PROLONGED OR REPEATED CONTACT.
Work Hygienic Practices:WASH HANDS AFTER USE AND BEFORE EATING, DRINKING, OR SMOKING. LAUNDER CONTAMINATED CLOTHES BEFORE REUSE.
Supplemental Safety and Health

Chemical Properties

HCC:F4
Boiling Pt:B.P. Text:>307F,>153C
Vapor Pres:2.6 MM HG
Vapor Density:>1 (AIR=1)
Spec Gravity:0.9
Viscosity:>10
Evaporation Rate & Reference:Solubility in Water:NIL
Appearance and Odor:BROWN LIQUID; MILD ODOR.
Percent Volatiles by Volume:>65

Stability

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS, STRONG MINERAL ACIDS, STRONG ALKALIS, AND EPOXY HARDENERS.

Stability Condition to Avoid:HEAT, SPARKS, AND OPEN FLAMES.

Hazardous Decomposition Products:INCOMPLETE COMBUSTION CAN YIELD CARBON MONOXIDE AND TOXIC VAPORS.

Disposal

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS. MATERIAL IS A RCRA IGNITABLE WASTE (40 CFR 261).

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.