

955 SEMI GLOSS,EGGSHELL,GLOSS LATEX ENAMEL

MSDS Number

BPSYK

National Stock Number

8010-00F025867

Product Name

955 SEMI GLOSS,EGGSHELL,GLOSS LATEX ENAMEL

Manufacturer

FARWEST PAINT MFG CO

Product Identification

Product ID:955 SEMI GLOSS,EGGSHELL,GLOSS LATEX ENAMEL

MSDS Date:10/04/1991

FSC:8010

NIIN:00F025867

MSDS Number: BPSYK

Responsible Party

FARWEST PAINT MFG CO

4522 S 133 ST

TUKWILA , WA 98168-3251

US

Emergency Phone: 206-941-1619

Info Phone: 206-244-8844

Cage: 6F266

Contractor

FARWEST PAINT MANUFACTURING CO

TUKWILA, WA 98168

US

206-244-8844

Cage: 6F266

Ingredients

9-11 LBS

RTECS: 9999999WG

ETHYLENE GLYCOL, GLYCOL

CAS: 107-21-1

RTECS: KW2975000

Fraction By Weight: 4.0%

OSHA PEL50PPM

ACGIH TLV: C 127 MG/CUM

EPA Report Quantity: 1 LB

DOT Report Quantity: 1 LB

PROPANOIC ACID, 2-METHYL, MONOESTER

CAS: 25265-77-4
RTECS: UF6000000
Fraction By Weight: 2.0%
OSHA PEL100PPM
ACGIH TLV: 100PPM

62 GM/L
RTECS: 9999999VO

Hazards

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:SKIN/EYES: IRRITATION. INGESTION:
INJURY.
Explanation of Carcinogenicity:NONE
Effects of Overexposure:INHALATION: MUCOUS MEMBRANE IRRITATION,
DIZZINESS & HEADACHE. INGESTION: LARGE AMOUNTS SEVERE INJURY.

First Aid

First Aid:INHALATION: REMOVE TO FRESH AIR. SKIN: WASH W/PLENTY OF SOAP
& WATER. EYE: FLUSH IMMEDIATELY W/LARGE AMOUNTS OF WATER FOR AT
LEAST 15 MINS. INGESTION: OBTAIN MEDICAL ATTENTION IN ALL CASES.

Fire Fighting

Extinguishing Media:FOAM, DRY CHEMICAL, CO2 OR WATER FOG.
Fire Fighting Procedures:WATER MAY BE USED TO COOL & PROTECT EXPOSED
CONTAINERS.
Unusual Fire/Explosion Hazard:WILL NOT BURN, CLOSED CONTAINERS MAY
BURST IF EXPOSED TO EXTREME HEAT OR FIRE.

Accidental Release

Spill Release Procedures:VENTILATE AREA. COLLECT W/ABSORBENT MATERIAL.

Handling

Handling and Storage Precautions:AVOID TEMPS STORE CONTAINERS W/LIDS TIGHTLY CLOSED & APPROPRIATELY LABELED.
Other Precautions:AVOID DISCHARGE TO NATURAL WATERS. AVOID BREATHING
VAPOR & SPRAY MIST. AVOID CONTACT W/SKIN & EYES.

Exposure Controls

Respiratory Protection:WEAR A PROPERLY FITTED ORGANIC VAPOR/PARTICULATE
RESPIRATOR APPROVED BY NIOSH/OSHA.
Ventilation:LOCAL EXHAUST: PREFERABLE. GENERAL: ACCEPTABLE
Protective Gloves:IMPERVIOUS
Eye Protection:GOGGLES
Other Protective Equipment:EYE WASH & SAFETY SHOWER.
Work Hygienic Practices:KEEP WORK AREA CLEAN. WASH HANDS THOROUGHLY
BEFORE HANDLING, FOOD DRINK OR SMOKING. REMOVE & WASH CONTAMINATED
CLOTHES.
Supplemental Safety and Health

Chemical Properties

Boiling Pt:B.P. Text:212F
Vapor Pres:23.8
Vapor Density:>1
pH:7-8
Evaporation Rate & Reference:SLOWER THAN ETHER
Solubility in Water:COMPLETE
Appearance and Odor:THIXOTROPIC LIQUID W/SLIGHT ODOR; COLOR OF TINT.
Percent Volatiles by Volume:7.5%

Stability

Stability Indicator/Materials to Avoid: YES
OXIDIZERS OR HYDROFLUORIC ACID.
Stability Condition to Avoid: ELEVATED TEMPERATURES & OXIDIZING AGENTS.
Hazardous Decomposition Products: CO & CO₂

Disposal

Waste Disposal Methods: DISPOSE OF IN ACCORDANCE W/ FEDERAL, STATE & LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.