

93215, ALL PURPOSE ETP CUTTING FLUID

MSDS Number

BPTBL

National Stock Number

9150-00N032548

Product Name

93215, ALL PURPOSE ETP CUTTING FLUID

Manufacturer

PREMIER INDUSTRIAL CORP

Product Identification

Product ID:93215, ALL PURPOSE ETP CUTTING FLUID MSDS Date: 08/28/1989 FSC:9150 NIIN:00N032548 MSDS Number: BPTBL

Responsible Party

PREMIER INDUSTRIAL CORP

4500 EUCLID AVE

CLEVELAND, OH 44103

US

Emergency Phone: 216-391-8300

Info Phone: 216-391-8300

Preparer: G.F.S Cage: 18399 **Contractor**

PREMIER FARNELL CORPORATION

CLEVELAND, OH 44103-3736

US

216-391-8300 Cage: 18399

Ingredients

HYDROTREATMENT); (PETROLEUM OIL).

RTECS: 9999999ZZ

MINERAL OIL, PETROLEUM DISTILLATES, SOLVENT-DEWAXED HEAVY

CAS: 64742-63-8 RTECS: PY8038000

Fraction By Weight: 65% OSHA PEL5 MG/M3 (OIL MIST)

ACGIH TLV: 5MG/M3;10 STEL(MIST)

Hazards

LD50 LC50 Mixture: SEE INGREDIENT 1

Routes of Entry: Inhalation:YES Skin:NO Ingestion:YES



Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:PRODUCT IS NOT A PRIMARY SKIN OR EYE IRRITANT. CHRONIC IRRITATION MAY OCCUR AFTER PROLONGED AND REPEATED

CONTACT WITH SKIN.

Explanation of Carcinogenicity: NOT RELEVANT

Effects of Overexposure: SEE HEALTH HAZARDS.

Medical Cond Aggravated by Exposure: NONE SPECIFIED BY MANUFACTURER.

First Aid

First Aid:EYE: IMMED FLUSH WITH PLENTY OF WATER FOR AT LEAST 15 MINUTES & CALL PHYSICIAN. SKIN: WASH THOROUGHLY WITH PLENTY OF SOAP AND WATER. INHAL: REMOVE TO FRESH AIR. INGEST: SEEK PHYS IMMED. SHOW MSDS OR L ABEL, DO NOT INDUCE VOMITING.

Fire Fighting

Flash Point: 450F, 232C

Extinguishing Media: CO2, DRY CHEMICAL, FOAM.

Fire Fighting Procedures: WEAR NIOSH/MSHA APPROVED SCBA AND FULL

PROTECTIVE EQUIPMENT.

Unusual Fire/Explosion Hazard: NONE.

Accidental Release

Spill Release Procedures: CLEAN UP WITH ABSORBENT MATERIAL. DISPOSE OF AS A NON-HAZARDOUS WASTE. CONTAIN AND PICK-UP WASTE MATERIALS. Neutralizing Agent: NONE SPECIFIED BY MANUFACTURER.

Handling

Handling and Storage Precautions: AVOID PRLNG/RPTD CONT W/SKIN. ALWAYS READ & FOLLOW DIRECTONS ON PRODUCT LABEL.

Other Precautions:IN CASE OF ACCIDENT/ILLNESS, SEEK PHYS IMMED, SHOW LBL/ MSDS. KEEP OUT OF REACH OF CHILDREN. ADDNL TECH DATA SHEETS &/OR MATL SFTY DATA SHEETS ARE AVAIL UPON REQUEST. FOR PROFESSIONAL & INDUSTRIAL USE ONLY.

Exposure Controls

Respiratory Protection: USE ONLY WITH ADEQUATE VENTILATION. USE NIOSH/MSHA APPROVED RESPIRATOR APPROPRIATE FOR EXPOSURE OF CONCERN

Ventilation:LOCAL: RECOMMENDED. MECH:REQUIRED.

Protective Gloves: SOLVENT RESISTALT GLOVES.

Eye Protection: CHEMICAL WORKERS GOGGLES .

Other Protective Equipment: AVOID PROLONGED OR REPEATED CONTACT WITH

SKIN.

Work Hygienic Practices: NONE SPECIFIED BY MANUFACTURER.

Supplemental Safety and Health

NONE SPECIFIED BY MANUFACTURER.

Chemical Properties

HCC:V6

Boiling Pt:B.P. Text:680F,360C

Vapor Pres:NIL

Spec Gravity: 0.99

Evaporation Rate & Reference: Solubility in Water: NIL

Appearance and Odor: TAN OPAQUE FLUID, W/PETROLEUM ODOR.

Percent Volatiles by Volume: NIL

Stability

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZERS.

Stability Condition to Avoid: KEEP AWAY FROM HEAT AND FLAME.

Hazardous Decomposition Products: PYROLYSIS PRODUCTS. CO, CO2.

Disposal

Waste Disposal Methods: DISPOSE OF WASTES IN ACCORDANCE WITH FEDERAL, STATE AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):



This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.