

EXT. ACRYLIC LATEX FOR WOOD & MASONRY, WHIT

MSDS Number

BPVDB

National Stock Number

8010-00-823-7962

Product Name

EXT. ACRYLIC LATEX FOR WOOD & MASONRY, WHIT

Manufacturer

FARWEST PAINT MFG CO

Product Identification

Product ID:EXT. ACRYLIC LATEX FOR WOOD & MASONRY, WHIT

MSDS Date:10/01/1992

FSC:8010

NIIN:00-823-7962

MSDS Number: BPVDB

Responsible Party

FARWEST PAINT MFG CO

4522 S 133 ST

TUKWILA , WA 98168-3251

US

Emergency Phone: 206-941-1619

Info Phone: 206-244-8844

Preparer: NORMA HABEEB

Cage: 6F266

Contractor

FARWEST PAINT MANUFACTURING CO

TUKWILA, WA 98168

US

206-244-8844

Cage: 6F266

Ingredients

ETHYLENE GLYCOL (SARA 313)

CAS: 107-21-1

RTECS: KW2975000

Fraction By Weight: 1.59%

OSHA PEL100 PPM

ACGIH TLV: 50 PPM

EPA Report Quantity: 1 LB

DOT Report Quantity: 1 LB

GLYCOL ETHER (SARA 313)

CAS: 25265-77-4

RTECS: UF6000000

Fraction By Weight: 1.04%

OSHA PEL100 PPM

ACGIH TLV: 100 PPM

94 GRAMS/LITER (LESS WATER)

RTECS: 9999999VO

Hazards

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:INHALATION: PROLONGED INHALATION IN
CONFINED AREAS, MAY LEAD TO MEMBRANE IRRITATION/DIZZINESS/HEADACHE.
SKIN: IRRITATION. EYE: IRRITATION. INGEST: AMOUNTS INGESTED
INCIDENTAL TO CONSUMER/INDUSTRIAL HA NDLING ARE NOT LIKELY TO CAUSE
INJURY, HOWEVER, INGESTION OF LARGER AMOUNTS COULD CAUSE SERIOUS
INJURY.

Effects of Overexposure:NONE

Medical Cond Aggravated by Exposure:NONE

First Aid

First Aid:INHALE: MOVE TO FRESH AIR. IF RESPIRATORY SYMPTOMS DEVELOP,
SEEK MEDICAL ATTENTION AT ONCE. SKIN: WASH OFF QUICKLY W/PLENTY
WATER/SOAP/WATER. REMOVE/WASH CONTAMINATED CLOTHING BEFORE REUSE.
EYE: FLUSH IMMEDIATELY W/LARGE AMOUNTS OF WATER, ESPECIALLY UNDER
LIDS, FOR 15 MINUTES. OBTAIN EMERGENCY MEDICAL TREATMENT.
INGESTION: IF SWALLOWED, OBTAIN MEDICAL TREATMENT IMMEDIATELY.

Fire Fighting

Flash Point Method:TCC

Extinguishing Media:FOAM, DRY CHEMICAL, WATER, WATER FOG

Fire Fighting Procedures:WATER MAY BE USED TO COOL AND PROTECT ADJACENT
CONTAINERS.

Unusual Fire/Explosion Hazard:WILL NOT BURN. CLOSED CONTAINERS MAY
RUPTURE WHEN EXPOSED TO EXTREME HEAT OR FIRE.

Accidental Release

Spill Release Procedures:COMPLY WITH ALL APPLICABLE
HEALTH/ENVIRONMENTAL REGULATIONS. VENTILATE AREA. SPILLS MAY BE
COLLECTED W/ABSORBENT MATERIALS.

Handling

Handling and Storage Precautions:AVOID TEMPERATURES BELOW 40F. KEEP
FROM FREEZING. STORE CONTAINERS WITH LIDS TIGHTLY CLOSED AND
APPROPRIATELY LABELED.

Exposure Controls

Respiratory Protection:IF EXPOSURE NOT CONTROLLED BELOW APPLICABLE
LIMITS BY VENTILATION. WEAR PROPERLY FITTED ORGANIC
VAPOR/PARTICULATE RESPIRATOR APPROVED BY NIOSH/OSHA.
Ventilation:LOCAL EXHAUST PREFERABLE. GENERAL EXHAUST ACCEPTABLE IF THE
EXPOSURE TO MATERIALS IS MAINTAINED BELOW APPLICABLE LIMITS.

Protective Gloves:PROTECTIVE GLOVES

Eye Protection:SAFETY GOGGLES W/UNPERFORATED SIDESHIELD

Other Protective Equipment:EYE WASH/SAFETY SHOWERS/GOGGLES/SAFETY
GLASSES/IMPERVIOUS GLOVES

Work Hygienic Practices:KEEP WORK AREA CLEAN/FREE FROM SPILLS/LEAKS.
ALWAYS WASH HANDS W/SOAP/WATER BEFORE HANDLING FOOD/DRINK/SMOKING.
Supplemental Safety and Health

Chemical Properties

Boiling Pt:B.P. Text:212F,100C

Melt/Freeze Pt:M.P/F.P Text:32.0F,0.0C

Vapor Pres:23.8 @ 20C

Vapor Density: >AIR
Spec Gravity: 1.3896
pH: 7.0
Viscosity: 75-85 KU
Evaporation Rate & Reference: SLOWER THAN ETHER
Solubility in Water: INFINITE
Appearance and Odor: THIXOTROPIC LIQUID WITH SLIGHT ODOR, COLOR OF TINT.
Percent Volatiles by Volume: 3.5

Stability

Stability Indicator/Materials to Avoid: YES
OXIDIZERS AND/OR HYDROFLUORIC ACID.
Stability Condition to Avoid: ELEVATED TEMPERATURES, CONTACT WITH
OXIDIZING AGENTS.
Hazardous Decomposition Products: CARBON MONOXIDE AND CARBON DIOXIDE

Disposal

Waste Disposal Methods: DISPOSE OF ACCORDING TO LOCAL, STATE AND FEDERAL
REGULATIONS. AVOID DISCHARGE TO NATURAL WATERS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.