

## **TT-P-25E,PRIMER,COATING,EXTERIOR,TINT**

### **MSDS Number**

BQHFB

### **National Stock Number**

8010-00F025983

### **Product Name**

TT-P-25E,PRIMER,COATING,EXTERIOR,TINT

### **Manufacturer**

S L GILLMAN PAINT CO

### **Product Identification**

Product ID:TT-P-25E,PRIMER,COATING,EXTERIOR,TINT

MSDS Date:10/01/1985

FSC:8010

NIIN:00F025983

MSDS Number: BQHFB

### **Responsible Party**

S.L. GILLMAN PAINT CO.

2250 MORELAND AVENUE, S.E.

ATLANTA , GA 30315

US

Emergency Phone: 404-589-4400 OR 404-622-1326

Cage: 00269

### **Contractor**

S.L. GILLMAN PAINT COMPANY

ATLANTA

404 622 1326

Cage: 00269

### **Ingredients**

PETROLEUM HYDROCARBONS

MINERAL SPIRITS

TALC (POWDER), (ASBESTOS FREE), TALCUM; HYDROUS MAGNESIUM

CAS: 14807-96-6

RTECS: WW2710000

OSHA PEL20 MPPCF

ACGIH TLV: 2 MG/CUM (RESP DUST)

### **Hazards**

Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:INHALATION: DIZZINESS,  
LIGHT-HEADEDNESS, HEADACHE.

Explanation of Carcinogenicity:NONE

Medical Cond Aggravated by Exposure:ASTHMA

## First Aid

First Aid:INHALATION: REMOVE TO FRESH AIR. ADMINISTER OXYGEN. EYES: IRRIGATE THOROUGHLY W/WATER FOR 15 MINS. SKIN: FLUSH THOROUGHLY W/WATER. INGESTION: DON'T INDUCE VOMITING. OBTAIN MEDICAL ATTENTION IN ALL CAS ES.

## Fire Fighting

Flash Point Method:TCC  
Flash Point:105F/40.6C  
Lower Limits:1%  
Upper Limits:6%  
Extinguishing Media:FOAM, CO2, DRY CHEMICAL  
Fire Fighting Procedures:WEAR SCBA. WATER MAY BE UNSUITABLE AS EXTINGUISHING MEDIA, BUT HELPFUL TO KEEP ADJACENT CONTAINERS COOL. AVOID SPREADING BURNING LIQUID W/WATER.  
Unusual Fire/Explosion Hazard:OXIDIZING AGENTS MAY CAUSE VIGOROUS REACTION. FLAMMABLE LIQUID.

## Accidental Release

Spill Release Procedures:ELIMINATE ALL IGNITION SOURCES. FLUSH SPILLS AWAY W/WATER. SMALL SPILLS MAY BE COLLECTED W/ABSORBENT MATERIAL.

## Handling

Handling and Storage Precautions:AVOID CONTACT W/SKIN & EYES. AVOID INHALATION OF VAPORS. KEEP CONTAINERS TIGHTLY CLOSED, COOL, & AWAY FROM OPEN FLAMES & SPARKS.  
Other Precautions:HAZARDOUS RESIDUE MAY REMAIN IN EMPTY CONTAINERS. DON'T REUSE.

## Exposure Controls

Respiratory Protection:NIOSH APPROVED RESPIRATOR FOR ORGANIC VAPOR.  
Ventilation:LOCAL EXHAUST: RECOMMENDED. MECHANICAL (GENERAL): CLASS D EXPLOSION PROOF.  
Protective Gloves:IMPERVIOUS RUBBER  
Eye Protection:SAFETY GLASSES OR GOGGLES  
Other Protective Equipment:IMPERVIOUS APRON  
Supplemental Safety and Health

## Chemical Properties

Boiling Pt:B.P. Text:313-388F  
Vapor Pres:2  
Vapor Density:4.9  
Spec Gravity:0.781  
Solubility in Water:NEGLIGIBLE  
Appearance and Odor:COLOR AS INDICATED ON LABEL, CHARACTERISTIC ODOR.

## Stability

Stability Indicator/Materials to Avoid:YES  
STRONG OXIDIZING AGENTS  
Stability Condition to Avoid:OPEN FLAMES, SPARKS, EXCESSIVE HEAT, OR OTHER SOURCES OF IGNITION  
Hazardous Decomposition Products:CO, CO2

## Disposal

Waste Disposal Methods:OBSERVE ALL FEDERAL, STATE & LOCAL LAWS IN DISPOSING OF WASTE. DON'T REUSE EMPTY CONTAINERS. FLAMMABLE LIQUID.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.