

ZINC OXIDE GRADE TR-4

MSDS Number

BQHPN

National Stock Number

6810-00F026159

Product Name

ZINC OXIDE GRADE TR-4

Manufacturer

G H CHEMICALS LTD

Product Identification

Product ID:ZINC OXIDE GRADE TR-4

MSDS Date:05/29/1989

FSC:6810

NIIN:00F026159

MSDS Number: BQHPN

Responsible Party

G H CHEMICALS LTD

1550 BROUILLETTE ST

ST HYACINTHE

CN

Emergency Phone: 514-774-9151

Info Phone: 514-774-9151

Cage: GHCHM

Contractor

G H CHEMICALS LTD

456

ST HYACINTHE

CA

514-774-9151

Cage: GHCHM

Ingredients

ZINC OXIDE

CAS: 1314-13-2

RTECS: ZH4810000

Fraction By Weight: >99.8%

OSHA PEL15MG/M3 TDUST/5 FUME

ACGIH TLV: 10MG/M3 TDUST; 9293

Hazards

Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:EYE: IRRITATION. INHALATION: METAL

FUME FEVER. SYMPTOMS OCCUR 4 TO 12 HOURS AFTER EXPOSURE/LAST UP TO

24 HOURS. SKIN: OCCUPATIONAL DERMATITIS (OXIDE POX) OCCURS WHEN

ZINC OXIDE DUST COMBINES W/DEBRIS/ BACTERIA TO BLOCK SWEAT GLANDS

AS A RESULT OF POOR PERSONAL HYGIENE.

Explanation of Carcinogenicity:NONE

Effects of Overexposure:THERE ARE NO CUMULATIVE EFFECTS AS A RESULT OF LONG TERM EXPOSURE TO ZINC OXIDE DUST OR FUMES.

First Aid

First Aid:INHALATION: REMOVE TO FRESH AIR. TREAT ACCORDING TO THE SYMPTOMS. SKIN: WASH THOROUGHLY W/NON-ABRASIVE SOAP & WATER. EYES: FLUSH W/LUKEWARM GENTLY FLOWING WATER FOR 20 MINS. OBTAIN MEDICAL ATTENTION I N ALL CASES.

Fire Fighting

Unusual Fire/Explosion Hazard:REACTS VIOLENTLY W/CHLORINATED RUBBER; EXPLOSIVELY W/MAGNESIUM; VIGOROUSLY W/STRONG ACIDS; FORMS WATER SOLUBLE ZINCATES W/STRONG BASES.

Accidental Release

Spill Release Procedures:SHOVEL SPILLED PRODUCT INTO CLEAN, DRY LABELLED CONTAINERS & COVER. SWEEP &/OR FLUSH AREA CLEAN W/WATER. PROVIDE ADEQUATE VENTILATION TO PREVENT DUST ACCUMULATION DURING CLEANUP.

Handling

Handling and Storage Precautions:STORE ZINC OXIDE AWAY FROM ITS INCOMPATIBLE MATERIALS. STORE IN SUITABLE, LABELLED CONTAINERS IN DRY PLACE.

Other Precautions:KEEP CONTAINERS TIGHTLY CLOSED WHEN NOT IN USE & WHEN EMPTY. AVOID GENERATING DUST. ZINC OXIDE FUMES OCCUR ONLY DURING THE FORMATION OF ZINC OXIDE FROM ZINC METAL.

Exposure Controls

Respiratory Protection:DUST MASK OR MECHANICAL FILTER RESPIRATOR.

Ventilation:LOCAL EXHAUST/GENERAL MECHANICAL: TO PREVENT BUILDUP OF DUST OR FUMES ABOVE APPROVED LIMITS.

Protective Gloves:REQUIRED

Eye Protection:SAFETY GOGGLES

Work Hygienic Practices:PRACTICE GOOD PERSONAL HYGIENE.

Supplemental Safety and Health

THIS PRODUCT CAN BE USED AS A PIGMENT IN PAINT/INK/PLASTICS/ENAMEL, ACTIVATOR IN RUBBER, PHARMACEUTICAL IN ANTISEPTIC/ASTRINGENT/TOPICAL PROTECTANT, OR IN COSMETICS, CERAMICS, GLASS ADHESIVES, & ELECT RONICS.

Chemical Properties

Melt/Freeze Pt:M.P/F.P Text:1975C

Spec Gravity:5.65

pH:7.4

Solubility in Water:INSOLUBLE

Appearance and Odor:FINE, WHITE POWDER, ODORLESS.

Stability

Stability Indicator/Materials to Avoid:YES

CHLORINATED RUBBER/MAGNESIUM/STRONG ACIDS & BASES

Stability Condition to Avoid:REACTS VIOLENTLY W/CHLORINATED RUBBER AT 215C.

Hazardous Decomposition Products:WATER SOLUBLE ZINCATES

Disposal

Waste Disposal Methods:RECYCLE USED SPILLED PRODUCT IF IN ACCEPTABLE CONDITION. OTHERWISE, DISPOSE ACCORDING TO APPLICABLE FEDERAL, STATE, & LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their

particular situation.