

Q.D. ENAMEL SUPER WHITE, 290100

MSDS Number

BQLJK

National Stock Number

8010-00N035794

Product Name

Q.D. ENAMEL SUPER WHITE, 290100

Manufacturer

BENNETTE PAINT MANUFACTURING CO INC

Product Identification

Product ID:Q.D. ENAMEL SUPER WHITE, 290100

MSDS Date:12/13/1988

FSC:8010

NIIN:00N035794

MSDS Number: BQLJK

Responsible Party

BENNETTE PAINT MANUFACTURING CO INC

401 INDUSTRY DR

HAMPTON , VA 23661

US

Emergency Phone: 804-838-7777

Info Phone: 804-838-7777

Cage: 3Y107

Contractor

BENNETTE PAINT MANUFACTURING CO INC

HAMPTON, VA 23661

US

804-838-7777

Cage: 3Y107

Ingredients

10 @ 77F

CAS: 8052-41-3

RTECS: WJ8925000

Fraction By Weight: 39.32%

OSHA PEL500 PPM

ACGIH TLV: 100 PPM; 9293

1.35 LB/GL (161 GR/LT).

RTECS: 9999999VO

Fraction By Weight: SEE ING

Hazards

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:INHAL:TEMPORARY DIZZINESS, HEADACHE,
POSSIBLE NAUSEA; SYMPTOMS DISAPPEAR WHEN EXPOSURE CEASES. EYE/SKIN:
EYE OR SKIN CONTACT MAY CAUSE DISCOMFORT BY DEFATTING ACTION OF
SOLVENT. REPEATED CONTACT TO SK IN MAY CAUSE DERMATITIS. INGEST:DO
NOT INGEST. (ACUTE & CHRONIC): INHAL:TEMPORARY DIZZINESS,
HEADACHE,(EFTS OF OVEREXP)
Explanation of Carcinogenicity:NOT RELEVANT
Effects of Overexposure:HLTH HAZ: POSSIBLE NAUSEA; SYMPTOMS DISAPPEAR
WHEN EXPOSURE CEASES. EYE/SKIN CONTACT MAY CAUSE DISCOMFORT BY
DEFATTING ACTION OF SOLVENT. REPEATED CONTACT TO SKIN MAY CAUSE
DERMATITIS.
Medical Cond Aggravated by Exposure:ANY EXISTING
CARDIOVASCULAR/RESPIRATORY AILMENT.

First Aid

First Aid:INHAL: REMOVE FROM EXPOS IMMED; CALL A PHYSICIAN. IF BRTHG IS
IRREGULAR OR STOPPED, START RESUSCITATION, ADMINISTER OXYGEN.
INGEST: DO NOT INDUCE VOMITING; CALL A PHYSICIAN. SKIN: REMOVE
CONTAMINATED CLOTHING, AND WASH SKIN THOROUGHLY. EYE: FLUSH EYES
WITH CLEAN WATER FOR AT LEAST 15 MIN OR UNTIL IRRITATION SUBSIDES.
IF IRRITATION PERSISTS, SEEK MEDICAL ATTENTION.

Fire Fighting

Flash Point Method:TCC
Flash Point:105F,41C
Lower Limits:0.9%
Upper Limits:7%
Extinguishing Media:FOAM, CO*2, DRY CHEMICAL, WATER FOG.
Fire Fighting Procedures:WEAR NIOSH/MSHA APPROVED SCBA AND FULL
PROTECTIVE EQUIPMENT .
Unusual Fire/Explosion Hazard:KEEP AWAY FROM HEAT, SPARKS, AND OPEN
FLAMES. FIGHT AS VOLATILE LIQUID FIRE. USE WATER TO KEEP
FIRE-EXPOSED CONTAINERS COOL TO REDUCE PRESSURE.

Accidental Release

Spill Release Procedures:REMOVE SOURCES OF IGNITION & PROVIDE
VENTILATION. LARGE SPILLS MAY BE SCOOPED UP WITH NON-SPARKING
TOOLS. PROVIDE RESPIRATORY PROTECTION IF REQUIRED. SMALL QUANTITIES
MAY BE PICKED UP WITH ABSORBENT M ATERIAL.
Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

Handling

Handling and Storage Precautions:STORE AWAY FROM HEAT, SPARKS, AND OPEN
FLAME. AVOID PROLONGED SKIN CONTACT. DO NOT BREATHE SPRAY MIST.
COMBUSTIBLE LIQUID CLASS II.
Other Precautions:GROUND CNTNRS WHEN PURING & LIMIT FREE FALL TO A FEW
INCHES TO PVNT STATIC SPARKS. AVOID SPONTANEOUS COMBUSTION OF
CONTAMINATED RAGS & OTHER EASILY IGNITABLE ORGANIC ACCUMULATION BY
IMMEDIATE IMMERSIO N IN WATER. EMPTIED CNTNRS (SUPP DATA)

Exposure Controls

Respiratory Protection:NIOSH/MSHA APPROVED MASK OR RESPIRATOR FOR
ORGANIC VAPORS.
Ventilation:VENT SHOULD BE DESIGNED & MAINTAINED TO PROVIDE VOLUME AND
PATTERN SUFFICIENT TO PREVENT VAP CONC IN EXCESS OF TLV/LEL.
Protective Gloves:NEOPRENE RUBBER.
Eye Protection:CHEMICAL WORKERS GOGGLES
Other Protective Equipment:EYE WASH STATION AND SAFETY SHOWERS SHOULD
BE AVAILABLE.
Work Hygienic Practices:WASH HANDS AFTER USE AND BEFORE EATING OR USING
WASHROOM.
Supplemental Safety and Health
OTHER PREC: MAY RETAIN HAZARDOUS PROPERTIES. DO NOT CUT, PUNCTURE, OR
WELD ON OR NEAR CONTAINERS. KEEP AWAY FROM CHILDREN.

Chemical Properties

Boiling Pt:B.P. Text:>316F,>158C
Vapor Pres:SEE INGRED
Vapor Density:HVR/AIR
Spec Gravity:1.2 (H*2O=1)
Evaporation Rate & Reference:SLOWER THAN ETHER
Solubility in Water:INSOLUBLE
Appearance and Odor:VISCOUS LIQUID. MILD ODOR.

Stability

Stability Indicator/Materials to Avoid:YES
AVOID CONTACT WITH STRONG OXIDIZING AGENTS.
Stability Condition to Avoid:EXTREME HEAT OR HUMIDITY. ANY SOURCE OF IGNITION.
Hazardous Decomposition Products:USUAL PRODUCTS OF COMBUSTION - CARBON MONOXIDE, CARBON DIOXIDE, AND POSSIBLE ACROLEIN.

Disposal

Waste Disposal Methods:IN ACCORDANCE WITH LOCAL, STATE, AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.