

X 4000/4500 TONER, 6080

MSDS Number

BQRDJ

National Stock Number

6850-00N036573

Product Name

X 4000/4500 TONER, 6080

Manufacturer

PELIKAN INC

Product Identification

Product ID:X 4000/4500 TONER, 6080 MSDS Date:10/19/1987 FSC:6850 NIIN:00N036573 MSDS Number: BQRDJ

Responsible Party

PELIKAN INC

ONE IMAGING LN

DERRY, PA 15627

US

Emergency Phone: 412-694-2792

Info Phone: 412-694-2792

Cage: FO912

Contractor

PELIKAN INC TONER DEVELOPER DIV

DERRY, PA 15627

.

US

(412) 694-2792

Cage: 47811

Ingredients

CARBON; (CARBON BLACK)

CAS: 7440-44-0 RTECS: FF5250100

OSHA PEL15 MG/M3 TDUST

ACGIH TLV: 2 MG/M3 TDUST; 9293

KYNAR, 1,1-DIFLUOROETHANE HOMOPOLYMER; (POLYVINYLIDIENE

CAS: 24937-79-9

STYRENE, ACRYLATE COPOLYMER; (STYRENE/NBMA)

CAS: 25213-39-2

Hazards



LD50 LC50 Mixture: NONE SPECIFIED BY MANUFACTURER. Routes of Entry: Inhalation: YES Skin: NO Ingestion: YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic: THIS MATERIAL WHEN USED AS INTENDED,

DOES NOT REPRESENT A HEALTH OR SAFETY HAZARD.

Explanation of Carcinogenicity: NOT RELEVANT

Effects of Overexposure: MINIMAL RESPIRATORY TRACT IRRITATION MAY OCCUR

AS WITH EXPOSURE TO LARGE AMOUNTS OF ANY NON-TOXIC DUST.

Medical Cond Aggravated by Exposure: NONE SPECIFIED BY MANUFACTURER.

First Aid

First Aid: EYES: FLUSH WITH WATER FOR AT LEAST 15 MINUTES. SKIN: WASH WITH SOAP AND WATER. INHAL: REMOVE FROM EXPOSURE. INGEST: DILUTE STOMACH CONTENTS WITH SEVERAL GLASSES OF WATER.

Fire Fighting

Flash Point: NONE

Extinguishing Media: WATER, FOAM, DRY CHEMICAL, CARBON DIOXIDE. Fire Fighting Procedures: USE NIOSH/MSHA APPROVED SCBA AND FULL PROTECTIVE EQUIPMENT . AVOID INHALATION OF SMOKE.

Unusual Fire/Explosion Hazard:TONER IS A COMBUSTIBLE POWDER. WHEN DISPERSED IN AIR, IT FORMS EXPLOSIVE MIXTURE.

Accidental Release

Spill Release Procedures: REMOVE LOOSE TONER WITH VACUUM CLEANER. REMOVE RESIDUE WITH SOAP AND WATER. GARMENTS MAY BE WASHED OR DRY-CLEANED. Neutralizing Agent: NONE SPECIFIED BY MANUFACTURER.

Handling

Handling and Storage Precautions: KEEP CONTAINER CLOSED AND STORE IN A COOL, DRY PLACE.

Other Precautions: DO NOT HANDLE IN AREAS WHERE WIND BLOWS. AVOID INHALATION OF SMOKE. NON-HAZARDOUS FOR TRANSPORTATION.

Exposure Controls

Respiratory Protection: NOT REQUIRED FOR NORMAL USE. USE NIOSH/MSHA APPROVED RESPIRATOR APPROPRIATE FOR EXPOSURE OF CONCERN .

Ventilation: NONE SPECIFIED BY MANUFACTURER.

Protective Gloves: IMPERVIOUS GLOVES .

Eve Protection: CHEMICAL WORKERS GOGGLES .

Other Protective Equipment: FOR USE OTHER THAN NORMAL - GOGGLES AND

NIOSH/MSHA APPROVED RESPIRATORS MAY BE NEEDED.

Work Hygienic Practices: NONE SPECIFIED BY MANUFACTURER.

Supplemental Safety and Health

NONE SPECIFIED BY MANUFACTURER.

Chemical Properties

HCC:N1

Spec Gravity:1.2 (H*20 = 1) Solubility in Water:INSOLUBLE

Appearance and Odor: BLACK POWDER WITH A FAINT ODOR.

Stability

Stability Indicator/Materials to Avoid:YES

NONE

Stability Condition to Avoid: NONE

Hazardous Decomposition Products: PRODUCT OF COMBUSTION ARE TOXIC. AVOID BREATHING SMOKE.

Disposal

Waste Disposal Methods: DO NOT INCINERATE. NO SPECIAL TECHNIQUES BEYOND NORMAL PRACTICE. INSURE CONFORMITY WITH LOCAL, STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever,

https://msdsreport.com/msds/BQRDJ



particular situation.

expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their