# EXT. TRIM ENAMEL BLUE 15044, LEAD AND CHROM

## **MSDS Number**

**BQSQM** 

## **National Stock Number**

8010-01-333-9816

## **Product Name**

EXT. TRIM ENAMEL BLUE 15044, LEAD AND CHROM

#### Manufacturer

FARWEST PAINT MFG CO

# **Product Identification**

Product ID:EXT. TRIM ENAMEL BLUE 15044, LEAD AND CHROM MSDS Date:09/19/1991

FSC:8010 NIIN:01-333-9816 MSDS Number: BQSQM

# **Responsible Party**

FARWEST PAINT MFG CO

4522 S 133 ST

TUKWILA, WA 98168

US

Emergency Phone: 206-941-1619

Info Phone: 206-244-8844

Cage: 6F266

## **Contractor**

FARWEST PAINT MANUFACTURING CO

TUKWILA, WA 98168

206-244-8844

US

Cage: 6F266

# **Ingredients**

ETHYLENE GLYCOL

CAS: 107-21-1

RTECS: KW2975000

Fraction By Weight: 4.0%

OSHA PEL50 PPM ACGIH TLV: 50 PPM

EPA Report Quantity: 1 LB DOT Report Quantity: 1 LB

TEXANOL (ESTER ALCOHOL) (SARA 313)

CAS: 25265-77-4 RTECS: UF6000000 Fraction By Weight: 2%



OSHA PEL100 PPM ACGIH TLV: 100 PPM

#### **Hazards**

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic: INHALATION: PROLONGED INHALATION, IN

CONFINED AREAS, MAY LEAD TO MUCOUS MEMBRANE

IRRITATION-DIZZINESS-HEADACHE. SKIN: IRRITATION. EYE: IRRITATION. INGESTION: AMOUNTS INGESTED INCIDENTAL TO CONSUMER AN D INDUSTRIAL HANDLING ARE NOT LIKELY TOCAUSE INJURY, HOWEVER, INGESTION OF

LARGER AMOUNTS COULD CAUSE SERIOUS INJURY

#### First Aid

First Aid:INHALATION: REMOVE TO FRESH AIR. IF RESPIRATORY SYMPTOMS DEVELOP-SEEK MEDICAL ATTN IMMEDIATELY. SKIN: WASH OFF QUICKLY WITH PLENTY OF WATER. REMOVE AND WASH CONTAMINATED CLOTHING BEFORE REUSE. EYE: FL USH IMMEDIATELY WITH LARGE AMOUNTS OF WATER, ESPECIALLY UNDER LIDS, FOR 15 MINUTES. OBTAIN EMERGENCY MEDICAL TREATMENT. INGESTION: IF SWALLOWED, OBTAIN MEDICAL TREATMENT IMMEDIATELY.

## Fire Fighting

Extinguishing Media: FOAM, DRY CHEMICAL, WATER, OR WATER FOG Fire Fighting Procedures: WATER MAY BE USED TO COOL AND PROTECT EXPOSED CONTAINERS.

Unusual Fire/Explosion Hazard: WILL NOT BURN, CLOSED CONTAINERS MAY BURST IF EXPOSED TO EXTREME HEAT OR FIRE.

#### **Accidental Release**

Spill Release Procedures: COMPLY WITH ALL APPLICABLE HEALTH AND ENVIRONMENTAL REGULATIONS. VENTILATE AREA. SPILLS MAY BE COLLECTED WITH ABSORBENT MATERIALS.

### Handling

Handling and Storage Precautions: AVOID TEMPERATURES BELOW 40F. KEEP FROM FREEZING. STORE CONTAINERS WITH LIDS TIGHTLY CLOSED AND APPROPRIATELY LABELED.

Other Precautions: USE ONLY WITH ADEQUATE VENTILATION. AVOID BREATHING VAPOR AND SPRAY MIST. AVOID CONTACT WITH SKIN AND EYES.

# **Exposure Controls**

Respiratory Protection:IF PERSONAL EXPOSURE CANNOT BE CONTROLLED BELOW APPLICABLE LIMITS BY VENTILATION, WEAR A PROPERLY FITTED ORGANIC VAPOR/PARTICULATE RESPIRATOR APPROVED BY NIOSH/OSHA FOR PROTECTION AGAINST MATERIALS.

Ventilation:LOCAL EXHAUST PREFERRABLE. GENERAL EXHAUST IF EXPOSURE TO MATERIALS ARE MAINTAINED BELOW APPLICABLE EXPOSURE LIMITS.

Protective Gloves: GLOVES RECOMMENDED BY SUPPLIER

Eye Protection: SFTY GLASSES W/UNPERFORATED SIDESHIELDS

Other Protective Equipment: EYE WASH, SAFETY SHOWERS, GOGGLES, SAFETY GLASSES, IMPERVIOUS GLOVES.

Work Hygienic Practices: KEEP AREA CLEAN & FREE FROM SPILLS/LEAKS. ALWAYS WASH HANDS THOROUGHLY W/SOAP & WATER BEFORE HANDLING FOOD-DRINK-SMOKING

Supplemental Safety and Health

# **Chemical Properties**

Boiling Pt:B.P. Text:212F,100C Vapor Pres:23.8 @ 25C Vapor Density:> THAN AIR

pH:7-8

Evaporation Rate & Reference: SLOWER THAN ETHER

Solubility in Water:INFINITE

Appearance and Odor:THIXOTROPIC LIQUID WITH SLIGHT ODOR; COLOR OF TINT.

Percent Volatiles by Volume: 7.5%





# **Stability**

Stability Indicator/Materials to Avoid:YES OXIDIZERS AND/OR HYDROFLUORIC ACID Stability Condition to Avoid: ELEVATED TEMPERATURES, CONTACT WITH **OXIDIZING AGENTS** Hazardous Decomposition Products: CARBON MONOXIDE AND CARBON DIOXIDE

## **Disposal**

Waste Disposal Methods: DISPOSE OF ACCORDING TO LOCAL, STATE AND FEDERAL REGULATIONS. AVOID DISCHARGE TO NATURAL WATERS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.