

04050 ACRYWELD PART A

MSDS Number

BQZCM

National Stock Number

8040-00F027209

Product Name

04050 ACRYWELD PART A

Manufacturer

HARDMAN INC

Product Identification

Product ID:04050 ACRYWELD PART A

MSDS Date:08/15/1988

FSC:8040

NIIN:00F027209

Kit Part:Y

MSDS Number: BQZCM

Responsible Party

HARDMAN INC

600 CORTLANDT ST

BELLEVILLE , NJ 07109-3328

US

Emergency Phone: 201-751-3000

Info Phone: 201-751-3000

Preparer: NORMAN S WOLFROM

Cage: 96900

Contractor

HARDMAN INC

BELLEVILLE, NJ 07109-3328

US

201-751-3000

Cage: 96900

Ingredients

METHYL METHACRYLATE, (MONOMER)

CAS: 80-62-6

RTECS: OZ5075000

Fraction By Weight: 50-75%

OSHA PEL410 MG/CUM

ACGIH TLV: 410 MG/CUM

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

METHACRYLIC ACID

CAS: 79-41-4

RTECS: OZ2975000

OSHA PEL20 PPM

ACGIH TLV: 70 MG/CUM

AROMATIC AMINE

8.42

RTECS: 9999999WG

Hazards

Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:INHALATION: IRRITATION, WATERY EYES.

Explanation of Carcinogenicity:NONE

First Aid

First Aid:INHALATION: REMOVE TO FRESH AIR. GIVE OXYGEN IF BREATHING IS DIFFICULT. EYES: FLUSH THOROUGHLY W/WATER FOR AT LEAST 15 MINS.

INGESTION: DRINK 1-2 GLASSES OF WATER. DON'T INDUCE VOMITING. SKIN: WIPE EX CESS & FLUSH W/PLENTY OF WATER FOR AT LEAST 15 MINS. FOLLOW BY WASHING W/SOAP & WATER. OBTAIN MEDICAL ATTENTION IN ALL CASES.

Fire Fighting

Flash Point:53F

Extinguishing Media:WATER SPRAY, DRY CHEMICAL, FOAM, CO2

Fire Fighting Procedures:USE FULL PROTECTIVE CLOTHING & A POSITIVE PRESSURE SCBA.

Accidental Release

Spill Release Procedures:CONTAIN SPILL IF POSSIBLE. WIPE UP OR ABSORB ON SUITABLE MATERIAL & SHOVEL UP. CLEAN UP W/SUITABLE VENTILATION.

Handling

Other Precautions:AVOID ALL PERSONAL CONTACT.

Exposure Controls

Respiratory Protection:IN THE ABSENCE OF PROPER ENVIRONMENTAL CONTROL OR VENTILATION, THEN A POSITIVE-PRESSURE BREATHING APPARATUS OR FULL FACE RESPIRATOR W/AN APPROVED CANISTER IS RECOMMENDED.

Ventilation:LOCAL EXHAUST

Protective Gloves:NITRILE RUBBER, IMPERVIOUS

Eye Protection:SAFETY GLASSES W/SIDE SHIELDS

Work Hygienic Practices:REMOVE/LAUNDER CONTAMINATED CLOTHING BEFORE REUSE. CONTAMINATED LEATHER CANNOT BE DECONTAMINATED, SHOULD BE DESTROYED.

Supplemental Safety and Health

Chemical Properties

Boiling Pt:B.P. Text:200F

Vapor Density:>1

Appearance and Odor:LIQUID

Percent Volatiles by Volume:0%

Stability

Stability Indicator/Materials to Avoid:YES

OXIDIZING AGENTS

Disposal

Waste Disposal Methods:INCINERATE OR BURY IN LEGAL LANDFILL IN ACCORDANCE W/FEDERAL, STATE & LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.