

## **818 ENAMEL**

### **MSDS Number**

BQZXN

### **National Stock Number**

8010-00F027709

### **Product Name**

818 ENAMEL

### **Manufacturer**

PLASTI KOTE INC (TEMPO PRODUCTS CO)

### **Product Identification**

Product ID:818 ENAMEL

MSDS Date:09/04/1992

FSC:8010

NIIN:00F027709

MSDS Number: BQZXN

### **Responsible Party**

PLASTI-KOTE INC (TEMPO PRODUCTS CO)

1000 LAKE RD

MEDINA , OH 44258

US

Emergency Phone: 216-725-4511

Info Phone: 216-725-4511

Cage: EO706

### **Contractor**

TEMPO PRODUCTS CO A PLASTI-KOTE CO INC

MEDINA, OH 44256

US

330-725-4511

Cage: 07708

### **Ingredients**

ACETONE; DIMETHYL KETONE

CAS: 67-64-1

RTECS: AL3150000

Fraction By Weight: 33-42%

OSHA PEL1000PPM

ACGIH TLV: 750PPM/1000STEL;9293

EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

ETHYL ACETATE

CAS: 141-78-6

RTECS: AH5425000

Fraction By Weight: 0-5%

OSHA PEL1400 MG/CUM

ACGIH TLV: 1400 MG/CUM

EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

ETHANOL (ETHYL ALCOHOL), TECSOL, ALCOHOL

CAS: 64-17-5

RTECS: KQ6300000

Fraction By Weight: 5-10%

OSHA PEL1000 PPM

ACGIH TLV: 1000 PPM

DIACETONE ALCOHOL

CAS: 123-42-2

RTECS: SA9100000

Fraction By Weight: 5-10%

OSHA PEL240 MG/CUM

ACGIH TLV: 238 MG/CUM

2-BUTANONE (METHYL ETHYL KETONE) (MEK)

CAS: 78-93-3

RTECS: EL6475000

Fraction By Weight: 0-5%

OSHA PEL200 PPM

ACGIH TLV: 590 MG/CUM

EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

XYLENE, DIMETHYLBENZENE, XYLOL

CAS: 1330-20-7

RTECS: ZE2100000

Fraction By Weight: 5-10%

OSHA PEL100 PPM

ACGIH TLV: 100 PPM, SKIN

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

HYDROCARBON PROPELLANT, PETROLEUM GASES LIQUEFIED

CAS: 68476-86-8

Fraction By Weight: 23%

7.8-8 (PAINT)

RTECS: 9999999WG

## Hazards

Routes of Entry: Inhalation:YES Skin:NO Ingestion:YES  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:INHALATION: NASAL & RESPIRATORY IRRITATION, DIZZINESS, WEAKNESS, FATIGUE, NAUSEA, HEADACHE, POSSIBLE UNCONSCIOUSNESS & ASPHYXIATION. EYES: IRRITATION, REDNESS, TEARING, & BLURRED VISION. INGESTION: GASTROINTESTINAL IRRITATION, NAUSEA, VOMITING, & DIARRHEA. SKIN: IRRITATION.  
Explanation of Carcinogenicity:NONE  
Effects of Overexposure:INHALATION: PERMANENT BRAIN & NERVOUS SYSTEM DAMAGE. INTENTIONAL MISUSE BY DELIBERATELY CONCENTRATING & INHALING THE CONTENTS MAY BE HARMFUL OR FATAL.  
Medical Cond Aggravated by Exposure:RESPIRATORY &/OR SKIN REACTION

## First Aid

First Aid:INHALATION: REMOVE TO FRESH AIR. IF BREATHING IS DIFFICULT ADMINISTER OXYGEN. IF BREATHING STOPS, GIVE ARTIFICIAL RESPIRATION. EYES: FLUSH W/WATER FOR 15 MINS. INGESTION: DON'T INDUCE VOMITING. ASPIRATION OF MATERIAL INTO LUNGS CAN CAUSE PNEUMONITIS, WHICH CAN BE FATAL. KEEP WARM & QUIET. SKIN: WASH W/SOAP & WATER OR VARIOUS HAND CLEANERS. OBTAIN MEDICAL ATTENTION IN ALL CASES.

## Fire Fighting

Flash Point:0F/-18C  
Lower Limits:1%  
Extinguishing Media:ALCOHOL FOAM, CO2, DRY CHEMICAL  
Fire Fighting Procedures:WATER SPRAY MAY BE INEFFECTIVE, BUT MAY BE USED TO COOL CLOSED CONTAINERS. FOG NOZZLES ARE PREFERABLE IF USING WATER. WEAR SELF-CONTAINED BREATHING APPARATUS.  
Unusual Fire/Explosion Hazard:CLOSED CONTAINERS MAY EXPLODE/AUTOIGNITE DUE TO PRESSURE BUILD-UP & EXPOSURE TO EXTREME HEAT. VAPORS ARE HEAVIER THAN AIR & MAY TRAVEL ALONG GROUND. FLAMMABLE.

## Accidental Release

Spill Release Procedures:ELIMINATE ALL IGNITION SOURCES. VENTILATE AREA. ABSORB LIQUID ON PAPER, VERMICULITE, FLOOR ABSORBENT OR OTHER ABSORBENT MATERIAL & TRANSFER TO CLOSED CONTAINER.

## Handling

Handling and Storage Precautions:DON'T STORE ABOVE 120F OR IN DIRECT SUNLIGHT. DON'T PUNCTURE OR INCINERATE.  
Other Precautions:STORE LARGE QUANTITIES IN BUILDING PROTECTED FOR STORAGE OF FLAMMABLE LIQUIDS. AVOID BREATHING VAPORS OR SPRAY MIST.

## Exposure Controls

Respiratory Protection:USE NIOSH/MSHA TC23C OR EQUIVALENT  
Ventilation:SUFFICIENT MECHANICAL (GENERAL) &/OR LOCAL EXHAUST TO KEEP EXPOSURE BELOW TLV. OPEN WINDOWS/DOORS TO ENSURE FRESH AIR.  
Protective Gloves:CHEMICAL RESISTANT SUCH AS NEOPRENE  
Eye Protection:CHEMICAL SPLASH GOGGLES  
Work Hygienic Practices:REMOVE/LAUNDER CONTAMINATED CLOTHING BEFORE REUSE. WASH HANDS BEFORE EATING OR USING WASHROOM.  
Supplemental Safety and Health

## Chemical Properties

Boiling Pt:B.P. Text:133-331F  
Melt/Freeze Pt:M.P/F.P Text: 1500F  
Vapor Density:>1  
Spec Gravity:Evaporation Rate & Reference:SLOWER THAN ETHER  
Solubility in Water:SLIGHT TO MODERATE  
Appearance and Odor:TYPICAL SOLVENT PAINT  
Percent Volatiles by Volume:85-90

## Stability

Stability Indicator/Materials to Avoid: YES

STRONG OXIDIZING AGENTS

Stability Condition to Avoid: HEAT, PILOT LIGHTS, FLAMES, SPARKS,

HEATERS, SMOKING, ELECTRIC MOTORS, & OTHER IGNITION SOURCES

Hazardous Decomposition Products: CO<sub>2</sub>, CO, VARIOUS HYDROCARBONS,

NITROGEN COMPOUNDS

## Disposal

Waste Disposal Methods: DEPOSIT ABSORBENT MATERIAL IN A POSTED TOXIC

SUBSTANCE LANDFILL IN ACCORDANCE W/FEDERAL, STATE, & LOCAL

REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department

of Defense. The United States of America in no manner whatsoever,

expressly or implied, warrants this information to be accurate and

disclaims all liability for its use. Any person utilizing this

document should seek competent professional advice to verify and

assume responsibility for the suitability of this information to their

particular situation.