

16-655 RESIN HYDROCARBON

MSDS Number

BRBBL

National Stock Number

8010-00F027769

Product Name

16-655 RESIN HYDROCARBON

Manufacturer

SEYMOUR OF SYCAMORE INC

Product Identification

Product ID:16-655 RESIN HYDROCARBON

MSDS Date:01/22/1990

FSC:8010

NIIN:00F027769

MSDS Number: BRBBL

Responsible Party

SEYMOUR OF SYCAMORE INC

917 CROSBY AVE

SYCAMORE , IL 60178-1343

US

Emergency Phone: 815-891-9101

Info Phone: 815-892-9101

Cage: 59581

Contractor

SEYMOUR OF SYCAMORE

SYCAMORE, IL 60178-1343

US

815-895-9101/800-255-3924

Cage: 59581

Ingredients

METHANOL (METHYL ALCOHOL), COLUMBIAN SPIRITS

CAS: 67-56-1

RTECS: PC1400000

Fraction By Weight: 2-5%

OSHA PELS,200PPM/250STEL

ACGIH TLV: S,200PPM/250STEL; 93

EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

MEDIUM ALIPHATIC NAPHTHA (AROMATIC 100), PARAFFIN-NAPTHANES

CAS: 64742-88-7

OSHA PEL100 PPM

ACGIH TLV: 100 PPM

TITANIUM DIOXIDE, TIO₂

CAS: 13463-67-7

RTECS: XR2275000

OSHA PEL15 MG/M3 TDUST

ACGIH TLV: 10 MG/M3 TDUST; 9293

TOLUENE

CAS: 108-88-3

RTECS: XS5250000

Fraction By Weight: 7-17%

OSHA PEL200 PPM/150 STEL

ACGIH TLV: 50 PPM; 9293

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

V M & P NAPHTHA, LIGROINE, MINERAL SPIRITS

CAS: 8032-32-4

RTECS: OI6180000

OSHA PEL300 PPM

ACGIH TLV: 300 PPM

XYLENE, DIMETHYLBENZENE, XYLOL

CAS: 1330-20-7

RTECS: ZE2100000

Fraction By Weight: 2-6%

OSHA PEL100 PPM

ACGIH TLV: 100 PPM, SKIN

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

PROPANE

CAS: 74-98-6

RTECS: TX2275000

OSHA PEL1000 PPM

ACGIH TLV: SIMPLE ASPHYXIAN

ISOBUTANE, 2-METHYLPROPANE

CAS: 75-28-5

RTECS: TZ4300000

OSHA PEL1800 MG/CUM

ACGIH TLV: 1000 PPM

COLUMBIA CARBON, CARBON BLACK, LAMPBLACK (SUSPECTED HUMAN

CAS: 1333-86-4

RTECS: FF5800000

OSHA PEL3.5 MG/CUM

ACGIH TLV: 3.5 MG/CUM

HEXANE, N-HEXANE

CAS: 110-54-3

RTECS: MN9275000

OSHA PEL500 PPM

ACGIH TLV: 50 PPM; 9293

EPA Report Quantity: 1 LB

DOT Report Quantity: 1 LB

Hazards

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:INHALATION: RESPIRATORY SYSTEM IRRITATION. EYES: IRRITATION. INGESTION: ACCIDENTAL INGESTION IS UNLIKELY FROM AN AEROSOL CAN.

Explanation of Carcinogenicity:SEE INGREDIENTS.

Effects of Overexposure:INHALATION:

IRRITATION/HEADACHE/DIZZY/NAUSEA/UNCONSCIOUS/ASPHYXIA. SKIN:

DEFATTING (IRRITATION/DERMATITIS). HEXANE: PERIPHERAL

POLYNEUROPATHY. METHYL ALCOHOL: CNS (OPTIC NERVE)

EFFECT/BLIND/POISONOUS ABSORPTION/LIVER DAMAGE/DEATH. VM&P: SKIN

IRRITATION/CNS DEPRESSION. TOLUENE: CARDIAC EFFECT. MINERAL SPIRIT:

NARCOSIS.

First Aid

First Aid:INHALATION: REMOVE TO FRESH AIR. IF BREATHING STOPS, BEGIN ARTIFICIAL RESPIRATION. EYES: IMMEDIATELY FLUSH W/PLENTY OF WATER FOR AT LEAST 15 MINS. SKIN: WASH W/SOAP & WATER. INGESTION: OBTAIN MEDICAL ATTENTION IN ALL CASES.

Fire Fighting

Flash Point Method:TOC

Flash Point:-10F

Lower Limits:0.7%

Upper Limits:9.5%

Extinguishing Media:CO2, DRY CHEMICAL, OR FOAM

Fire Fighting Procedures:WATER SPRAY MAY BE INEFFECTIVE. WATER MAY BE USED TO COOL CONTAINERS TO PREVENT BURSTING. IF WATER IS USED, FOG NOZZLES ARE PREFERABLE. WEAR GOGGLES/SCBA.

Unusual Fire/Explosion Hazard:EXPOSURE TO HEAT OR PROLONG EXPOSURE TO SUN MAY CAUSE BURSTING.

Accidental Release

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION. AVOID BREATHING VAPORS. VENTILATE AREA. WIPE UP W/INERT MATERIALS & PLACE IN APPROPRIATE CONTAINER.

Handling

Handling and Storage Precautions:DON'T STORE >120F. USE ONLY AS DIRECTED. AVOID CONTINUOUS BREATHING OF VAPORS & SPRAY MIST.

Other Precautions:INTENTIONAL MISUSE BY DELIBERATELY CONCENTRATING

VAPORS & INHALING CONTENTS CAN BE HARMFUL OR FATAL.

Exposure Controls

Respiratory Protection:WEAR SELF-CONTAINED BREATHING APPARATUS FOR CONCENTRATIONS ABOVE TLV LIMITS.

Ventilation:USE W/ADEQUATE VENTILATION, SUFFICIENT TO PREVENT INHALATION OF SOLVENT VAPORS.

Protective Gloves:OPTIONAL

Eye Protection:AS NEEDED

Supplemental Safety and Health

Chemical Properties

Vapor Pres:40 PSIA

Vapor Density:>1

Evaporation Rate & Reference:FASTER THAN ETHER

Solubility in Water:INSOLUBLE

Appearance and Odor:PAINT SOLVENT ODOR.

Percent Volatiles by Volume: 85%

Stability

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS

Stability Condition to Avoid:TEMPS >120F, SPARKS, PILOT LIGHT, OPEN

FLAME, SUN, OR OTHER SOURCES OF IGNITION

Hazardous Decomposition Products:HAZARDOUS FUMES SUCH AS CO, CO2, PHOSGENE, HYDROGEN CHLORIDE, & CHLORINATED ACIDS, ALDEHYDES, & KETONES

Disposal

Waste Disposal Methods:DON'T INCINERATE AEROSOL, DISPOSE OF IN ACCORDANCE W/LOCAL, STATE, & FEDERAL REGULATIONS. DON'T PLACE AEROSOL CANS IN HOME COMPACTOR. DON'T PUNCTURE.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.