

TAPE AWAY

MSDS Number

BRBKX

National Stock Number

6850-00F028057

Product Name

TAPE AWAY

Manufacturer

DEFLECT O CORP

Product Identification

Product ID:TAPE AWAY
MSDS Date:10/01/1988
FSC:6850
NIIN:00F028057
MSDS Number: BRBKX

Responsible Party

DEFLECT-O CORP
7035 E 86TH ST
INDIANAPOLIS , IN 46250-1547
US
Emergency Phone: 800-428-4328
Info Phone: 317-849-9556
Preparer: MYRNA G SPROUL
Cage: 54326

Contractor

DEFLECT-O CORP
INDIANAPOLIS, IN 46250-1547
US
317-849-9556
Cage: 54326

Ingredients

ISOPARAFFINIC HYDROCARBONS (NAPHTHA PETROLEUM),
CAS: 64742-48-9

Hazards

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:EYE: TEMPORARY DISCOMFORT &
IRRITATION. INGESTION: TOXIC. DON'T INDUCE VOMITING BECAUSE SMALL
AMOUNTS OF SOLVENT, IF ASPIRATED IN THE LUNGS DURING VOMITING MAY
CAUSE SEVERE PULMONARY INJURY & EVEN DEATH. INHALATION:
RESPIRATORY TRACT IRRITATION, HEADACHE/DIZZINESS/SLEEPINESS & OTHER
CENTRAL NERVOUS SYSTEM EFFECTS.
Explanation of Carcinogenicity:NONE
Effects of Overexposure:SKIN: IRRITATION & DERMATITIS.
Medical Cond Aggravated by Exposure:DERMATITIS OR OTHER SKIN
CONDITIONS.

First Aid

First Aid:EYES: FLUSH W/WATER FOR AT LEAST 15 MINS; IF A BURNING SENSATION PERSISTS CALL A PHYSICIAN. SKIN: WASH W/SOAP & WATER. INGESTION: DON'T INDUCE VOMITING. INHALATION: REMOVE TO FRESH AIR. OBTAIN MEDICAL ATTENTION IN ALL CASES.

Fire Fighting

Flash Point Method:TCC
Flash Point:115F/46C
Lower Limits:0.7%
Upper Limits:7%
Extinguishing Media:FOAM, WATER SPRAY (FOG), DRY CHEMICAL, CO2, & VAPORIZING LIQUID TYPE EXTINGUISHING AGENTS ARE SUITABLE.
Fire Fighting Procedures:WATER UNDER MANY SITUATIONS, MAY BE INEFFECTIVE AS IT CAN SPREAD THE FIRE.
Unusual Fire/Explosion Hazard:KEEP MATERIAL AWAY FROM SPARK & HEAT SOURCES. FLAMMABLE. AUTOIGNITION TEMPERATURE 750F/399C.

Accidental Release

Spill Release Procedures:SHUT OFF SOURCES OF IGNITION. KEEP PEOPLE AWAY. WIPE UP OR ABSORB SPILL IN SUCH A WAY TO MINIMIZE SKIN CONTACT.

Handling

Handling and Storage Precautions:KEEP CONTAINER CLOSED WHEN NOT IN USE. STORE AWAY FROM HEAT, SPARKS, FLAMES OR STRONG OXIDANTS.
Other Precautions:AVOID CONTACT W/EYES/SKIN. KEEP OUT OF REACH OF CHILDREN. IF CONTACT IS LIKELY, WEAR RUBBER GLOVES & GOGGLES.

Exposure Controls

Protective Gloves:RUBBER
Eye Protection:GOGGLES
Work Hygienic Practices:REMOVE & WASH CONTAMINATED CLOTHES BEFORE REUSE.
Supplemental Safety and Health
STUDIES HAVE SHOWN THAT MANY PETROLEUM HYDROCARBONS POSE POTENTIAL HUMAN HEALTH RISKS WHICH MAY VARY FROM PERSON TO PERSON.

Chemical Properties

Boiling Pt:B.P. Text:340-386F
Vapor Pres:Vapor Density:>5
Spec Gravity:0.760
Evaporation Rate & Reference:(BU AC = 1): 0.1
Solubility in Water:NEGLIGIBLE
Appearance and Odor:WATER WHITE LIQUID, W/FAINT ODOR.
Percent Volatiles by Volume:100

Stability

Stability Indicator/Materials to Avoid:YES
OXIDIZERS, OXYGEN, LIQUID CHLORINE & HYPOCHLORITES.
Stability Condition to Avoid:HEAT, SPARKS, FLAMES
Hazardous Decomposition Products:CO, & UNIDENTIFIED ORGANIC COMPOUNDS MAY BE FORMED DURING COMBUSTION.

Disposal

Waste Disposal Methods:DISCARD CONTAMINATED RAGS OR ABSORBENT IN A WASTE CONTAINER. OBSERVE RCRA, LOCAL, STATE & FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.