

963 PACON SUPREME ALKYD SEMI-GLOSS NEUTRAL BASE

MSDS Number

BRBTQ

National Stock Number

8010-00F028303

Product Name

963 PACON SUPREME ALKYD SEMI-GLOSS NEUTRAL BASE

Manufacturer

BRUNING PAINT CO INC

Product Identification

Product ID:963 PACON SUPREME ALKYD SEMI-GLOSS NEUTRAL BASE MSDS Date:10/11/1989 FSC:8010 NIIN:00F028303 MSDS Number: BRBTQ

Responsible Party

BRUNING PAINT CO INC

601 S HAVEN ST

BALTIMORE , MD 21224-4347

US

Emergency Phone: 301-342-3636AM/301-342-3641PM

Info Phone: 301-342-3636AM/301-342-3641PM

Cage: EO376

Contractor

KYANIZE PAINT

BALTIMORE, MD 21224

US

800-368-2076

Cage: 85520

Ingredients

V M & P NAPHTHA, LIGROINE, MINERAL SPIRITS CAS: 8032-32-4 RTECS: OI6180000 Fraction By Weight: 35-50% OSHA PEL300 PPM ACGIH TLV: 300 PPM

8.8 WT/GAL. RTECS: 9999999WG

3.707 RTECS: 9999999VO



Hazards

Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:EYES: IRRITATION. Explanation of Carcinogenicity:NONE Effects of Overexposure:INHALATION: PERMANENT BRAIN & NERVOUS SYSTEM DAMAGE. MUCOUS MEMBRANE IRRITATION.

•

First Aid

First Aid:EYE: FLUSH W/LUKE WARM WATER FOR AT LEAST 15 MINS. SKIN: WASH W/COPIOUS AMOUNTS OF LUKE WARM WATER. INHALATION: REMOVE TO FRESH AIR. RESTORE BREATHING IF REQUIRED. INGESTION: RINSE MOUTH IMMEDIATELY. GIVE EXPOSED INDIVIDUAL 6 TO 8 OUNCES OF LIQUID. (NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON.) DON'T INDUCE VOMITING UNLESS ADVISED BY A PHYSICIAN. OBTAIN MEDICAL ATTENTION IN ALL CASES.

Fire Fighting

Flash Point Method:TCC Flash Point:104F Lower Limits:.9% Upper Limits:7.0% Extinguishing Media:NATIONAL FIRE PROTECTION ASSOCIATION CLASS B EXTINGUISHER IS DESIGNED TO EXTINGUISH NFPA CLASS 1B FLAMMABLE LIQUID FIRES Fire Fighting Procedures:WATER SPRAY MAY BE INEFFECTIVE. USE WATER TO COOL CLOSED CONTAINERS TO PREVENT PRESSURE BUILDUP/AUTOIGNITION/EXPLOSION. FOG NOZZLES ARE PREFERABLE.

Accidental Release

Spill Release Procedures:CONTAIN DISCHARGE. KEEP ALL SOURCES OF IGNITION AWAY. VENTILATE AREA. USE NON-SPARKING TOOLS FOR CLEANUP. COVER W/INERT MATERIAL TO REDUCE FUMES. KEEP OUT OF DRAINS/SEWERS/WATERWAYS. CONTACT FIRE AUTH ORITIES. NOTIFY LOCAL HEALTH/POLLUTION AGENCIES.

Handling

Handling and Storage Precautions: KEEP CONTAINERS TIGHTLY CLOSED. GROUND CONTAINERS WHEN POURING & LIMIT FREE FALL TO A FEW INCHES TO PREVENT STATIC SPARKS. DON'T TAKE INTERNALLY. Other Precautions: KEEP OUT OF REACH OF CHILDREN. INTENTIONAL MISUSE BY DELIBERATELY CONCENTRATING & INHALING THE CONTENTS MAY BE HARMFUL OR FATAL. DON'T BREATH VAPORS OR SPRAY MIST. AVOID CONTACT W/EYES. DON'T CUT OR P UNCTURE OR WELD NEAR CONTAINER.

Exposure Controls

Respiratory Protection: IN OUTDOOR OR OPEN AREAS USE NIOSH/MSHA APPROVED MECHANICAL FILTER RESPIRATOR. IN RESTRICTED VENTILATION AREAS USE NIOSH/MSHA APPROVED CHEMICAL MECHANICAL FILTER RESPIRATOR. IN CONFINED AREAS USE NIOS H/MSHA APPROVED AIR LINE RESPIRATOR/HOOD Ventilation: PROVIDE GENERAL DILUTION OR LOCAL EXHAUST. Protective Gloves: NATURAL RUBBER, NEOPRENE, NITRILE Eye Protection: GOGGLES Other Protective Equipment: APRON Work Hygienic Practices: REMOVE & WASH CONTAMINATED CLOTHES BEFORE REUSE. WASH HANDS THOROUGHLY BEFORE EATING & USING WASHROOM. Supplemental Safety and Health THIS PRODUCT CONTAINS PIGMENTS WHICH MAY BECOME A DUST NUISANCE UPON ABRASIVE BLASTING, SANDING, GRINDING.

Chemical Properties

Boiling Pt:B.P. Text:300-388F Vapor Pres:2.00 Vapor Density:>1 Evaporation Rate & Reference:SLOWER THAN BU AC Percent Volatiles by Volume:56.98



Stability

Stability Indicator/Materials to Avoid:YES STRONG ACIDS Stability Condition to Avoid:SPARKS, OPEN FLAME, HOT SURFACES, & ALL SOURCES OF HEAT & IGNITION. Hazardous Decomposition Products:CO, CO2, & OXIDES OF NITROGEN.

Disposal

Waste Disposal Methods:DON'T FLUSH TO SEWER, WATERSHED, OR WATERWAY. DISPOSE OF IN ACCORDANCE W/LOCAL, STATE & FEDERAL REGULATIONS. DON'T INCINERATE CLOSED CONTAINERS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.