# **802 ZINC PRIMER GREEN**

## **MSDS Number**

**BRBYM** 

#### **National Stock Number**

8010-00F028398

#### **Product Name**

802 ZINC PRIMER GREEN

#### Manufacturer

PLASTI KOTE INC (TEMPO PRODUCTS CO)

## **Product Identification**

Product ID:802 ZINC PRIMER GREEN MSDS Date:09/04/1992 FSC:8010 NIIN:00F028398 MSDS Number: BRBYM

# **Responsible Party**

PLASTI-KOTE INC (TEMPO PRODUCTS CO)

1000 LAKE RD

MEDINA , OH 44258

US

Emergency Phone: 216-725-4511

Info Phone: 216-725-4511

Cage: E0706

Contractor

TEMPO PRODUCTS CO A PLASTI-KOTE CO INC

MEDINA, OH 44256

US

330-725-4511 Cage: 07708

#### **Ingredients**

HYDROCARBON PROPELLANT, PETROLEUM GASES LIQUEFIED

CAS: 68476-86-8

Fraction By Weight: 27%

7.8-8 (PAINT)

RTECS: 9999999WG

XYLENE, DIMETHYLBENZENE, XYLOL

CAS: 1330-20-7 RTECS: ZE2100000

Fraction By Weight: 20-25%

OSHA PEL100 PPM

ACGIH TLV: 100 PPM, SKIN



EPA Report Quantity: 1000 LBS DOT Report Quantity: 1000 LBS

ACETONE; DIMETHYL KETONE

CAS: 67-64-1

RTECS: AL3150000

Fraction By Weight: 30-35%

OSHA PEL1000PPM

ACGIH TLV: 750PPM/1000STEL;9293

EPA Report Quantity: 5000 LBS DOT Report Quantity: 5000 LBS

## **Hazards**

Routes of Entry: Inhalation:YES Skin:NO Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic: INHALATION: NASAL & RESPIRATORY IRRITATION, DIZZINESS, WEAKNESS, FATIGUE, NAUSEA, HEADACHE,

POSSIBLE UNCONSCIOUSNESS & ASPHYXIATION. EYES: IRRITATION, REDNESS, TEARING, & BLURRED VISION. INGESTION: GA STROINTESTINAL IRRITATION,

NAUSEA, VOMITING, & DIARRHEA. SKIN: IRRITATION.

Explanation of Carcinogenicity: NONE

Effects of Overexposure: INHALATION: PERMANENT BRAIN & NERVOUS SYSTEM DAMAGE. INTENTIONAL MISUSE BY DELIBERATELY CONCENTRATING & INHALING THE CONTENTS MAY BE HARMELY OR FATAL

THE CONTENTS MAY BE HARMFUL OR FATAL.

Medical Cond Aggravated by Exposure: RESPIRATORY &/OR SKIN REACTION

## First Aid

First Aid:INHALATION: REMOVE TO FRESH AIR. IF BREATHING IS DIFFICULT ADMINISTER OXYGEN. IF BREATHING STOPS, GIVE ARTIFICIAL RESPIRATION. EYES: FLUSH W/WATER FOR 15 MINS. INGESTION: DON'T INDUCE VOMITING. ASPIRA TION OF MATERIAL INTO LUNGS CAN CAUSE PNEUMONITIS, WHICH CAN BE FATAL. KEEP WARM & QUIET. SKIN: WASH W/SOAP & WATER OR VARIOUS HAND CLEANERS. OBTAIN MEDICAL ATTENTION IN ALL CASES.

## Fire Fighting

Flash Point:0F/-18C Lower Limits:1%

Extinguishing Media:ALCOHOL FOAM, CO2, DRY CHEMICAL Fire Fighting Procedures:WATER SPRAY MAY BE INEFFECTIVE, BUT MAY BE

USED TO COOL CLOSED CONTAINERS. FOG NOZZLES ARE PREFERABLE IF USING WATER. WEAR SELF-CONTAINED BREATHING APPARATUS.

Unusual Fire/Explosion Hazard: CLOSED CONTAINERS MAY EXPLODE/AUTOIGNITE DUE TO PRESSURE BUILD-UP & EXPOSURE TO EXTREME HEAT. VAPORS ARE

HEAVIER THAN AIR & MAY TRAVEL ALONG GROUND. FLAMMABLE.

# **Accidental Release**

Spill Release Procedures: ELIMINATE ALL IGNITION SOURCES. VENTILATE AREA. ABSORB LIQUID ON PAPER, VERMICULITE, FLOOR ABSORBENT OR OTHER ABSORBENT MATERIAL & TRANSFER TO CLOSED CONTAINER.

# Handling

Handling and Storage Precautions: DON'T STORE ABOVE 120F OR IN DIRECT SUNLIGHT. DON'T PUNCTURE OR INCINERATE.

Other Precautions:STORE LARGE QUANTITIES IN BUILDING PROTECTED FOR STORAGE OF FLAMMABLE LIQUIDS. AVOID BREATHING VAPORS OR SPRAY MIST.

#### **Exposure Controls**

Respiratory Protection: USE NIOSH/MSHA TC23C OR EQUIVALENT Ventilation: SUFFICIENT MECHANICAL (GENERAL) &/OR LOCAL EXHAUST TO KEEP EXPOSURE BELOW TLV. OPEN WINDOWS/DOORS TO ENSURE FRESH AIR.



Protective Gloves: CHEMICAL RESISTANT SUCH AS NEOPRENE

Eye Protection: CHEMICAL SPLASH GOGGLES

Work Hygienic Practices: REMOVE/LAUNDER CONTAMINATED CLOTHING BEFORE

REUSE. WASH HANDS BEFORE EATING OR USING WASHROOM.

Supplemental Safety and Health

# **Chemical Properties**

Boiling Pt:B.P. Text:133-331F Melt/Freeze Pt:M.P/F.P Text: 1500F

Vapor Density:>1

Spec Gravity: Evaporation Rate & Reference: SLOWER THAN ETHER

Solubility in Water:SLIGHT TO MODERATE Appearance and Odor:TYPICAL SOLVENT PAINT

Percent Volatiles by Volume:85-90

# **Stability**

Stability Indicator/Materials to Avoid:YES STRONG OXIDIZING AGENTS Stability Condition to Avoid:HEAT, PILOT LIGHTS, FLAMES, SPARKS, HEATERS, SMOKING, ELECTRIC MOTORS, & OTHER IGNITION SOURCES Hazardous Decomposition Products:CO2, CO, VARIOUS HYDROCARBONS, NITROGEN COMPOUNDS

#### **Disposal**

Waste Disposal Methods: DEPOSIT ABSORBENT MATERIAL IN A POSTED TOXIC SUBSTANCE LANDFILL IN ACCORDANCE W/FEDERAL, STATE, & LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.