

CYCLE - II LATEX S/G PALO. BEIGE P/C 77401

MSDS Number

BRKMV

National Stock Number

8010-01-347-0931

Product Name

CYCLE - II LATEX S/G PALO. BEIGE P/C 77401

Manufacturer

MAJOR PAINT COMPANY

Product Identification

Product ID: CYCLE - II LATEX S/G PALO. BEIGE P/C 77401

MSDS Date: 08/03/1992

FSC: 8010

NIIN: 01-347-0931

MSDS Number: BRKMV

Responsible Party

MAJOR PAINT COMPANY

1300 WEST 190TH STREET

TORRANCE , CA 90509-2868

US

Emergency Phone: 310-542-7701

Info Phone: 310-542-7701

Cage: MAJOR

Contractor

MAJOR PAINT COMPANY

2868

TORRANCE, CA 90509-2868

US

310-542-7701

Cage: MAJOR

Ingredients

DIETHYLENE GLYCOL MONOETHYL ETHER (VAPOR PRESSURE 0.1 MM HG

CAS: 111-90-0

RTECS: KK8750000

Fraction By Weight: 2%

2,2,4-TRIMETHYL-1,3-PENTANEDIOL MONOISBUTYRATE

CAS: 25265-77-4

RTECS: UF6000000

1.55 LB/GL

RTECS: 9999999VO

Hazards

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:MAY CAUSE NOSE & THROAT IRRITATION.
MAY CAUSE NERVOUS SYSTEM DEPRESSION CHARACTERIZED BY THE FOLLOWING
PROGRESSIVE STEPS: HEADACHE, DIZZINESS, NAUSEA, STAGGERING GAIT,
CONFUSION, UNCONSCIOUSNESS. REPO RTS HAVE ASSOCIATED
REPEATED/PROLONGED OVEREXPOSURE TO SOLVENT W/PERMANENT
BRAIN/NERVOUS SYSTEM DAMAGE. SLIGHT ALKALINE.
Explanation of Carcinogenicity:DETECTABLE AMNTS OF CHEMICAL KNOWN TO
THE STATE OF CALIF. CAUSE CANCER &/OR REPRODUCTIVE HARM MAY BE
PRESENT IN PRODUCT.
Effects of Overexposure:MAY CAUSE IRRITATION OR BURNING OF THE EYES.
REPEATED OR PROLONGED LIQUID CONTACT MAY CAUSE SKIN IRRITATION WITH
DISCOMFORT AND DERMATITIS. INGESTION: GASTROINTESTINAL DISTRESS.
Medical Cond Aggravated by Exposure:UNKNOWN BUT UNLIKELY

First Aid

First Aid:INHALATION: REMOVE TO FRESH AIR. IF NOT BREATHING GIVE CPR.
EYES: IMMED FLUSH W/WATER FOR 15 MINUTES. CONSULT A PHYSICIAN.
SKIN: WASH EXPOSED SKIN WITH SOAP & WATER. IF IRRITATION OCCURS,
CONSULT A PH YSICIAN. INGESTION: GASTROINTESTINAL DISTRESS, CONSULT
A PHYSICIAN IMMED. DO NOT INDUCE VOMITING. IN ALL CASES, IF
SYMPTOMS PERSIST, CONSULT A PHYSICIAN.

Fire Fighting

Flash Point:201F,94C
Lower Limits:1.2 %
Upper Limits:23.5 %
Extinguishing Media:FOAM, CO2, DRY CHEMICAL, WATER FOG.
Fire Fighting Procedures:AVOID CONFINED SPACES. WEAR FULL PROTECTIVE
EQUIPMENT INCLUDING A POSITIVE PRESSURE NIOSH APPROVED
SELF-CONTAINED BREATHING APPARATUS.
Unusual Fire/Explosion Hazard:CLOSED CONTAINERS CAN BUILDUP PRESSURE &
EXPLODE EXPOSED TO EXTREME HEAT. WATER FROM FOG NOZZLES HELPFUL IN
COOLING CONTAINERS TO PREVENT PRESSURE BUILDUP.

Accidental Release

Spill Release Procedures:VENTILATE AREA. REMOVE SOURCES OF IGNITION.
PREVENT SKIN CONTACT & AVOID BREATHING OF VAPOR. CONFINE & REMOVE
WITH INERT ABSORBENT. PLACE IN NON-LEAKING CONTAINERS.

Handling

Handling and Storage Precautions:OBSERVE LABEL PRECAUTIONS. KEEP AWAY
FROM ALL HEAT TYPES. CLOSE CONTAINER TIGHTLY AFTER EACH USE. DON'T
STORE > 120F. STORE IN DRY WELL VENT AREA.
Other Precautions:AVOID UNNECESSARY CONTACT. DO NOT TAKE INTERNALLY.
USE WITH ADEQUATE VENTILATION. DON'T SAND, FLAME CUT, BRAZE, OR
WELD DRY COATING WITHOUT A NIOSH/MSHA APPROVED RESPIRATOR OR
SUFFICIENT VENTILATION. DON'T BREATH VAPORS OR MISTS.

Exposure Controls

Respiratory Protection:IF TLV/PEL LIMIT IS EXCEEDED WEAR A
VAPOR/PARTICULATE RESPIRATOR APPROVED NIOSH/MSHA FOR USE WITH
PAINTS SUCH AS A TC-23C DURING APPLICATION & UNTIL ALL VAPORS &
SPRAY MISTS ARE EXHAUSTED. FOLLOW MANU FACTURER'S DIRECTIONS FOR
RESPIRATOR USE
Ventilation:PROVIDE SUFFICIENT VENTILATION IN VOLUME AND PATTERN TO
KEEP CONTAMINANTS BELOW APPLICABLE OSHA REQUIREMENTS.
Protective Gloves:NEOPRENE GLOVES OR BETTER
Eye Protection:GOGGLES, SAFETY, FULL-FACE SHIELD
Other Protective Equipment:APRON, COVERALLS, OR WORK CLOTHES. EYE
WASHES & SAFETY SHOWERS MAY ALSO NEED TO BE PROVIDED.
Work Hygienic Practices:AS W/ALL CHEMICAL PRODUCTS, USE CARE IN
HANDLING. DON'T SMOKE/EAT W/O FIRST WASHING HANDS. LAUNDER CLOTHES
BEFORE REUSE.
Supplemental Safety and Health

Chemical Properties

HCC:N1
Boiling Pt:B.P. Text:BASIC H2O
Vapor Density:> AIR
Spec Gravity:1.2
Evaporation Rate & Reference:SLOWER THAN ETHER
Solubility in Water:MISCIBLE
Appearance and Odor:MILD SMELLING THICKENED LIQUID

Stability

Stability Indicator/Materials to Avoid:YES
NONE REASONABLY FORESEEABLE.
Stability Condition to Avoid:NONE REASONABLY FORESEEABLE.
Hazardous Decomposition Products:MAY PRODUCE FUMES WHEN HEATED TO
DECOMPOSITION. MAY RELEASE CARBON MONOXIDE, CARBON DIOXIDE, &
OXIDES OF NITROGEN.

Disposal

Waste Disposal Methods:DO NOT ALLOW MATERIAL TO CONTAMINATE GROUND
WATER SYSTEM. DISPOSE OF ABSORBED MATERIAL IN ACCORDNACE WITH ALL
LOCAL, STATE & FEDERAL REGULATIONS. DO NOT INCINERATE IN CLOSED
CONTAINERS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.