

BAY COUNTRY VINYL FLAT

MSDS Number

BRWWR

National Stock Number

8010-00F029685

Product Name

BAY COUNTRY VINYL FLAT

Manufacturer

BRUNING PAINT CO INC

Product Identification

Product ID: BAY COUNTRY VINYL FLAT

MSDS Date: 01/18/1990

FSC: 8010

NIIN: 00F029685

MSDS Number: BRWWR

Responsible Party

BRUNING PAINT CO INC

601 S HAVEN ST

BALTIMORE , MD 21224-4347

US

Emergency Phone: 301-342-3636AM/301-342-3641PM

Info Phone: 301-342-3636AM/301-342-3641PM

Cage: EO376

Contractor

KYANIZE PAINT

BALTIMORE, MD 21224

US

800-368-2076

Cage: 85520

Ingredients

ETHYLENE GLYCOL, GLYCOL

CAS: 107-21-1

RTECS: KW2975000

Fraction By Weight: 1.26%

ACGIH TLV: C 127 MG/CUM

EPA Report Quantity: 1 LB

DOT Report Quantity: 1 LB

SILICA DIOXIDE, CRYSTALLINE QUARTZ, SAND (GROUP 2A IARC)

CAS: 14808-60-7

RTECS: VV7330000

Fraction By Weight: 1.80%

OSHA PELSEE TABLE Z3

ACGIH TLV: 0.1 MG/M3 RDUST;9293

PIGMENT

11

RTECS: 9999999WG

0.769 LBS/GAL

RTECS: 9999999VO

Hazards

Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:YES OSHA:NO
Health Hazards Acute and Chronic:PROLONGED EXPOSURE TO SOLVENTS IS
FOUND TO CAUSE PERMANENT BRAIN & NERVOUS SYSTEM DAMAGE.
CRYSTALLINE SILICA MAY CAUSE SILICOSIS. EYES: IRRITATION.
Explanation of Carcinogenicity:SEE INGREDIENTS

First Aid

First Aid:EYES: FLUSH W/LUKE WARM WATER FOR 15 MINS. SKIN: FLUSH
W/PLENTY OF LUKE WARM WATER. REMOVE CONTAMINATED CLOTHING PROMPTLY.
INHALATION: REMOVE TO FRESH AIR. RESTORE BREATHING IF REQUIRED.
INGESTION: RI NSE MOUTH IMMEDIATELY. GIVE EXPOSED INDIVIDUAL 6-8 OZ
OF LIQUID. NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON.
DON'T INDUCE VOMITING. OBTAIN MEDICAL ATTENTION IN ALL CASES.

Fire Fighting

Flash Point Method:TCC
Extinguishing Media:CO2, DRY CHEMICAL, OR FOAM
Fire Fighting Procedures:WATER SPRAY MAY BE INEFFECTIVE. USE WATER TO
COOL CLOSED CONTAINERS TO PREVENT PRESSURE
BUILDUP/AUTOIGNITION/EXPLOSION W/HEAT. FOG NOZZLES ARE PREFERABLE.

Accidental Release

Spill Release Procedures:DON'T FLUSH TO SEWER, WATERSHED OR WATERWAY.

Handling

Handling and Storage Precautions:KEEP FROM FREEZING. DON'T STORE ABOVE
120F. DON'T TAKE INTERNALLY. CLOSE CONTAINER AFTER EACH USE.
Other Precautions:KEEP OUT OF REACH OF CHILDREN. INTENTIONAL MISUSE BY
DELIBERATELY CONCENTRATING & INHALING THE CONTENTS CAN BE HARMFUL
OR FATAL. DON'T BREATHE VAPORS OR SPRAY MIST.

Exposure Controls

Respiratory Protection:IN OUTDOOR OR OPEN AREAS USE NIOSH/MSHA APPROVED
MECHANICAL FILTER RESPIRATOR. IN RESTRICTED VENTILATION AREAS USE
NIOSH/MSHA APPROVED CHEMICAL-MECHANICAL FILTERS. IN CONFINED AREAS
USE NIOSH/MSHA AIR LINE TYPE RESPIRATOR OR HOODS.
Ventilation:PROVIDE GENERAL DILUTION OR LOCAL EXHAUST IN VOLUME &
PATTERN TO KEEP BELOW TLV.
Work Hygienic Practices:REMOVE/LAUNDER CONTAMINATED CLOTHING BEFORE
REUSE. WASH HANDS THOROUGHLY BEFORE EATING & USING WASHROOM.
Supplemental Safety and Health
PERCENT VOLATILE BY WEIGHT: 54.29 THIS PRODUCT CONTAINS PIGMENTS WHICH
MAY BECOME A DUST NUISANCE WHEN REMOVED BY BLASTING, SANDING, OR
GRINDING.

Chemical Properties

Boiling Pt:B.P. Text:212-490F
Vapor Pres:17

Vapor Density: >1
Evaporation Rate & Reference: SLOWER THAN BU AC
Percent Volatiles by Volume: 70.02%

Stability

Stability Indicator/Materials to Avoid: YES
STRONG ACIDS
Stability Condition to Avoid: FREEZING, TEMPERATURES >120F
Hazardous Decomposition Products: CO, CO₂ & OXIDES OF NITROGEN

Disposal

Waste Disposal Methods: DISPOSE OF IN ACCORDANCE W/LOCAL, STATE, & FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.