

215 CROWN LATEX ARCHITECTURAL COATING

MSDS Number

BRYLM

National Stock Number

8010-00F028747

Product Name

215 CROWN LATEX ARCHITECTURAL COATING

Manufacturer

O'BRIEN CORP

Product Identification

Product ID:215 CROWN LATEX ARCHITECTURAL COATING

MSDS Date:08/01/1990

FSC:8010

NIIN:00F028747

MSDS Number: BRYLM

Responsible Party

O'BRIEN CORPORATION

450 E GRAND AVENUE

SOUTH SAN FRANCISCO , CA 94080-6207

US

Emergency Phone: 800-338-8084

Info Phone: 800-338-8084

Cage: 85207

Contractor

O'BRIEN CORPORATION, FULLER O'BRIEN PAINTS

SOUTH SAN FRANCISCO, CA 94080-6207

US

Cage: 85207

Ingredients

CALCIUM CARBONATE, DOMOLITE, LIMESTONE, WHITING *97-2*

CAS: 1317-65-3

RTECS: EV9580000

Fraction By Weight: 5%

OSHA PEL15 MG/M3

ACGIH TLV: 10 MG/CUM TOTAL DUST

CRYSTALLINE-QUARTZ SILICA, SILICA DUST (SUSPECTED HUMAN

CAS: 14808-60-7

RTECS: VV7330000

Fraction By Weight:

OSHA PEL10 MG/CUM %RESP SIO2

ACGIH TLV: 0.1 MG/CUM RESP DUST

SILICA CRYSTALLINE, SILICA (CRISTOBALITE) (SUSPECTED HUMAN

CAS: 14464-46-1

RTECS: VV7325000

Fraction By Weight:

ACGIH TLV: 0.05 MG/CUM

ETHYLENE GLYCOL *97-2*

CAS: 107-21-1

RTECS: KW2975000

Fraction By Weight:

OSHA PEL50 PPM

ACGIH TLV: C 127 MG/CUM

EPA Report Quantity: 1 LB

DOT Report Quantity: 1 LB

ETHYLENE OXIDE (SUSP HUMAN CARCINOGEN BY ACGIH, IARC, SUSP

CAS: 75-21-8

RTECS: KX2450000

Fraction By Weight:

ACGIH TLV: 1.8 MG/CUM (A2)

EPA Report Quantity: 10 LBS

DOT Report Quantity: 10 LBS

FORMALDEHYDE, FORMALIN (SUSPECTED HUMAN CARCINOGEN BY IARC;

CAS: 50-00-0

RTECS: LP8925000

Fraction By Weight:

ACGIH TLV: 0.37 MG/CUM IC (2A)

EPA Report Quantity: 100 LBS

DOT Report Quantity: 100 LBS

1,2-PROPANEDIOL (PROPYLENE GLYCOL)

CAS: 57-55-6

RTECS: TY2000000

Fraction By Weight:

AMORPHOUS SILICA GEL, SILICON DIOXIDE *97-2*

CAS: 7631-86-9

Fraction By Weight: 10%

PROPANOIC ACID, 2-METHYL, MONOESTER

CAS: 25265-77-4

RTECS: UF6000000

Fraction By Weight:

TITANIUM DIOXIDE, TITANIUM OXIDE (SUSPECTED ANIMAL

CAS: 13463-67-7

RTECS: XR2275000

Fraction By Weight: 15-25%

OSHA PEL15 MG/CUM

ACGIH TLV: 10 MG/CUM (DUST)

VINYL ACETATE

CAS: 108-05-4

RTECS: AK0875000

Fraction By Weight:

ACGIH TLV: 35 MG/CUM

EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

2-(2-BUTOXYETHYOXY)-ETHANOL, DIETHYLENE GLYCOL MONOBUTYL

CAS: 112-34-5

RTECS: KJ9100000

Fraction By Weight:

RTECS: 9999999VO

Hazards

LD50 LC50 Mixture:ORAL LD50 (RAT): 9500 MG/KG (SEE SUPP)

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:YES

Health Hazards Acute and Chronic:PRIMARY IRRITANT. HAZARDS OF INDIVIDUAL INGREDIENTS; EYE: IRIDOCYCLITIS, BURNS, POSSIBLE PERMANENT DAMAGE. SKIN: BURNS, DERMATITIS. INHALATION: LUNG INJURY, CNS DEPRESSION, SILICOSIS, PNEUMONIA, EDEMA . INGESTION: CNS EFFECTS, GI TRACT IRRITATION. ADVERSE REPRODUCTIVE EFFECTS & CHROMOSOME DAMAGE. (SEE SUPP)

Explanation of Carcinogenicity:SEE INGREDIENTS

Effects of Overexposure:IRRITATION, ECZEMA-LIKE CONDITION, DEFATTING, HEADACHE, NAUSEA, VOMITING, DIFFICULTY BREATHING, DIZZINESS, COUGH, CYANOSIS, DROWSINESS, PAIN, DIARRHEA, UNCONSCIOUSNESS

Medical Cond Aggravated by Exposure:LUNG DISEASE, SKIN & RESPIRATORY CONDITIONS.

First Aid

First Aid:INGESTION: DRINK 2 GLASSES OF WATER & INDUCE VOMITING BY PLACING FINGER AT BACK OF THROAT. NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON. INHALATION: REMOVE TO FRESH AIR. RESTORE BREATHING. EY ES: FLUSH W/COOL WATER FOR 15 MINS. SKIN: WASH THOROUGHLY W/SOAP & WATER. OBTAIN MEDICAL ATTENTION IN ALL CASES.

Fire Fighting

Flash Point:>200F

Unusual Fire/Explosion Hazard:CLOSED CONTAINERS MAY EXPLODE WHEN EXPOSED TO EXTREME HEAT.

Accidental Release

Spill Release Procedures:SOAK UP & REMOVE W/INERT ABSORBENT MATERIAL. PROVIDE ADEQUATE VENTILATION.

Exposure Controls

Respiratory Protection:USE APPROVED MECHANICAL RESPIRATOR/MASK TO AVOID BREATHING SPRAY MISTS.

Ventilation:PROVIDE SUFFICIENT VENTILATION IN VOLUME & PATTERN TO KEEP BELOW TLV.

Protective Gloves:AS REQUIRED

Eye Protection:GOGGLES, SAFETY GLASSES W/SIDE SHIELDS

Other Protective Equipment:PROTECTIVE OVERALLS

Work Hygienic Practices:REMOVE/LAUNDER CONTAMINATED CLOTHING BEFORE REUSE. DISCARD CONTAMINATED SHOES.

Supplemental Safety and Health

THIS IS A LATEX PAINT. PRIMARY HEALTH HAZARD IS POSSIBLE IRRITATION TO EYES & SKIN. HEALTH HAZARDS ARE FOR EACH INGREDIENT. LD50 INFORMATION IS FOR TITANIUM DIOXIDE.

Chemical Properties

Boiling Pt:B.P. Text:212F

Vapor Density:Evaporation Rate & Reference:SLOWER THAN ETHER

Percent Volatiles by Volume:65

Stability

Stability Indicator/Materials to Avoid:YES

Stability Condition to Avoid:EXTREME HEAT

Hazardous Decomposition Products:CO, CO2, NITROGEN OXIDE

Disposal

Waste Disposal Methods:DISPOSE OF IAW/FEDERAL, STATE & LOCAL REGULATIONS. DON'T INCINERATE IN CLOSED CONTAINERS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.