

LIQUID EPOXY COATING SURE-POXY HI-BILD (SUPP DATA)

MSDS Number

BSBFT

National Stock Number

8030-00N040002

Product Name

LIQUID EPOXY COATING SURE-POXY HI-BILD (SUPP DATA)

Manufacturer

KAUFMAN PRODUCTS INC

Product Identification

Product ID:LIQUID EPOXY COATING SURE-POXY HI-BILD (SUPP DATA)

MSDS Date:04/01/1990

FSC:8030

NIIN:00N040002

Kit Part:Y

MSDS Number: BSBFT

Responsible Party

KAUFMAN PRODUCTS INC

3811 CURTIS AVE

BALTIMORE , MD 21226

US

Emergency Phone: 301-947-8600;800-424-9300(CHEMTREC)

Info Phone: 301-947-8600

Cage: KAUFM

Contractor

KAUFMAN PRODUCTS INC

BALTIMORE, MD 21226

US

301-947-8600

Cage: KAUFM

Ingredients

5 PPM MAX-TYPICALLY 1 PPM).

EPICHLOROHYDRIN BIS-PHENOL A; (BLEND OF LIQ EPOXY RESINS

CAS: 25068-38-6

RTECS: SL6475000

ACGIH TLV: 500 PPM

Hazards

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:IRRITATION TO SKIN & ESPECIALLY EYES.

COULD CAUSE A RASH, BURN OR AN ASTHMATIC TYPE RESPONSE IN

SENSITIZED PERSONS. POSSIBLE PERMANENT EYE INJURY.

Explanation of Carcinogenicity:NOT RELEVANT.

Effects of Overexposure:SEE HEALTH HAZARDS.

Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

First Aid

First Aid:INHAL: SUPPLY FRESH AIR. EYES: FLUSH W/COPIOUS AMTS OF WATER FOR AT LEAST 15 MINUTES. CALL MD. SKIN: REMOVE CONTAMD CLTHG. WASH WITH SOAP & WATER FOR AT LEAST 15 MINS. INGEST: DO NOT INDUCE VOMIT. GIV E LARGE AMOUNTS OF WATER & AT LEAST 1 OZ OF VINEGAR IN EQUAL AMOUNTS OF WATER. CALL MD IMMEDIATELY .

Fire Fighting

Flash Point:480F,249C

Extinguishing Media:FOAM, DRY CHEMICAL, WATER.

Fire Fighting Procedures:WEAR NIOSH/MSHA APPROVED SCBA & FULL PROTECTIVE EQUIPMENT.

Unusual Fire/Explosion Hazard:AVOID CONTACT WITH LIQUID AND BREATHING OF SMOKE.

Accidental Release

Spill Release Procedures:STOP LEAK. CLEAN WITH CLOTH OR ABSORBENT.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

Handling

Handling and Storage Precautions:STORE IN COOL PLACE AWAY FROM SPARKS & FLAME.

Other Precautions:KEEP OUT OF THE REACH OF CHILDREN.

Exposure Controls

Respiratory Protection:NIOSH/MSHA APPROVED ORGANIC RESPIRATOR.

Ventilation:LOCAL EXHAUST RECOMMENDED.

Protective Gloves:BUTYL OR RUBBER GLOVES.

Eye Protection:ANSI APRV CHEM WORKERS GOGGLES .

Other Protective Equipment:APRON & BOOTS.

Work Hygienic Practices:NONE SPECIFIED BY MANUFACTURER.

Supplemental Safety and Health

TRADENAME/PART #: ORANGE COMP A, 743.

Chemical Properties

Vapor Density:HVR/AIR

Spec Gravity:1.13

Evaporation Rate & Reference:SLOWER THAN ETHER

Solubility in Water:NONE

Appearance and Odor:CLEAR LIQUID OF LOW VISCOSITY CHARACTERISTIC ODOR.

Percent Volatiles by Volume:1 MAX

Stability

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS SUCH AS ACIDS & BASES.

Stability Condition to Avoid:NONE SPECIFIED BY MANUFACTURER.

Hazardous Decomposition Products:CARBON MONOXIDE, ALDEHYDES & OTHER ORGANICS.

Disposal

Waste Disposal Methods:GOVERNMENT APPROVED CHEMICAL DISPOSAL OR LANDFILL. DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE & FEDERAL REGULATIONS .

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.