

## **ALL ACRYLIC VYNCRYL WHT & WTB, 070-0001**

### **MSDS Number**

BSBVP

### **National Stock Number**

8010-00N043893

### **Product Name**

ALL ACRYLIC VYNCRYL WHT & WTB, 070-0001

### **Manufacturer**

DECRATREND PAINT CORP

### **Product Identification**

Product ID:ALL ACRYLIC VYNCRYL WHT & WTB, 070-0001

MSDS Date:01/01/1992

FSC:8010

NIIN:00N043893

MSDS Number: BSBVP

### **Responsible Party**

DECRATREND PAINT CORP

251 MASON WAY

CITY OF INDUSTRY , CA 91746

US

Emergency Phone: 818-333-4592

Info Phone: 818-333-4592

Cage: 42590

### **Contractor**

DECRATREND PAINT CORP

CITY OF INDUSTRY, CA 91746

US

818-333-4592

Cage: 42590

### **Ingredients**

0.1@68F

CAS: 107-21-1

RTECS: KW2975000

Fraction By Weight: 2.45%

OSHA PEL50 PPM, C

ACGIH TLV: 50 PPM,VAPOR, C

EPA Report Quantity: 1 LB

DOT Report Quantity: 1 LB

DIATOMACEOUS EARTH, FLUX CALCINED; (DIATEMACEOUS EARTH)

CAS: 68855-54-9

Fraction By Weight:

OSHA PELN/K .

ACGIH TLV: N/K .

CLAY (KAOLIN); (CALCINED ALUMINUM SILICATE)

CAS: 1332-58-7

RTECS: GF1670500

Fraction By Weight: 10%

OSHA PEL10 MG/M3 TDUST

ACGIH TLV: 2 MG/M3 TDUST

17@68F

Fraction By Weight: 20%

OSHA PELN/K

ACGIH TLV: N/K

17@68F

Fraction By Weight: 10%

OSHA PELN/K

ACGIH TLV: N/K

PROPIONIC ACID, 2-METHYL-, MONOESTER

CAS: 25265-77-4

RTECS: UF6000000

Fraction By Weight:

OSHA PELN/K

ACGIH TLV: N/K

0.97 LB/GL (117 G/L)

RTECS: 9999999VO

OSHA PELN/K

ACGIH TLV: N/K

## Hazards

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:ACUTE: MAY CAUSE IRRIT TO SKIN, EYES, & INTESTINAL SYS. CHRONIC: NONE KNOWN. INHAL: ADVERSE HLTH EFTS FROM VAPS/SPRAY MISTS IN POORLY VENTILATED AREAS MAY INCLUDE IRRIT OF MUC MEMB OF NOSE, THROAT, & RESP TRACT & SYMPS OF HDCH & NAUS. EYES: IN DIRECT CONT, MAY CAUSE IRRIT. SKIN: PRLNGD & RPTD CONT W/ (EFTS OF OVEREXP)

Explanation of Carcinogenicity:NOT RELEVANT

Effects of Overexposure:HLTH HAZ: PROD MAY CAUSE SKIN IRRIT. SKIN

ABSORP: REDNESS, DRYING OF SKIN, OR OTHER SIGNS OF IRRITATION OR CONTACT DERMATITIS. INGEST: CAN CAUSE GASTROINTESTINAL IRRITATION, NAUSEA, VOMITING AND DIARR HEA.

Medical Cond Aggravated by Exposure:NONE.

## First Aid

First Aid: INHAL: REMOVE TO FRESH AIR. EYES: FLUSH IMMEDIATELY WITH LARGE AMOUNTS OF WATER FOR AT LEAST 15 MINUTES. TAKE TO A PHYSICIAN FOR MEDICAL ATTENTION. SKIN: REMOVE WITH SOAP AND WATER. REMOVE ALL CONTAMINATED CLOTHING. INGEST: DRINK 1-2 GLASSES OF WATER TO DILUTE. DO NOT INDUCE VOMITING. CONSULT A PHYSICIAN OR POISON CONTROL CENTER IMMEDIATELY. TREAT SYMPTOMATICALLY.

## Fire Fighting

Flash Point Method: PMCC

Flash Point: 241°F, 116°C

Lower Limits: 0.6%

Upper Limits: 4.2%

Extinguishing Media: FOAM, CARBON DIOXIDE, DRY CHEMICAL, WATER FOG.

Fire Fighting Procedures: WEAR NIOSH/MSHA APPROVED SCBA AND FULL PROTECTIVE EQUIPMENT. COOL CONTAINERS WITH WATER SPRAY.

Unusual Fire/Explosion Hazard: NONE SPECIFIED BY MANUFACTURER.

## Accidental Release

Spill Release Procedures: DIKE, CONTAIN, OR ABSORB WITH INERT MATERIAL (I.E. SAND, VERMICULITE, ETC.) TRANSFER TO CONTAINERS FOR RECOVERY OR DISPOSAL. PREVENT RUNOFF INTO SEWERS, STREAMS, OR OTHER BODIES OF WATER.

Neutralizing Agent: NONE SPECIFIED BY MANUFACTURER.

## Handling

Handling and Storage Precautions: DO NOT EXPOSE TO EXTREMES IN TEMPERATURES. AVOID EXPOSURE TO HIGH TEMPERATURES. DO NOT ALLOW TO FREEZE.

Other Precautions: DO NOT TAKE INTERNALLY. AVOID PROLONGED OR REPEATED EXPOSURE TO LEVELS ABOVE TLV.

## Exposure Controls

Respiratory Protection: NOT NORMALLY REQUIRED. IF TLV IS EXCEEDED USE NIOSH/MSHA APPROVED ORGANIC VAPOR AND MIST PROTECTION.

Ventilation: USE ADEQUATE MECHANICAL (GENERAL &/OR LOCAL) VENTILATION TO MAINTAIN EXPOSURE BELOW TLV.

Protective Gloves: WEAR RESISTANT GLOVES SUCH AS POLYETHYLENE.

Eye Protection: ANSI APPROVED CHEMICAL SAFETY GOGGLES.

Other Protective Equipment: WEAR IMPERMEABLE CLOTHING. FURNISH EYE WASH STATIONS.

Work Hygienic Practices: WASH HANDS BEFORE EATING OR USING RESTROOMS. REMOVE AND WASH CONTAMINATED CLOTHING BEFORE REUSE.

Supplemental Safety and Health  
NONE SPECIFIED BY MANUFACTURER.

## Chemical Properties

HCC: N1

Boiling Pt: B.P. Text: >212°F, >100°C

Vapor Pres: SEE INGREDIENTS

Vapor Density: LTR/AIR

Spec Gravity: 1.3 (H<sub>2</sub>O=1)

Evaporation Rate & Reference: SLOWER THAN ETHER

Solubility in Water: COMPLETELY

Appearance and Odor: TYPICAL FOR WATER BASED LATEX COATING

## Stability

Stability Indicator/Materials to Avoid: YES

AVOID CONTACT WITH STRONG OXIDIZING AGENTS.

Stability Condition to Avoid: NONE.

Hazardous Decomposition Products: MAY FORM TOXIC MATERIALS, CARBON DIOXIDE, CARBON MONOXIDE, ETC.

## Disposal

Waste Disposal Methods: DISPOSE IN/ACCORDANCE WITH ALL LOCAL, STATE, OR FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.