

## **WET WALL GROUT WHITE**

### **MSDS Number**

BSBVS

### **National Stock Number**

5610-00N043896

### **Product Name**

WET WALL GROUT WHITE

### **Manufacturer**

W R BONSAL CO

### **Product Identification**

Product ID:WET WALL GROUT WHITE

MSDS Date:01/01/1990

FSC:5610

NIIN:00N043896

MSDS Number: BSBVS

### **Responsible Party**

W R BONSAL CO

CHARLOTTE , NC 28224

US

Emergency Phone: 704-525-1621

Info Phone: 704-525-1621

Cage: 3R363

### **Contractor**

W R BONSAL CO

CHARLOTTE, NC 28224

US

704-525-1621

Cage: 3R363

### **Ingredients**

SILICATE, PORTLAND CEMENT

CAS: 65997-15-1

RTECS: VV8770000

Fraction By Weight:

OSHA PEL10 MG/M3 TDUST

ACGIH TLV: 10 MG/M3 TDUST

CALCIUM CARBONATE

CAS: 1317-65-3

RTECS: EV9580000

Fraction By Weight:

OSHA PEL15 MG/M3 TDUST

ACGIH TLV: 10 MG/M3 TDUST

CALCIUM HYDROXIDE

CAS: 1305-62-0

RTECS: EW2800000

Fraction By Weight:

OSHA PEL5 MG/M3

ACGIH TLV: 5 MG/M3

TITANIUM OXIDE; (TITANIUM DIOXIDE)

CAS: 13463-67-7

RTECS: XR2275000

Fraction By Weight:

OSHA PEL10 MG/M3 TDUST

ACGIH TLV: 10 MG/M3 TDUST

## Hazards

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.

Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:EXCESS EXPOSURE BY INHALATION OVER AN EXTENDED PERIOD OF TIME MAY RESULT IN THE DEVELOPMENT OF PULMONARY DISEASES INCLUDING PNEUMOCONIOSIS AND SILICOSIS. PROLONGED CONTACT MAY CAUSE SKIN IRRITATION OR DERMATITIS. SKIN AND EYE IRRITANT.

Explanation of Carcinogenicity:NOT RELEVANT

Effects of Overexposure:SEE HEALTH HAZARDS.

Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

## First Aid

First Aid:INHAL: REMOVE FROM EXPOSURE. IF NOT BREATHING, GIVE ARTF RESP, IF BREATHING DIFFICULT, GIVE OXYGEN, CONSULT A PHYSICIAN.  
EYE: FLUSH THORO WITH WATER FOR AT LEAST 15 MINUTES. CONSULT A PHYSICIAN. SKIN: WASH THORO WITH SOAP AND WATER. INGEST: CALL MD IMMED .

## Fire Fighting

Flash Point:NON FLAMMABLE

Extinguishing Media:WATER.

Fire Fighting Procedures:WEAR NIOSH/MSHA APPROVED SCBA AND FULL PROTECTIVE EQUIPMENT .

Unusual Fire/Explosion Hazard:NONE.

## Accidental Release

Spill Release Procedures:USE PERSONAL PROTECTIVE EQUIPMENT TO PREVENT DUST EXPOSURES AND PROTECT AGAINST ALKALINE BURNS/IRRITATION.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

## Handling

Handling and Storage Precautions:STORE IN MANNER TO PREVENT CONTACT WITH STRONG ACIDS. AVOID CONTACT W/WATER TO PRESERVE PRODUCT.

Other Precautions:NONE.

## Exposure Controls

Respiratory Protection:NIOSH/MSHA APPROVED RESPIRATOR FOR PROTECTION AGAINST SILICA AND NUISANCE DUSTS.

Ventilation:LOCAL EXHAUST: YES.

Protective Gloves:RUBBER, PVC/NEOPRENE.

Eye Protection:ANSI APPROVED CHEM SFTY GOGG .

Other Protective Equipment:RUBBER BOOTS, ARM SLEEVES AND APRONS WHEN NECESSARY TO PREVENT SKIN CONTACT.

Work Hygienic Practices:NONE SPECIFIED BY MANUFACTURER.

Supplemental Safety and Health  
NONE SPECIFIED BY MANUFACTURER.

## Chemical Properties

HCC:B3  
Solubility in Water:SLIGHTLY  
Appearance and Odor:DRY, WHITE POWDER, NO ODOR

## Stability

Stability Indicator/Materials to Avoid:YES  
HIGHLY ALKALINE. STRONG ACIDS MAY CAUSE VIOLENT, EXOTHERMIC REACTION,  
EVOLVE TOXIC GASES/VAPS, DEPENDING ON TYPE ACID.

## Disposal

Waste Disposal Methods:DISPOSE OF I/A/W FEDERAL, STATE AND LOCAL  
REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.